### Planning Commission Radnor Township Wayne, Delaware County, Pennsylvania

Monday June 2, 2014 7:00 P.M.

### Agenda

Minutes of the May 5, 2014 meeting

613 W. Lancaster Avenue

Final

2013-D-13

Remove existing bar/restaurant and construct new restaurant with parking

695 Clyde Road

Preliminary

2014-D-05

Ithan Elementary School

Expand existing building by adding two classrooms and associated walkways

651 W. Wayne Avenue

Preliminary

2014-D-06

Wayne Elementary School

Construct an addition for new classrooms and other facilities including new walkways and associated improvements

Ordinance No. 2014-03 An ordinance of Radnor Township, Delaware County, Pennsylvania, amending Chapter 245, Stormwater management, of the Radnor Code, by amending certain provisions regarding purpose, and existing conditions concerning calculation methodology.

ZHB Discussion:

**APPEAL #2916** 

The applicant, Radnor Chester Road Investment, L. P. & 252 RCR Investments, L.P., property located at 240-252 Radnor Chester Road and split zoned PB and R1 seeks variances from the flowing sections of the Zoning Code (1) 280-60(B) relating to Building Area; (2) 280-60(C) relating to setback along a 50' by 50' parcel owned by the Township; and (3) 280-61(D) relating to buffer along the 50' by 50' Township owned parcel. Applicant seeks a special exception under 280-101(A)(1), a variance from the cited sections, or contends that it is permitted by right or as a decrease in existing non-conformity from the following sections of the Zoning Code: (1)280-60(C) regarding continuation of the existing Rear Yard setback on the rear property line in common with Radnor Financial Center for the parking structure and (2) 280-4 regarding continuation of the existing size of parking spaces in parking structure. In addition, Applicant seeks any other zoning or alternative relief required pursuant to Plans presented with Application.

### Public Participation

Next Special Planning Commission Meeting

Tuesday, June 17, 2014 7 PM

Next Regular Planning Commission Meeting

Monday, July 7, 20147 PM

### Radnor Township Planning Commission Minutes of the Meeting of May 5, 2014 301 Iven Ave., Wayne, PA

Co-Chair Skip Kunda called the meeting to order at 7 PM with the following Commission members present: Kathy Bogosian, Regina Majercak, Doug McCone, Elizabeth Springer and Susan Stern. Attendance included: Roger Phillips, PE, Township Engineer; Amy Kaminski, PE, Township Traffic Engineer; John Rice, Esq., and Stephen Norcini, PE, Director of Public Works. Julia Hurle, Steve Cooper and John Lord were absent.

### Minutes of the Meetings of April 8, 2014

Susan Stern moved to approve the minutes. Seconded by Doug McCone, the motion passed.

ZHB Discussion – APPEAL # 2914 – The applicant, Cabrini College, property located at 610 King of Prussia Road and zoned PI, seeks a dimensional variance to Section 280-70.B of the Radnor Township Zoning Code regarding building length. The applicant desires to expand the existing Dixon Athletic Center.

Joanne Semeister, Esq. appeared with several of Cabrini's Administrative Staff. Robert Lambert, PE presented a power point describing the site including items that were approved on the Preliminary Plan and the proposed increase in length to the Dixon Center.

Susan Stern questioned the proposed additional uses and the possible requirement for additional parking. Skip Kunda questioned if this amended plan would have to comply with the new stormwater ordinance. Regina Majercak would like to see the applicant responsible for complying with the current stormwater ordinance when it goes to final and wants to see parking adequately addressed.

Regina Majercak moved to recommend that the zoning relief request be granted conditioned upon meeting the stormwater ordinance in place at the final plan approval as well as providing parking for the additional space that's new to this plan. Seconded by Doug McCone, the motion passed.

### Delaware County Act 537 Sewage Facilities Plan Update Eastern Service Area

Steve Norcini described the Act 537 which is submitted quite often in the Engineering Department for properties that transfer from septic to public sewer. This Act affects all of Delaware County and they are looking to get all of the municipalities on board to move forward. All sewage flows from the surrounding area move downstream through Haverford, Springfield and eventually ends up at Philadelphia. If flows are reduced to Philadelphia and the treatment plants, the costs and fees that the Township has to pay are reduced. Radnor is the largest component in the RHM (Radnor Haverford Marple) Sewer Authority. One way of finding inadequate laterals would be to institute inspections of laterals at the time of a property transfer. Cracked lines would have to be repaired which could in turn reduce the cost to the township due to the reduction in flows.

Steve Norcini recommends that inflow and infiltration (I & I) be instituted and he will recommend the same to the Board of Commissioners. A plan could be instituted to begin inspecting on a pro-active basis in addition to checking laterals during the transfer of real estate process. DEP is a driving force in aggressive elimination of I & I.

Susan Stern moved to accept the County's Act 537 Plan with the option that the Township moves forward in reducing the I & I. Seconded by Kathy Bogosian, the motion passed.

Public Comment - None

Regina Majercak announced that on Thursday, May 8<sup>th</sup> at 7 PM., the stormwater advisory committee would be meeting at the willows cottage. This meeting is open to the public.

Respectfully submitted,

Suzan Jones



### Excellence Delivered As Promised

### **MEMORANDUM**

Date: May 28, 2014

To: Radnor Township Planning Commission

From: Roger Phillips, PE

cc: Stephen Norcini, P.E. - Director of Public Works

Kevin W. Kochanski, RLA, CZO - Director of Community Development

Peter Nelson, Esq. – Grim, Biehn, and Thatcher Amy B. Kaminski, P.E. – Gilmore & Associates, Inc. Suzan Jones – Radnor Township Engineering Department

William Miller – Radnor Township Codes Official

Ray Daly - Radnor Township Codes Official

RE: 613 W Lancaster Avenue

Eagle Green, LP - Applicant

Date Accepted:

May 5, 2014

90 Day Expiration:

August 3, 2014

Gannett Fleming, Inc. has completed a review of the 613W. Lancaster Avenue Final Land Development Plan for compliance with the Radnor Township Code. The existing property is located in the C-2 zoning district and contains a 1,881 s.f. restaurant/bar and parking. The applicant is proposing to remove the existing building and construct a 2,800 s.f. restaurant.

This Land Development Application is subject to Zoning, Subdivision and Land Development, Stormwater Management, and other applicable codes of the Township of Radnor.

Plans Prepared By:

Site Engineering Concepts

Dated:

12/02/2013, last revised 04/30/2014

The Board of Commissioners approved the preliminary plan at their April 7, 2014 meeting. The following modifications to the subdivision and land development ordinance were approved by the Board of Commissioners preliminary plan resolution on April 7, 2014:

- a. §255.29.A (1) as to parking aisle dimensions and parking stall dimensions.
- b. §255.29.A (7) as to required off street parking spaces.
- c. §255.29.B (1) as to parking area tree planting.

### **Gannett Fleming**

The following items must be addressed for final approval:

### I Zoning Ordinance Review

- 1. The following items are existing non conformities, that the applicant intends to continue with the proposed project:
  - §280-52.E Rear Yards There shall be a rear yard of each lot of not less than 35 feet. The existing rear yard setback is 33.47 feet and the proposed rear yard setback is 34.4 feet.
  - §280-52.G Impervious Lot Coverage Not more than 70% of the lot maybe occupies by impervious surfaces. The existing conditions are 77.71% impervious and the proposed conditions are 71.41% impervious.
  - §280-4 Parking Space An outdoor space or garage space used for parking motor vehicles, which shall measure not less than nine feet six inches by 20 feet, accessible from a street, alley or driveway and surfaced with a Township approved durable dustproof all weather surface. The existing parking spaces are 7.8' 9.0' x 15'.3" 17'.0". The proposed parking spaces are 9' x 17' and the proposed Handicapped spaces are 8' x 17' with an aisle.

### II. Stormwater Management

- A general note shall be added to the plans indicating that a grading plan and erosion sediment
  and control plans will be submitted and approved prior to issuing any building permits. Any
  revisions to the size or location of the individual structures or other features will be
  addressed at that time, and a final approval of the stormwater management plan will be
  required as part of the Grading Permit process.
- 2. §245-18.S Since the applicant intends to meet the stormwater management ordinance criteria through off site stormwater management measures, an agreement with the adjacent property should be provided in order to maintain stormwater controls without future modifications.

### III General Comments

- Sewage Facilities Planning must be addressed for the increase in wastewater discharge. A
  planning module exemption form will be completed for any increase in sewage flow due to
  the building expansion. The applicant has indicated in the response letter dated May 1, 2014
  that a planning module or exemption request has been submitted. As of the date of this
  letter, we have not been provided with any such submission.
- 2. A Highway Occupancy Permit must be prepared for the modification to the existing driveway and curbing along Lancaster Avenue. The applicant has indicated they are in the process of submitting a Highway Occupancy Permit. A copy of the permit application must be submitted.



### **Gannett Fleming**

- 3. All existing and proposed utility connections must be shown on the plans. The applicant has indicated that this will be provided on the permit plans once the architectural plans are further developed.
- 4. An easement has been shown on the plan for the construction of the parking island located on the adjacent parcel. The easement shall include a requirement that the parking island cannot be altered or removed without the written approval of the Radnor Township Board of Commissioners. A copy of the easement description must be submitted for review.

Should the Planning Commission consider recommending approval of this project, we recommend that the recommendation be conditioned on requiring the applicant to satisfactorily address the above comments.

If you have any questions or require any additional information, please contact me.

Very truly yours,

GANNETT FLEMING, INC.

Roger A. Phillips, P.E. Senior Project Manager



### GILMORE & ASSOCIATES, INC.

Engineering & Consulting Services

### **MEMORANDUM**

Date:

May 23, 2014

To:

Steve Norcini, P.E.

Radnor Township Public Works Director

From:

Damon Drummond, P.E., PTOE G&A Senior Transportation Engineer

cc:

Roger Phillips, P.E.

Gannett Fleming, Inc., Senior Project Manager

Amy Kaminski, P.E., PTOE

**G&A** Department Manager of Transportation

Reference:

613 W. Lancaster Avenue TMP No. 36-01-00274-00

Radnor Township Application No. 2013-D-13 Preliminary/Final Land Development Review

G&A Job #13-12043

Pursuant to your request, Gilmore & Associates, Inc. (G&A) has completed a transportation review of the above referenced Final Land Development Plans for 613 W. Lancaster Avenue Road. G&A offers the following for Radnor Township's consideration:

### A. PROJECT DESCRIPTION

The applicant intends to demolish the existing 1,881 s.f. end building (Cooz Corner) and construct a 2,800 s.f. restaurant in its place. In addition, the applicant proposes to redesign the parking area and its access to Lancaster Pike, US Route 30. The existing parking area provides parking for the existing building and four other attached businesses. Per the application, the applicant requests a waiver for section §255-14 for developing preliminary plans.

### B. REVIEWED MATERIALS

- 613 W. Lancaster Avenue Road Final Land Development Plans (7 sheets), dated January 27, 2014 last revised April 30, 2014 prepared by Site Engineering Concepts, LLC., prepared for Eagle Green LP.
- Submission letter prepared by Site Engineering Concepts, LLC, dated January 27, 2014, responding to Gilmore & Associates, Inc. comment letter, dated January 6, 2014.

### C. REVIEW COMMENTS:

Gilmore & Associates, Inc. (G&A) January 6, 2014 letter including, Site Engineering (SE) responses and G&A follow up discussions:

- §255.20.B(5)(c)[2]: A limited Traffic Impact Analysis should be prepared to analyze the PM and Saturday peak hours along with the existing traffic counts and proposed trip generation of the new restaurant. The study should focus on the traffic operations at all accesses to Sugartown Road, Lancaster Avenue and the intersection of Sugartown Road and Lancaster Avenue.
  - **SE Response**: The applicant requests the Board of Commissioners, at its discretion, not require this study. 255.20.B(5)(c)[1][b] of the Radnor Township code only requires traffic studies for commercial sites exceeding 50,000 sf, this site proposes 2,800 sf. In addition, the square footage of commercial space and number of parking spaces are reduced by this application.
  - **G&A follow up:** A study of the intersection of Lancaster Avenue and Sugartown Road (PM and Saturday Peak Hours) would provide useful information regarding potential turn restrictions for accesses to both Lancaster Avenue and Sugartown Road/Old Eagle School Road. In addition, five (5) years of historical crash records (both reportable and non-reportable) would provide additional information regarding the turn maneuvers and parking maneuvers for the onstreet diagonal parking spaces located along Lancaster Avenue, in front of the site.
  - **SE Response:** The historical crash records have been provided and per further correspondence the study is no longer required.
  - **G&A follow up**: Based on the traffic support data provided we support a waiver for the township's traffic impact analysis requirement.

### 2. §255-29.A.(1):

- a. Parking stalls are required to be a minimum 9.5-foot wide by 20-foot length. The plan indicates the existing parking dimensions do not meet the current SALDO requirements (various widths from 7.8 feet and lengths from 15.3 feet). With the redesign of the parking area, we recommend all parking stalls meet the current 9.5 feet wide by 20 feet in length as required by SALDO.
- **SE Response**: As approved by the Township Zoning Officer and discussed with the planning commission, the applicant proposes to reduce the existing non-conformity.
  - b. Parking aisles must include a minimum 22-foot wide two-way aisle width; the proposed plans do not meet this requirement.
- **SE Response**: The applicant has improved the existing non-conformity and proposes 21' aisles.

Steve Norcini, P.E. 613 W. Lancaster Avenue TMP No. 36-01-00274-00 May 23, 2014

**G&A follow up:** The submitted plan does not meet the ordinance requirements; however, we defer to the Township Zoning Officer.

SE Response: This waiver has been granted.

**G&A follow up:** So Noted.

 §255-27.I.(2): Driveway accesses must provide a minimum 200 feet between adjacent driveways. The Township may want to consider restricting turn movements or the elimination of one of the access driveways, with one shared access to Lancaster Avenue/SR 0030 or movement restrictions for 613 and 605 W. Lancaster Avenue.

SE Response: As discussed with the Planning Commission, the applicant would like to provide as much access and maneuverability to this site as possible. Given the interplay between various neighboring properties and businesses, the plan is designed to provide multiple ingress/egress opportunities and allow motorists options to safely access to and from Lancaster Avenue and Old Eagle School Road.

**G&A follow up:** We defer to PennDOT regarding elimination or consolidation of the driveway accesses to Lancaster Avenue.

**SE Response:** The applicant is in the process of submitting a Highway Occupancy Permit.

G&A follow up: So Noted.

4. §255-29.A.(9): Vehicular maneuvers in and out of the diagonal parking spaces adjacent to Lancaster Avenue/SR 0030 likely conflict with westbound traffic movements. The Township may want to consider eliminating the diagonal parking spaces or revise the layout to parallel parking spaces. The parallel parking spaces would allow parking maneuvers outside the travel lane and could reduce the potential for conflicts with vehicles traveling along Lancaster Avenue/SR-0030)

**SE Response:** Many of these parking spaces are not on the applicant's property. One space will be eliminated to improve the driveway entrance with the site entrance curbing being greatly improved providing some protection to the existing angled spaces.

**G&A follow up:** We continue to recommend investigating elimination of the onstreet parking spaces along this frontage or minimally, a conversion to parallel parking spaces.

**SE Response**: The spaces along Lancaster Avenue support the adjoining properties. These spaces are consistent with many others along Lancaster Avenue in Wayne.

Steve Norcini, P.E. 613 W. Lancaster Avenue TMP No. 36-01-00274-00 May 23, 2014

**G&A follow up:** We will defer to PennDOT regarding parking along Lancaster Avenue.

### 5. Sheet 3:

a. Parking Summary: The parking area serves more than just the existing restaurant building; the surface lot provides parking for the other four (4) attached buildings. The Parking Summary analysis should be revised to include any buildings utilizing the surface lot to ensure adequate facilities are provided.

**SE Response:** This property is independent of the other stores along Lancaster Avenue. In the interest of being a good neighbor, the applicant has not historically restricted the use of the parking by the adjacent properties nor has current plans to do so. There is however, no right to use the property.

**G&A follow up:** So noted.

SE Response: Comment has been adequately addressed.

b. The applicant should verify that gore striping exists near the property due east of the parcel.

**SE Response:** Following recent renovations and repairs at the Currie Spa property, the gore striping is re-painted.

G&A follow up: Comment has been adequately addressed.

SE Response: Comment has been adequately addressed.

c. The affected property owners adjacent to the site must provide written permission for any work shown outside the applicant's property line boundaries. To reduce the potential for encroachment during construction, we further recommend obtaining a five foot construction easement from adjacent property owners for any construction work located near the property lines.

**SE Response:** If necessary, the adjacent property owner at 605 W Lancaster Avenue will provide written permission.

G&A follow up: So noted.

**SE Response:** A proposed easement has been added to the plan in the area of the parking island on the adjacent parcel.

G&A follow up: So noted.

Steve Norcini, P.E. 613 W. Lancaster Avenue TMP No. 36-01-00274-00 May 23, 2014

### 6. All Sheets:

- a. For consistency, the Title Block and plans should identify the correct roadway name for SR 0030. The plans indicate *Lancaster Pike* and the Title Block indicates *Lancaster Avenue*.
- b. The legal right-of-way line for Lancaster Avenue (SR 0030) should be verified and identified on the plans.
- c. The plans should be revised to include labels for all radii in the parking area.

**G&A follow up:** Applicant has satisfactory addressed comments.

SE Response: Comment has been adequately addressed.

7. It appears the applicant will be altering the driveway configuration; as such, the applicant should reach out to PennDOT regarding the proposed changes and determine if an HOP is required. The Township requests the opportunity to review all HOP plan submissions to PennDOT; as well as be given the opportunity to attend all meetings with PennDOT and copied on all correspondence regarding the same. At a minimum, PennDOT may want to review the proposed ADA curb ramps crossing the revised site driveway.

**SE Response**: The applicant is in the process of preparing a HOP permit for the improved driveway.

**G&A follow up:** The Township should receive timely submissions concurrent with PennDOT and should be included in any meetings.

**SE Response:** The applicant is in the process of submitting a Highway Occupancy Permit.

**G&A follow up:** So noted.

8. During our field review, we noted a low hanging utility wire in the parking area (approximately 10' off the ground directly above several active parking spaces). The owner should immediately address this safety concern.

**SE Response:** The applicant is working with the utility company (Verizon) to raise or relocate this wire onto the new pole recently installed by Peco.

**G&A follow up:** So noted.

SE Response: Comment has been adequately addressed.

**G&A follow up:** So noted.

If you have any questions regarding the above, please contact this office.

ELAINE P. SCHAEFER
President

JAMES C. HIGGINS Vice-President

WILLIAM A. SPINGLER
DONALD E. CURLEY
JOHN FISHER
JOHN NAGLE
RICHARD F. BOOKER



### RADNOR TOWNSHIP 301 IVEN AVENUE WAYNE, PENNSYLVANIA 19087-5297

Phone (610) 688-5600 Fax (610) 971-0450 www.radnor.com ROBERT A. ZIENKOWSKI

Township Manager Township Secretary

JOHN B. RICE, ESQ. Solicitor

JOHN E. OSBORNE Treasurer

May 13, 2014

Sean McCloskey Eagle Green, LP 620 Righters Ferry Road Bala Cynwyd, PA 19004

RE: 613 W. Lancaster Avenue

Land Development Application #2013-D-13 Final Plan

Dear Mr. McCloskey:

In accordance with Section 255-18 of the Code of the Township of Radnor, we have performed a completeness review of your land development application to remove the existing building and construct a 2,800 s.f. restaurant, and have determined your application to be administratively complete. Therefore, I have accepted the application for final land development for review by the Township Staff, Shade Tree Commission, Planning Commission, and Board of Commissioners.

These plans are available for public viewing in the Engineering Department. These plans will be reviewed by the Planning Commission at their meeting on **Monday June 2, 2014**. Subsequent to the Planning Commission meeting, your plan will be reviewed by the Board of Commissioners. You or your representative should plan to attend all scheduled meetings.

If the Planning Commission takes action, your plan will then be reviewed by the Board of Commissioners at a future meeting. These dates will be provided to you once it is placed on the agenda.

If you have any questions or require any additional information, please contact me.

Sincerely,

Roger A. Phillips, PE Township Engineer

CC: Site Engineering Concepts, LLC.

### SITE ENGINEERING CONCEPTS, LLC

Consulting Engineering and Land Development Services

01 May 2014

Suzan Jones. Radnor Township 301 Iven Avenue Radnor, PA 19087

Re: 613 W Lancaster Avenue Final Land Development

Dear Ms. Jones:

Please find the enclosed 33 copies of the plan set for submission of a Final Plan Application. We have also included the appropriate fees, applications, permeability test report and copy of the deed.

We have addressed the comments from Gannett Fleming's March 3, 2014 and Gilmore's January 29, 2014 review letters.

Gannett Fleming (comment, response):

### I Zoning Ordinance Review

- 1. The following items are existing non conformities, that the applicant intends to continue with the proposed project:
  - \( \frac{1}{2}80-52.E \text{Rear Yards} \text{There shall be a rear yard of each lot of not less than 35 feet. The existing rear yard setback is 33.47 feet and the proposed rear yard setback is 34.4 feet.

    Correct. This is a reduction in the existing non-conformity.
  - §280-52.G Impervious Lot Coverage Not more than 70% of the lot maybe occupies by impervious surfaces. The existing conditions are 77,71% impervious and the proposed conditions are 73.33% impervious.

Correct. This is a reduction in the existing non-conformity.

• §280-4 — Parking Space — An outdoor space or garage space used for parking motor vehicles, which shall measure not less than nine feet six inches by 20 feet, accessible from a street, alley or driveway and surfaced with a Township approved durable dustproof all weather surface. The existing parking spaces are 7.8' — 9.0' × 15'.3" — 17'.0". The proposed parking spaces are 9' × 17' and the proposed Handicapped spaces are 8' × 17' with an aisle.

Correct. This is a reduction in the existing non-conformity.

### II Subdivision and Land Development Review

1. §255.29.A(1) – A parking aisle with 90° parking and 2 direction is to be 22 feet. The existing two way parking aisle is 20.3 feet and the proposed parking aisle is 21 feet. The proposed parking aisle must meet the requirements or a waiver requested.

This waiver has been granted.

Suzan Jones Radnor Township 613 W Lancaster Avenue 01 May 2014 Page 2 of 6

2.  $\int 255.29 A(1) - 90^{\circ}$  parking stalls should be 9.5 feet  $\times$  20 feet. The existing parking spaces are 7.8'  $-9.0' \times 15'.3'' - 17'.0''$ . The proposed parking stall dimensions must meet the requirements or a waiver requested.

This waiver has been granted.

- 3. §255.29.A(7) No one area for off street parking of motor vehicles shall exceed 30 cars in capacity. The existing parking area provided 40 spaces and the proposed parking area proposed 37 spaces. The proposed parking must meet the requirements or a waiver requested.

  This waiver has been granted.
- 4. §255.29.B(1) All parking areas shall have at least one tree 2 ½ inches minimum caliper for every five parking spaces in single bays and one tree 2 ½ inches minimum in caliper for every 10 parking spaces in double bays. There are two trees in the existing parking area. The proposed plan removes the two existing trees and plants 2 new canopy trees, 2 flowering trees, 32 shrubs and fountain grass. The applicant has indicated that approval was received at the January 22, 2014 Shade Tree Meeting. Approval was received.

### III Stormwater Management

As discussed with Mr. Phillips, the applicant has performed additional testing including Ground Penetrating Radar (GPR) and a second Stormwater Soil Evaluation. The results concluded that an area in the Northeast corner had suitable soil for an additional small infiltration facility. A Rain Garden and Infiltration Bed are provided in this area.

- 1. §245-5 D(4) Construction of reconstruction of or addition of new impervious or semi pervious surfaces shall be regulated by the Stormwater Management Ordinance. Since this project is a reconstruction of an existing building, Stormwater Management must be addressed.

  See above response.
- 2. §245-5 F Table 105.1 located at the end of the Stormwater Management chapter summarized the applicability requirements of the chapter. Proposed impervious surface in table 105.1 includes new, additional or replacement impervious surface/cover. Repairing existing surfaces without reconstruction does not constitute "replacement".

See above response.

3.  $\int 245-12 - A$  drainage plan must be submitted in accordance with Article 3 – Drainage Plan Requirements.

The drainage plan is included on the proposed plan.

### IV General Comments

1. Sewage Facilities Planning must be addressed for the increase in wastewater discharge. A planning module exemption form will be completed for any increase in sewage flow due to the building expansion. The applicant understands this requirement and has submitted a planning module or exemption request.

Suzan Jones Radnor Township 613 W Lancaster Avenue 01 May 2014 Page 3 of 6

2. A Highway Occupancy Permit must be prepared for the modification to the existing driveway and curbing along Lancaster Avenue.

The applicant is in the process of submitting a Highway Occupancy Permit.

3. All existing and proposed utility connections must be shown on the plans. The applicant has indicated that this will be provided on the permit plans.

The utilities will be shown on the permit plans once the architectural plans are further

developed.

4. The location of the dumpster has been shown on the plans. Appropriate screenings as discussed in §206.4.] must be shown on the plans.

A detail of the dumpster enclosure has been added to the detail sheet.

- 5. The applicant has indicated that the 10 foot dead end driveway is an existing easement access Old Eagle School Road. Documentation must be provided.

  The easement language is included in the attached deed.
- 6. An easement is required for the construction of the parking island located on the adjacent parcel. The easement shall include a requirement that the parking island cannot be altered or removed without the written approval of the Radnor Township Board of Commissioners.

  A proposed easement has been added to the plan in the area of the parking island on the adjacent parcel.

Gilmore and Associates (comment, response):

### C. REVIEW COMMENTS:

Gilmore & Associates, Inc. (G&A) January 6, 2014 letter including, Site Engineering (SE) responses and G&A follow up discussions:

1. §255.20.B(5)(e)[2]: A limited Traffic Impact Analysis should be prepared to analyze the PM and Saturday peak hours along with the existing traffic counts and proposed trip generation of the new restaurant. The study should focus on the traffic operations at all accesses to Sugartown Road, Lancaster Avenue and the intersection of Sugartown Road and Lancaster Avenue.

SE Response: The applicant requests the Board of Commissioners, at its discretion, not require this study. 255.20.B(5)(c)[1][b] of the Radnor Township code only requires traffic studies for commercial sites exceeding 50,000 sf, this site proposes 2,800 sf. In addition, the square footage of commercial space and number of parking spaces are reduced by this application.

G&A follow up: A study of the intersection of Lancaster Avenue and Sugartown Road (PM and Saturday Peak Hours) would provide useful information regarding potential turn restrictions for accesses to both Lancaster Avenue and Sugartown Road/Old Eagle School Road. In addition, five (5) years of historical crash records (both reportable and non-reportable) would provide additional information regarding the turn maneuvers and parking maneuvers for the onstreet diagonal parking spaces located along Lancaster Avenue, in front of the site.

The historical crash records have been provided and per further correspondence the study is no longer required.

Suzan Jones Radnor Township 613 W Lancaster Avenue 01 May 2014 Page 4 of 6

2. §255-29.A.(1):

a. Parking stalls are required to be a minimum 9.5-foot wide by 20-foot length. The plan indicates the existing parking dimensions do not meet the current SALDO requirements (various widths from 7.8 feet and lengths from 15.3 feet). With the redesign of the parking area, we recommend all parking stalls meet the current 9.5 feet wide by 20 feet in length as required by SALDO.

SE Response: As approved by the Township Zoning Officer and discussed with the planning commission, the applicant proposes to reduce the existing non-conformity.

b. Parking aisles must include a minimum 22-foot wide two-way aisle width; the proposed plans do not meet this requirement.

SE Response: The applicant has improved the existing non-conformity and proposes 21' aisles. G&A follow up: The submitted plan does not meet the ordinance requirements; however, we defer to the Township Zoning Officer.

This waiver has been granted.

3. §255-27.I.(2): Driveway accesses must provide a minimum 200 feet between adjacent driveways. The Township may want to consider restricting turn movements or the elimination of one of the access driveways, with one shared access to Lancaster Avenue/SR 0030 or movement restrictions for 613 and 605 W. Lancaster Avenue.

SE Response: As discussed with the Planning Commission, the applicant would like to provide as much access and maneuverability to this site as possible. Given the interplay between various neighboring properties and businesses, the plan is designed to provide multiple ingress/egress opportunities and allow motorists options to safely access to and from Lancaster Avenue and Old Eagle School Road.

G&A follow up: We defer to PennDOT regarding elimination or consolidation of the driveway accesses to Lancaster Avenue.

The applicant is in the process of submitting a Highway Occupancy Permit.

4. §255-29.A.(9): Vehicular maneuvers in and out of the diagonal parking spaces adjacent to Lancaster Avenue/SR 0030 likely conflict with westbound traffic movements. The Township may want to consider eliminating the diagonal parking spaces or revise the layout to parallel parking spaces. The parallel parking spaces would allow parking maneuvers outside the travel lane and could reduce the potential for conflicts with vehicles traveling along Lancaster Avenue/SR-0030)

SE Response: Many of these parking spaces are not on the applicant's property. One space will be eliminated to improve the driveway entrance with the site entrance curbing being greatly improved providing some protection to the existing angled spaces.

G&A follow up: We continue to recommend investigating elimination of the on-street parking spaces along this frontage or minimally, a conversion to parallel parking spaces.

The spaces along Lancaster Avenue support the adjoining properties. These spaces are consistent with many others along Lancaster Avenue in Wayne.

Suzan Jones Radnor Township 613 W Lancaster Avenue 01 May 2014 Page 5 of 6

5. Sheet 3:

a. Parking Summary: The parking area serves more than just the existing restaurant building; the surface lot provides parking for the other four (4) attached buildings. The Parking Summary analysis should be revised to include any buildings utilizing the surface lot to ensure adequate facilities are provided.

SE Response: This property is independent of the other stores along Lancaster Avenue. In the interest of being a good neighbor, the applicant has not historically restricted the use of the parking by the adjacent properties nor has current plans to do so. There is however, no right to use the property.

G&A follow up: So noted.

Comment has been adequately addressed.

b. The applicant should verify that gore striping exists near the property due east of the parcel.

SE Response: Following recent renovations and repairs at the Currie Spa property, the gore striping is re-painted.

G&A follow up: Comment has been adequately addressed.

Comment has been adequately addressed.

c. The affected property owners adjacent to the site must provide written permission for any work shown outside the applicant's property line boundaries. To reduce the potential for encroachment during construction, we further recommend obtaining a five foot construction easement from adjacent property owners for any construction work located near the property lines.

SE Response: If necessary, the adjacent property owner at 605 W Lancaster Avenue will provide written permission.

G&A follow up: So noted.

A proposed easement has been added to the plan in the area of the parking island on the adjacent parcel.

- 6. All Sheets:
- a. For consistency, the Title Block and plans should identify the correct roadway name for SR 0030. The plans indicate Lancaster Pike and the Title Block indicates Lancaster Avenue.
- b. The legal right-of-way line for Lancaster Avenue (SR 0030) should be verified and identified on the plans.
- c. The plans should be revised to include labels for all radii in the parking area. G&A follow up: Applicant has satisfactory addressed comments.

Comment has been adequately addressed.

Suzan Jones Radnor Township 613 W Lancaster Avenue 01 May 2014 Page 6 of 6

7. It appears the applicant will be altering the driveway configuration; as such, the applicant should reach out to PennDOT regarding the proposed changes and determine if an HOP is required. The Township requests the opportunity to review all HOP plan submissions to PennDOT; as well as be given the opportunity to attend all meetings with PennDOT and copied on all correspondence regarding the same. At a minimum, PennDOT may want to review the proposed ADA curb ramps crossing the revised site driveway.

SE Response: The applicant is in the process of preparing a HOP permit for the improved driveway.

GCA follow up: The Township should receive timely submissions concurrent with PennDOT and should be included in any meetings.

The applicant is in the process of submitting a Highway Occupancy Permit.

8. During our field review, we noted a low hanging utility wire in the parking area (approximately 10' off the ground directly above several active parking spaces). The owner should immediately address this safety concern. SE Response: The applicant is working with the utility company (Verizon) to raise or relocate this wire onto the new pole recently installed by Peco.

G&A follow up: So noted.

Comment has been adequately addressed.

I believe these comments satisfactorily address the requirements. Should you have any questions and/or comments, please feel free to contact me.

Sincerely,

David J. Sanders, P.E.

RADNOR TOWNSHIP 301 IVEN AVE WAYNE PA 19087 P) 610 688-5600 F) 610 971-0450 WWW.RADNOR.COM

### SUBDIVISION -- LAND DEVELOPMENT

Location of Property 613	W Lancaster 1	Avenue	negative and a second s	
Zoning District C-2		Application N	Vo(Twp. Use)	
			, ,	
Fee \$1,550	Ward No. 1-1	Is property in	HARB District	No
Applicant: (Choose one)	Owner X	Equite	able Owner	·····
Name Eagle Green, I	Р			
Address 620 Righters	Ferry Road,	Bala Cynwyd	19004	
Telephone 610-668-030	0 Fax	610-668-0365	Cell	
Email glen@pennenerg	yrenewables.c	com		
Designer: (Choose one)	Engineer X		Surveyor	
Name SITE Engineeri	ng Concepts,	LLC; Attn: F	Rob Lambert	
Address P.O. Box 1992	; Southeaster	n, PA 19399		
Telephone 610-240-045	0 Fa	x 610-240-04	151	_
Bmail_rlambert@site-e	engineers.com	r		
Area of property 24,442	sf Ar	ea of disturbance _	15,000 sf	~~~
Number of proposed building	gs <u>1</u> Pro	pposed use of prop	cty_Restaur	ant
Number of proposed lots	1 (no change	)		
Plan Status: Sketch Plan _ Are there any requirements o				ith?

Are there an There ar	y infringements of Chapter 280 (Zoning), and if so what and why? e several existing non-conformities that will remain
	orporation/Partnership Name 3reen, LP
property wh	certify that I am the owner, equitable owner or authorized representative of the ich is the subject of this application.
Print Name	SEAN M'CLOSHEY
By filing thi	s application, you are hereby granting permission to Township officials to visit
the site for r	eview purposes.
NOTE:	All requirements of Chapter 255 (Subdivision of Lane) of the Code of the Township of Radnor must be complied with whether or not indicated in this application.

### RADNOR TOWNSHIP 301 IVEN AVE. WAYNE, PA 19087 610 688 5600 WWW.RADNOR.COM

### SUBDIVISION AND LAND DEVELOPMENT SUBMISSION GUIDELINES

- Complete the enclosed Radnor Township Subdivision and Land Development application form and the Delaware County Planning Department application form.
- Submit the completed application forms, the three (3) required filing fees, and the appropriate number of copies
  of plans to the Township Engineer. <u>ALL DOCUMENTS MUST BE SUBMITTED NOT LESS THAN
  31 CALENDAR DAYS PRIOR TO THE NEXT PLANNING COMMISSION MEETING DATE IN
  ORDER TO BE PLACED ON THE AGENDA.</u>
- 3. The applicant or his/her representative must be present at all meetings when the application is scheduled as an agenda item.
- 4. When approved or disapproved by the Planning Commission the application will go before the Radnor Township Board of Commissioners for their approval/disapproval. This will not occur any sooner than forty-five (45) days after first regular meeting of Planning Commission or until receipt of the Delaware County Planning Commission's comments.
- The application will be approved/disapproved by the Township's Board of Commissioners within (90) days from the date of the first regular meeting of the Planning Commission, unless an extension is granted by the applicant.

### **Meeting Dates:**

All meetings are held at the Township Municipal Building – 301 Iven Ave, Wayne, Pa.

Planning Commission – Regular Meetings – 1st Monday of the month – 7:00 PM

Board of Commissioner's – Regular Meetings – 2nd & 4th Monday of the month – 7:00 PM (except summer)

### All meetings subject to change during summer months and around holidays

### Required Dimensions and Number of Plans for Submission:

Plan Scale:

Not less than 1"= 100'

Plan Size: Maximum 24" x 36" for all submissions.

Minimum 18" x 30"

THIRTY-FIVE (35) complete sets of plans <u>FOLDED</u> and <u>STAPLED</u> are required for all stages of plan reviews; Sketch Plan, Preliminary Plan and Final Plan. <u>Notarized signature of owner on eight (8) of the copies.</u>

Two (2) copies of any calculations/reports.

Any Waivers to the SALDO must be submitted in writing at the time of the application.

Copy of the deed or copy of sales agreement shall accompany this submission. Title Report with all attachments required <u>Not a title policy</u>

### Application Fee;

Three (3) checks are required – (1) Delaware County Planning Department Review (payable to DCPD), (1) Radnor Township Application Fee, and (1) Radnor Township Escrow Fee (Both payable to Radnor Township).

(The Fee Schedule on file at the Township Bldg. and website)

### HILBEC Engineering & Geosciences, LLC Wastewater, Stormwater, Hydrogeology, Environmental, Testing & Design

26 Beaver Run Road, Downingtown, PA 19335-2257
Office: 610.873.6204 www.hilbec.com Fax: 610.873.6206

April 16, 2014

Site Engineering Concepts, LLC Mr. Robert Lambert, PE PO Box 1992 Southeastern, PA 19399

Re:

Stormwater Soil Evaluation 613 W. Lancaster Ave Radnor Township, Delaware County

### Dear Mr. Lambert:

On January 15 and April 8, 2014, I conducted soil evaluations for a proposed stormwater management system(s) at 613 W. Lancaster Ave. A backhoe was used to excavate test pits to determine the most suitable depth to conduct permeability testing within the soil horizons. Test holes are typically excavated to the limits of the reach of the machine, bedrock, or a depth where water may be encountered entering the excavation.

The entire property is covered by a parking lot which slopes roughly northeast to southwest. The site is underlain by mafic gneiss; not a carbonate material. Test pits #SWM-01 through #SWM-03 were conducted on January 15, 2014 while test pits #SWM-04 and #SWM-05, including two permeability tests, were completed on April 8, 2014. Hard rock and open voided rock was encountered in each of the test pits.

The January round of testing showed hard rock encountered at depths of 24" to 48" below the existing parking surface. Attempting to keep the PA DEP required 24" isolation buffer between the rock and the proposed system could not be achieved. Although the parking surface and underlying aggregate are not mineral soils and would be removed, the bituminous surface provides a suitable reference location. This depth has been included in the attached soil descriptions.

In April, the property owner enlisted the services of a firm specializing in Ground Penetrating Radar (GPR) to determine if areas of the site were clear of the shallow rock. The entire site was scanned and two areas were identified as less encumbered by rock toward the north-northeast side of the property. All other parts of the site indicated shallow rock conditions within 2 to 4 feet. Their report is included within the exhibits of this report.

On April 8, 2014, we cut through the bituminous paving in the center of the GPR identified area "A" located nearest the existing building and along the north property line. Labelled #SWM-04, hard rock was initially encountered at 39 inches toward the northwest but transitioned to open voided rock at 39" with refusal at 60 inches.

A second test pit (#SWM-05) was dug farther upslope at the second area identified by the GPR survey. Initially, hard rock was again found at 39" but tended to deepen after the first five feet toward the east, to a depth of 67 inches below the paving. This location yielded a rock shelf at 67" then deepened with open voided rock from 67 inches to a depth of 78" where refusal was again encountered. These conditions persisted for approximately 20 feet where the rock again rose to 67 inches. After another 6 to 7 feet, open voided rock was then encountered at 30" to 82" with no soil over a short length of approximately 8 feet. Below this, the rock became saprolitic below 82" to a depth of 95 inches where refusal again occurred. This area is aligned with the aforementioned rock orientation and is likely a rock fracture encased on either side by the harder rock.

As a rain garden was initially proposed toward the east-northeast corner of the site, test pit #SWM-05 was extended further to determine the subsoil at that location. Rock was encountered at 60 inches and was rising higher toward the east. No further excavation was conducted since the rock was rising toward the ground surface.

### **Soil Test Pit Limitations:**

Test ID	#SWM-01	#SWM-02	#SWM-03	#SWM-04	#SWM-05
Depth to Limiting Rock	24"	48"	46"	39" to 60"	67"

A Guelph Permeameter was used to determine the permeability of the soil at the portion of #SWM-05 which exhibited the widest area of soil, free of rock with open voids or hard rock (see attached plan for test locations). The Guelph is a constant head borehole permeameter using the principle of the Mariotte Siphon to supply a constant level of water in the hole; unlike a percolation falling head test. The depth of the holes from existing grade level were adjusted to account for topographic variations.

The Guelph allows the Field Saturated Permeability ( $K_{fs}$ ) to be determined by running the test twice, at two different heads. Two tests are run at different heads or water elevations in order to provide the "gradient" portion of the required calculations. The gradient is used to measure the flux or water movement within the soil. A fluid bulb quickly forms and allows the stabilized hydraulic conductivity to be calculated. Errors inherent in other types of permeability tests that are minimized or eliminated by the Guelph Permeameter are soil fracturing, varying heads, silted in holes, estimated readings due to scale, and leaking clay seals.

Permeability tests assume that homogeneous soil conditions exist at and below the test zone, which is why the central portions of one soil horizon are typically chosen for the test depths. However, soil suitability, PA DEP guidelines, and proposed system design may alter that test parameter. Even within a consistent soil, unseen heterogeneous soil conditions can exist and may consist of:

- 1. Changing soil horizons across or near the test zone
- 2. Rock or stony soil beneath the bottom of the test hole
- 3. Roots, animal burrows
- 4. Soil fractures & thinly laminated soils

The consistency of the soil can be estimated by comparing the assumed and calculated alpha value. The alpha value is a soil parameter that depends primarily upon the soil texture and structure. By definition, it is the ratio of gravity to capillary soil-water forces. The value of typical fine to coarse-grained soils ranges between 0.01 and 0.5 cm<sup>-1</sup>. Values considerably outside of this range (and negative values) suggest that heterogeneous soil conditions, such as in stony areas, may be encountered. Large alpha values suggest coarse textured or highly structured soils. Low alpha values suggest finer grained soils or a fine matrix. The geometric mean of the single head tests can be used in place of the two head approach to provide the permeability values if heterogeneous soil conditions cannot be avoided, such as in rocky areas.

A summary of the permeability test results can be seen in the table below:

Test ID	Test Probe #	Test Depth (inches)	Grade Elevation	Result (in/hr)	Geometric Mean
P5-A	CIVID CO.	43	~424.75	1.93	1.09
Р5-В	SWM-01	46	~425.0	0.62	1.09

Permeability test holes were excavated outside of the test pit toward Rt. 30. Rock appeared in the shallow cut for the test at its southernmost edge. The depths were adjusted for elevation to maintain the 24" isolation buffer as based upon the findings of the test probe and topography as the rock in this area mimics the topographic slope. The permeability test data indicates that the soil can infiltrate the applied stormwater assuming that a properly dimensioned stormwater system is provided. The overall "deeper" soil area has rough dimensions of 30' (E-W) x 25' (N-S) including a 2 foot horizontal isolation buffer due to the vertical rock orientation. The designer may want to consider adding a safety factor to the bed size due to the varying rock depth and open voids, as those aspects of the geology could convey the applied stormwater to a less manageable location elsewhere on the site.

The open rock was nearly vertical in orientation and trends roughly northeast/southwest. For the test pits closer to the existing structures, the proximity of the open voided rock and its orientation raise concerns that any buildup of stormwater will allow it to migrate off site to the north, or southwestward toward the existing basements of the buildings. Farther downslope, the stormwater may seep

underneath the paving attempting to reach an outlet at the ground surface and weaken the paved surface over time. Little to no soil exists between the fractured voids in the rock. No ground water was encountered. Please refer to the photos below for reference to each test pit.

I certify that I have directly performed and/or supervised the test procedures and preparation of this report. All information contained herein is accurate to the best of my knowledge and all test procedures have been performed using accepted practices. HILBEC Engineering & Geosciences, LLC cannot and does not make claim, warranty or guarantee that surface and sub-surface site conditions other than described herein, either natural or as altered by construction activities, may be different at some time in the future and thus may affect these findings.

Please refer to the attached location map of the test areas. If you have any further questions, please contact our office.

Very truly yours,

For HILBEC Engineering & Geosciences, LLC

Kevin R. Sech, P.G., P.E.



Test Pit #SWM-01



Test Pit #SWM-02




Test Pit #SWM-03



Test Pit #SWM-04 at 39 inches



Test Pit #SWM-04 at 48 to 60 inches



Test Pit #SWM-05 at 0 to 67 inches



Test Pit #SWM-05 at 48 inches

### HILBEC ENGINEERING & GEOSCIENCES, LLC

### SOIL DESCRIPTIONS

# HILBEC Engineering & Geosciences, LLC

Testing Conducted For Stormwater Management

HILBEC Engineering & Geosciences, L.C. 26 Beaver Run Road, Downingtown, PA 19335-2257

Project Name.	Jamo.		613 W. Lancaser Ave	caser Ave		Probe #:		SWM-04						
Municipality:	dity:		Radnor Tov	Radnor Township, Delaware County	uno	Test Date:		April 8, 2014						
Soil Profil.	te Desc	Soil Profile Description Prepared By:	Kevin R. St	Kevin R. Sech, P.G., P.E.		Soil Profile		ock with lit	tle to no sa	Rock with little to no soil filling voids @ 39"	ids @	39"		
General L	ocation	General Location of the Test Pit:	Westerly sic	Westerly side along North lot line	8	Limitation:		No water or mottling observed	nottling ol	perved				
Horizon Up	dŋ	7	Texture	S	Structure	3	Consistence	%JD	Boundary		Roots Coats	500000	Mottles	les.
Ap	n	.⊑	ne aggregate										1	
Bt	מי	5YR 4/3 23 Reddish Brown	Silty Clay Stony	Massive	Structuriess	Friable	Somewhat Moist	40%	Clear	Wavy	o N	1	:	;
		Roots from trees grow horizontally along top of soil layer	rizontally alc	ong top of soil layer				ļ						
BC	23	60 7.5YR 4/6 Brown Silty Clay	Silty Clay	Massive	Structurless	Friable	Somewhat Moist	75%	Pit Base		No	1	1 1	i
		Mafic Gneiss, near vertic	al orientation	1, little to no soil in join	Mafic Gneiss, near vertical orientation, little to no soil in joints. Open voids at 39" becoming competent at 60"	ming compe	tent at 60"							
												-		
											į			
													į	
Method of	4.	Rubber Tired Backhoe Remarks:	Remarks:	Rock with	Rock with open voids									
Excavation:	0n:													

## PROJECT LIMITATIONS:

I certify that I have directly performed and/or supervised all test procedures and/or preparation of this report. All information contained herein is accurate to the best of my knowledge and all test procedures have been performed using accepted practices. IIII.BLC Engineering & Geosciences, I.I.C cannot and does not make claim, warranty, or guarantee that surface and sub-surface site conditions or test results, other than described or conducted at the time of the test, may be different at some time in the future and thus may affect these findings herein. Tevin R. Sech



Kevin R. Sech, P.G., P.E.

## Testing Conducted For Stormwater Management

HILBEC Engineering & Geosciences, LLC 26 Beaver Run Road, Downingtown, PA 19335-2257

				K13 W I angages Ang	acer 400				Probe #:		SWM-05						
Froject trame.	ume.			Radnar Town	ship. Del	Radnor Township, Delaware County	4		Test Date:		April 8, 2014	7					
Soil Profile Des	e Descr	stantiscipulus. Soil Profile Description Prepared By:	rred By:	Kevin R. Sech, P.G., P.E.	h, P.G., P	Ė			Soil Profile		ock with li	ttle to no s	Rock with little to no soil filling voids $(\!a\!a\!-\!67"\!)$	oids @			
General L	ocation	General Location of the Test Pit:	<i>bit</i>	Easterly side along North	atong No.	rth lot line			Limitation:		o water or	No water or mottling observed	bserved				
Horizon ('D	10000000	ALOY	Color	Texture		ng.	Structure		Col	Consistence	CF%	Bour	Boundary	Roots	Coats	Morties	(es
Ap	90	4	Biack	1	:	1				L E	-	-	t 1	-	í i	1	
		Blacktor	Blacktop paving and stone aggregate	ne aggregate							-						
Bŧ	4	19 5YF	5YR 4/1 Dark Grey Sandy Loam	Sandy Loam		Massive	Stru	Structurless	- V Friable	V Friable Avg Moisture	20%	Clear	Wavy	Yes	1	:	:
		Roots fr	Roots from trees grow horizontally along top of soil layer	vizontally alon	ig top of su	oil layer											
BC	19	5YF 39 Yell	5YR 5/6 Yellowish Red	Silt Loam		Massivc	Stru	Structurless	Friable	Avg Moisture	30%	Clear	Wavy	No	1 1		:
												ļ					
מ	39	5YF 67 Var	5YR 5/2 Var Red Brown	Sandy Loam	1	Massive	Stru	Structurless		<del></del>	20%	Pit Base	1 1 1	oN.	 	:	L E
		Mafic Gne	Oreys  Mafic Gneiss, near vertical orientation, little to no soil in joints. Open voids at 39" toward east then becoming competent at 67"	al orientation,	little to no	soil in joints.	. Open voi	ds at 39" towar	d east then be	scoming compet	ent at 67"						
		29															
	Roc	ck Gneiss Ba	Rock Gneiss Backhoe would not penetrate for majority of the long pit. Hard rock at 39", 67", 78", 95" at various points in pit. See map and report	t penetrate for 1	majority o	f the long pit.	Hard rock	k at 39", 67", 78	8", 95" at var	ious points in pi	t. See may	and repor	1				
													ļ		İ		
Method of	ر و پو	Rubber	Rubber Tired Backhoe Remarks:	Remarks:		Rock with open voids	nen voids			;				3		ļ	
Excavation:														The Name College State of the	Jan. Alach		

## PROJECT LIMITATIONS:

I certify that I have directly performed and/or supervised all test procedures and/or preparation of this report. All information contained herein is accurate to the best of my knowledge and all test procedures have been performed using accepted practices. IIILBRC Engineering & Geosciences, IILC cannot and does not make claim, warranty, or guarantee that surface and sub-surface site conditions or test results, other than described or conducted at the time of the test, may be different at some time in the future and thus may affect these findings exem herein.



Kevin R. Sech, P.G., P.E.

### HILBEC ENGINEERING & GEOSCIENCES, LLC

### PERMEABILITY TEST RESULTS AND CALCULATIONS

# CONSTANT HEAD PERMEAMETER TEST

CONSTANT HEAD BOREHOLE PERMEAMETER ANALYSIS

Guelph Permeameter

Sands, Gravels, Coarse Grained Saprolite, Soil Fractures

Structured Soils from Clays to Loams Fine & Very Fine Textured Silts and Clay

0.12 cm-10.04 cm-10.36 ст-1

RANGE OF TYPICAL TEXTURAL DATA (ALPHA VALUES)

PROJECT NAME:	613 W. Lancaster Ave	F
TEST ID:	P5.A	} }
TEST DEPTIE	43"	Ĭ
SOTI, PROBE #:	SWAL-05	S

F	$\geq$	Ξ	Z
613 W. Lancaster Ave	P5A	43"	SWAL-05

EST DATE:	April 8, 2014	
THATTHER / TEND:	Sunny / 50	Degr
OLE DIAMETER	6.0 cm or inch	2
DE OF TEST AREA:	Westerly Side	92

	4	- 107 G III G		
,.	Sumy /	20	Degrees	
	0.0	6.0 cm or inch	2 3/8	
;;	1	Westerly Side	ย	

	Number	of Tubes	(1 or 2)	561	7
pu-	Change in	[rater]	(cus)	equal readings	1.4
Level at 10	Previous	Water	Level (cm)	consecutive	12.7
2nd	IV ater	Laur	Reading (cm) Level (cm)	ilized with 3	14.1
	Time	Interval	(speconds)	Stat	30
					<b>بب</b>
	umber	Tubes	or 2)		2

Time Interval (seconds)

16:11			- 1	0.00	- 1				- 0		- 1			- 1		t				- 1	ı		- 1	- 5		1	- 4	Ł	- 1	,	- 7	- 1	
	Number	of Tubes	(1 or 2)	444	2	2	2	2	2	2	2	7	2	2	2	2	2							***************************************								and the second	
<b>E</b> 5	Change in	[rene]	(cm)	equal readings	1.4	1.3	1.3	1,4	1.1	1.2	1.1	1:1	1.0	1.1	6.0	6.0	0.9															i	
2nd Level at 10 cm	Previous	Water	Level (cm)	consecutive	12.7	14.1	15.4	16.7	18.1	19.2	20.4	21.5	22.6	23.6	24.7	25.6	26.5																
2nd	Water.	Taist	Reading (cm)	Stabilized with 3 consecutive	14.1	15.4	16.7	18.1	19.2	20.4	21.5	22.6	23.6	24.7	25.6	26.5	27.4																
	Time	Interva!	(seconds)	Stab	1	30	30	30	30	30	30	30	30	30	30	30	30						Ì										
				200			1												Į.	,							1					>	
	_			2536	<u> </u>	(1)	<i>ا</i>	<del>-</del>	L/S	9	~	∞	6	9	7.	12	5	;	72	19		18	19	ล	17	딝	23	77.	K)	79	27	8	-
	Number	of Tubes	(1 or 2)	Sign	2	-	2 3		į				2		11	12	13	14	15	16	17	18	19	20	21	티	23	24	25	26	27	28	
m	hange in		(cm) (1 or 2)	equal readings	2	-	2	2	2	2	2	2	2		=	12	13	14	15	16	41	18	10	20	21	[7]	23	24	25	226	27	28	
Level at 5 cm	hange in	Lenal	(cm)	consecutive equal readings	2	0.7	2	0.6	0.5 2	2	0.5 2	0.5 2	0.5 2		11	12	133	14	151	16	LT	18	19	20	21	70	23	24	25	26	27	28	
1st Level at 5 cm	hange in	Water Loral	m) Level (cm) (cm)	consecutive equal reading	2	0.7	3.8 0.7 2	4.5 0.6 2	5.1 0.5 2	0.6 2	6.2 0.5 2	6.7 0.5 2	7.2 0.5 2		11	12	13	14	51	16	LI	18	19	50	21	32	23	24	25	26	27	28	

		70G	and Level at 10 cm	Cm		
	Time	Water.	Previous	Change in	Number	Section 1997
	Interval	Laur	Water	[rater]	of Tubes	
	(seconds)	Reading (cm)	Level (cm)	(cus)	(1 or 2)	
	TES.	Stabilized with 3	589-48	equal scadings	1 <i>8</i> 8	
	30	14.1	12.7	1.4	2	
(1)	30	15,4	14.1	1.3	2	
en.	30	16.7	15.4	1.3	2	
+	30	18.1	16.7	1,4	2	
L/S	30	19.2	18.1	1.1	2	
2	30	20.4	19.2	1.2	2	
1~	30	21.5	20.4	1.1	2	
æ	30	22.6	21.5	1.1	2	
0.	30	23.6	22.6	1.0	2	
9	30	24.7	23.6	1.1	2	
=	30	25.6	24.7	6.0	2	
입	30	26.5	25.6	6.0	2	
5	30	27.4	26.5	0.9	2	
14						
53						
16						
17						
8						
19						
20						
21						
딝				***************************************		
23						

2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	5 cm 35.22 cm² 30 seconds 0.5 cm 1.677.02 cm/sec 8.867.03 cm²/sec 1.647.03 cm²/sec 1.541 in.hr 10 cm 35.22 cm² 30 seconds 0.9 cm 35.22 cm² 14.44.03 cm/sec 1.144.03 cm/sec 1.104.03 cm/sec 1.106.03 cm/sec	TEST PARAMETHES. RUN OF FIRST APPLIED HEAD  First Applied Head (14)  Caoss Sectional Area of Reservoir (35.22 or 2.15)  Time Interval Of Readings (T)  Stabilized Reading  Average Rate of Fall (R <sub>1</sub> )  Piest Head Matric Flux Potential  Area of First Head Matric Flux Potential  First Head Matric Flux Potential  Area First Head Matric Flux Potential  Second Applied Head (1)  Caoss Sectional Area of Reservoir (35.22 or 2.15)  THEST PARAMETERS: RUN OF SECOND APPLIED HEAD  Caoss Sectional Area of Reservoir (35.22 or 2.15)  The Stabilized Readings (T)  Second Applied Head (1)  Average Rate of Fall (R <sub>2</sub> )  Second Head Matric Flux Potential  N sec  Second Head Kis  Average Rate of Fall (R <sub>2</sub> )  Average Rate of Fall (R <sub>2</sub> )  Second Head Kis  Caountic Mean of Field Saturated Hydraulic  Geometric Mean of Field Saturated Conductivity  Calculated Matric Flux Potential Over Gradient (qm)  n sec  Calculated Matric Flux Potential Over Gradient (qm)  n sec  Calculated Hield Saturated Conductivity  Calculated Field Saturated Conductivity  Nobsec  Calculated Field Saturated Conductivity  Calculated Field Saturated Conductivity  Calculated Field Saturated Conductivity  Calculated Field Saturated Conductivity For Single Head Analysis (Kis)
---------------------------------------	--	--

1.93 inches/hour

The Single Head Geometric Mean is used when

1. The Matrix Flix Potential, Alpha, or the Kfs values are Negative, a Heterogeneous suit likely exists

2. The second rate is not greater than the first rate 1.93

0.9 cm

Stabilized At:

0.5 cm

Stabilized At:

FINAL GONDUGINGE RATE mehes/hour

# CONSTANT HEAD PERMEAMETER TEST

CONSTANT HEAD BOREHOLE PERMEAMETER ANALYSIS

Guelph Permeameter

Sands, Gravels, Coarse Grained Saprolite, Soil Fractures

RANGE OF TYPICAL TEXTURAL DATA (ALPHA VALUES)

Compacted and Structurless Clay, Landfill Caps, etc.

Fine & Very Fine Textured Silts and Clay

0.04 cm-1 0.01 cm-1 0.12 cm-1

0.36 cm-1

Structured Soils from Clays to Loams

TEST PARAMETERS, RUN OF FIRST APPLIED HEAD

First Applied Head (H)

Cross Sectional Area of Reservoir (35.22 or 2.15)

Time Interval Of Readings (T)

First Head Matric Flux Potential

Average Rate of Fall (R1)

Stabilized Reading

PROJECT NAME: SOIL PROBE #: TEST DEPTH THST D.

613 W. Lancaster Ave SWN1-05 P5-13 -94

20 Sumy / SIDE OF TEST AREA: WHATHER / TEMP: HOLE DIAMETER: TEST DATE:

2 3/8 Degrees April 8, 2014 Easterly Side 6.0 cm or inch

Number of Tubes

Change in

st Lettel at 5 cm

Lere/

Time Interval (seconds) St.

15/200			$\neg$	200	- 6		- 1	
	Number	of Tubes	(1 or 2)	ings .	2	2	2	,
EED	Change in	I sust	(cm)	equal read	1.4	1.2	1.2	13
Level at 10	Previous	1V ater	Level (cm)	consecutive	6.6	11.3	12.5	12.7
2nd	Water.	Larel	Reading (cm)	Stabilized with 3 consecutive equal readings	11.3	12.5	13.7	0 2 1
	Time	Interval	(seconds)	Stal	જ	09	99	
						61	er,	*

Stabilized with 3 consecutive equal readings

erel (cm) Previous Valer

Reading (cm) Water 1202

Interval (spuccas) Ime

0.5 9.0 0.3 0.4 0.3 6,4 0.5 0.5 0.5

> 3.0 3.3 4.0 4.9

3.7 5.5 5.4 5.9 6.4

2.4

3.0

9 8 G 09 9 88 9 3

,		(an and da)	Destina (ma) 1 and (cm)	I good form	()
(1 05.7)		(seconas)	Seaang cm)	11111 1212	////
83		Sta	Stabilized with 3 consecutive equal read	consecutive	equal read
2	п	ઉ	11.3	6.6	1.4
2	ĊΊ	09	12.5	11.3	1.2
2	m,	99	13.7	12.5	1.2
2	44	09	15.0	13.7	1.3
2	io	09	16.2	15.0	1.2
2	9	99	17.5	16.2	1.3
2	~	99	18.7	17.5	1.2
2	20	09	19.6	18.7	6.0
2	6	09	20.6	19.6	1.0
2	10	09	21.4	20.6	8.0
	11	9	22.2	21.4	0.8
	12	09	23.0	22.2	8.0
	13				

4.5 5.4 5.9

-	2	Ξ	12	13	7	13	70	17	
		3					12		-
						A. OFFICE OF	ļ		~
0.07	21.4	22.2	23.0						
17.17	20.6	21.4	22.2						
	0.8	0.8	0.8						

19 20 21 22 23 24 25 26 27 28

нэда рэхн	
.52	
<b>Geometric Mean</b>	
Head	
Single	

Geometric Mean Conductivity For Single Head Analysis (Kfs)

Hydraulic Conductivity Over Gradient (Kfs)

1. The Matrix Flux Paential, Alpha, or the Kfs values are Negative, a Heterogeneous soil likely exists

The second rate is not greater than the first rate

0.8 cm

Stabilized At:

0.5 cm

Stabilized At:

FINAL CONDUCTIVITY RATE menes/hour 0.62

### TEST PARAMETERS, RUN OF SECOND APPLIED HEAD HYDRAULIC CONDUCTIVITY ANALYSIS .62 inches/hour 3.74 inches/hour .-03 cm<sup>2</sup>/sec $-03 \text{ cm}^2/\text{soc}$ 4.43 E-03 cm<sup>2</sup>/sec 5.32E-04 cm/scc 1.33E-02 cm/sec 8.81E-03 cm<sup>2</sup>/sec 5.07E-04 cm/sec -04 cm/scc -04 cm/scc 8.33E-03 cm/sec 60 seconds 60 seconds 0.75 in/hr 0.72 in/hr 1.09 cm-1 10 cm 35.22 cm<sup>2</sup> 35.22 cm<sup>2</sup> 5 cm 0.5 cm 0.8 cm 7 N 2

Second Head Matric Flux Potential

Average Rate of Pall (R.)

Stabilized Reading

Second Picad Kfs (m/hr)

Second Head Kfs

Cross Sectional Area of Reservoir (35.22 or 2.15)

Second Applied Head (H)

First Head Kfs (m/hr)

First Head Kfs

Time Interval Of Readings (T)

Geometric Mean of Matric Flux Potential For Single Head Methods

Calculated Matric Flux Potential Over Gradient (pm)


Calculated Field Saturated Conductivity

Calculated Alpha Value  $(\alpha^*)$ 

Geometric Mean of Field Saturated Hydraulia

### HILBEC ENGINEERING & GEOSCIENCES, LLC

### GPR REPORT (by others)



April 1, 2014

Attn: Peter Wieck

**Penn Group of Companies** 

620 Righters Ferry Road, Bala Cynwyd PA 19004

Re: GPR Survey Soil Density Detection @ 613 W Lancaster Ave, Radnor, PA

We appreciate the opportunity to work with you on your project in Radnor Township, PA.

### **Table of Contents**

- 1. Overview of GPR
- 2. Equipment & Capabilities
- 3. Site Description
- 4. Inspection Methods
- 5. Findings
- 6. Qualifications
- 7. Closing

### 1. Overview of GPR-

Ground Penetrating Radar (GPR) is a non-destructive testing technology that sends a series of radar pulses into the surface which reflect back off of anomalies below. As the radar pulses through the ground, the waves bend slightly when encountering a material with differing physical properties, particularly density and conductivity. Thousands of pulses are sent and received in a small area, and the received signals are combined to form a real-time image of what is in the ground. The various places where the radar waves bend are displayed as anomalies which can be interpreted as utilities, steel pipes, PVC conduits, underground storage tanks, voids, foundations, etc. One of the many advantages of the technology is the ability to locate metal and non-metallic objects as well as determining depth to the object. GPR data acquisition is very fast and results are available immediately, allowing any discovered anomalies to be marked directly in the field. Although confused with X-Ray, GPR uses less than 1% of your cell phones radiation emissions and is safe to work with human presence in close proximity.

### 2. Equipment and Capabilities-

Ground Penetrating Radar (GPR)

GSSI SIR-3000

-GPRS uses a Geophysical Survey Systems Inc. (GSSI) SIR-3000 radar unit. This is the most advanced GPR available. It allows for on-site interpretation, as well as stored data for later processing. This equipment is self-calibrating, allowing more precise depth and location measurements.

-GSSI is the world's leading GPR designer and manufacturer. Information can be found at www.geophysical.com.

### 400 MHZ GSSI Antenna

-For utility locating, we use a 400MHz antenna with the SIR-3000 GPR head unit. This antenna allows data collection to a maximum depth of approximately twelve feet, depending on soil conditions.

RD-7000 Radiofrequency Detection System

- Locating specific pipes and cables in large underground networks is becoming increasingly complex. Ground distortion effects, caused by differing soil types and proximity to other conductors, make the operator's job more difficult and time-consuming. The most important requirements for a locator under these circumstances are ease of use, accuracy and reliability. The RD-7000 Utility Locator addresses this need with several groundbreaking features that deliver accurate, reliable and repeatable measurements. I use this only to determine any type of electrical current running in the concrete. I use this as a backup with the SIR-3000 due to the possibility of electricity within the concrete structures.

### 3. Site Description-

At this site our primary objective was to scan around the side of 613 West Lancaster Ave to identify any possible soil density changes subsurface that may be located on the property, I also scanned between buildings and detected numerous areas of solid rock subsurface. I then marked out the areas where I could see softer soil free of major rock.

### 4. <u>Inspection Methods-</u>


Since the surface was outside in asphalt location the scans were performed every two feet, our 400MHz antenna was utilized. When scanning around the parking lot location, we performed North-South and East-West scans to ensure the locations of any underground rock was mapped out within the proposed locations were identified. All markings were in white paint to show the pockets of rock detected or not detected.

## 5. Findings-


The survey results and data were interpreted in real time at the requested area. I performed scans 1'-2' apart using the SIR-3000 with the 400 MHz antenna to locate any major rock subsurface. When scanning the asphalt area facing the East side of the parking lot, the data was clear and able to interpret. After scanning that entire area, I was able to differentiate between solid rock and areas free of solid rock. All findings are marked directly on the surface for further review.

#### Conclusion:


The data at this location was clear and able to interpret. After scanning the requested area, selected by the onsite contact, we were able to map out areas free of solid rock. If you have any questions or comments please feel free to contact me. Below are screen shots and photographs taken on site.



The above screen shot was taken from the SIR-3000 with the 400MHz antenna showing no solid rock beneath the surface. There are 2 gauges in each screen shot. The left side gives the technician the depth of each obstruction while the top allows you to see the distance of each scan performed.



This screen shot shows a solid rock shelf starting at 48" and goes to as shallow as 24".



This screen shows another area of good soil and turns into a sharp decline into hard rock subsurface.





Rhett Teller - Project Manager of Pennsylvania Tri-State Area Rhett.Teller@gp-radar.com • (215) 694-4747





Rhett Teller - Project Manager of Pennsylvania Tri-State Area Rhett.Teller@gp-radar.com • (215) 694-4747

# 6. Qualifications-

Ground Penetrating Radar Systems, Inc. (GPRS) was started in October 2001, by Matt Aston. The original intention in starting this business was to give contractors a reliable way to "see" into the concrete slabs in order to avoid cutting embedded electrical conduits and critical reinforcing steel. While GPRS performs this work on a regular basis, there are many other applications in which we use Ground Penetrating Radar to benefit our customer base.

Since our inception, GPRS has grown to be nationwide and has completed over six thousand projects. Unlike many other companies that provide GPR services, GPR is all we do. We are the only nationwide GPR company that only provides GPR services. We perform GPR services every day. This is not something we do once in a while. We are very proud of our performance. We are very proud of our ten years of zero recordables. We have had a reported incident of error on less than one percent of the projects we have completed. Our customers have expressed a high level of satisfaction, as evidenced by the fact that in 2010, nearly 80% of our business was either repeat or referred by our customers. GPRS has been involved on projects ranging from small residential jobs to major construction projects with values in excess of \$4 Billion.

## 7. Closing-

Thank you for the opportunity to serve you on this project. I hope this report has answered all the questions you had regarding this survey. However, if there is anything you have questions about or feel was omitted, please do not hesitate to contact me.

Thank you,


Rhett Teller

Project Manager of the Pennsylvania Tri-State Area

Ground Penetrating Radar Systems, Inc.


Philadelphia - 215-694-4747

Rhett.Teller@gp-radar.com



# HILBEC ENGINEERING & GEOSCIENCES, LLC

# TEST LOCATION PLAN



Prepared By:

Robert Chalphin Associates, Inc. (#145698-NFA)

Return To:

Robert Chalphin Associates, Inc.

515 Swede Street

Norristown, Pa 19401

(610) 279-8290

Property:

613 West Lancaster Avenue

Township of Radnor

Delaware County, Pennsylvania

Parcel#

36-01-00274-00.

RD BK05000-1151

2011058015 10/07/2011 10:28:16 AM:1

RCD FEE: \$92.50 POL SUB TAX: \$8,625.00 ST TAX: \$5,760.00

DELAWARE COUNTY

DT-DEED

Deed

Francine Cappelli and John Cappelli Jr to

Eagle Green, LP, a Pennsylvania Limited Partnership

# THIS DEED, MADE THE 15th day of August, 2011.

BETWEEN,

Francine Cappelli and John Cappelli Jr

(hereinafter called the "Grantors"), of the one part,

and

## Eagle Green, L.P., a Pennsylvania Limited Partnership

(hereinafter called the "Grantee"), of the other part.

WITNESSETH, That the said Grantors for and in consideration of the sum of One Dollar and No Cents -----(\$1.00)-----

lawful money of the United States of America, unto them, the said Grantors, well and truly paid by the said Grantee, at or before the sealing and delivery hereof, the receipt whereof is hereby acknowledged, have granted, bargained and sold, aliened, enfeoffed, released and confirmed, and by these presents do grant, bargain and sell, alien, enfeoff, release and confirm unto the said Grantee, its successors and assigns, as partnership property paid for with partnership funds:

ALL THAT CERTAIN lot or piece of ground, Situate in the Township of Radnor, County of Delaware and Commonwealth of Pennsylvania, described according to a plan thereof made by Messrs, Over and Tingley, Civil Engineers, Upper Darby, Pennsylvania on October 20, 1925 revised October 11, 1928, and described according to said revised plan, as follows, to wit:

BEGINNING at a point in the center line of Lancaster Turnpike (eighty feet wide) at the distance of One hundred twenty eight and seventy one-hundredths feet measured South fifty three degrees, ten minutes East front the point of intersection of the center line of the said Lancaster Turnpike with the center line of Old Eagle School Road (thirty three feet wide); thence extending South fifty three degrees, ten minutes East along the center line of said Lancaster Turnpike One hundred and twenty eight one-hundredths feet, thence extending North sixty five degrees, three minutes East one hundred seventy nine and ninety seven one-hundredths feet to a point; thence North fifty three degrees ten minutes West One hundred sixty and one hundred eighty seven onethousandths feet to a point; thence extending South forty five degrees, fifty two minutes West passing through the center line of a party wall of the buildings erected on the premises adjoining to the Northwest One hundred sixty and fifty one-hundredths feet to the first mentioned point and place of beginning.

continued

AND ALL THAT CERTAIN lot or piece of land with the buildings and improvements thereon erected, Situate at Strafford, Radnor Township, Delaware County Pennsylvania, bounded and described according to a survey and plan thereof made by Over and Tingley, Civil Engineers, Upper Darby, Pennsylvania, on October 20th, 1925, as follows, to wit:

BEGINNING at a point in the center line of Lancaster Turnpike (eighty feet wide) at the distance of One hundred seventeen and thirty seven one-hundredths feet measured Southeastwardly from the point of intersection of the center lines of said Lancaster Turnpike and Old Eagle School Road (thirty three feet wide); thence extending South fifty three degrees, ten minutes East along the center line of Lancaster Turnpike eleven and thirty three one-hundredths feet to a point; thence North forty five degrees, fifty two minutes East partly along the center line of a party wall One hundred sixty and fifty one-hundredths feet to a point; thence North fifty three degrees, ten minutes West, Thirty six and fifty three one-hundredths feet to a point and thence extending South thirty six degrees, fifty minutes West One hundred fifty eight and fifty one-hundredths feet to the place of beginning.

TOGETHER with the free use, right, liberty and privilege of a certain driveway laid out over the rear of the above described lots of ground between the yard and garage spaces and which leads Northwest into Old Eagle School Road, at all times hereafter forever, in common with the owners, tenants and occupiers of the above described lots over which said driveway extends.

BEING Folio No. 36-01-00274-00

BEING THE SAME PREMISES WHICH John Cappelli Jr. and Francine Cappelli, husband and wife, by Deed dated 4/1/2004 and recorded 6/11/2004 in the County of Delaware, Pennsylvania in Deed Volume 3203, Page 1453, granted and conveyed unto John Cappelli, Jr. and Francine Cappelli, as tenants in common, in fee.

**TOGETHER** with all and singular the improvements, ways, streets, alleys, passages, waters, water-courses, rights, liberties, privileges, hereditaments and appurtenances, whatsoever thereunto belonging, or in any wise appertaining, and the reversions and remainders, rents, issues, and profits thereof; and all the estate, right, title, interest, property, claim and demand whatsoever of it the said Grantors, as well at law as in equity, or otherwise howsoever, of, in, and to the same and every part thereof.

TO HAVE AND TO HOLD the said lot or piece of ground above described, with the buildings and improvements thereon erected, hereditaments and premises hereby granted, or mentioned and intended so to be, with the appurtenances, unto the said Grantee, its successors and assigns, to and for the only proper use and behoof of the said Grantee, its successors and assigns forever.

AND the said Grantors, for themselves, their heirs and assigns, do covenant, promise and agree, to and with the said Grantee, its successors and assigns, by these presents that they, the said Grantors, their heirs and assigns, all and singular the hereditaments and premises hereby granted or mentioned and intended so to be, with the appurtenances, unto the said Grantee, its successors and assigns, against them, the said Grantors, their heirs and assigns, and against all and every person or persons whomsoever lawfully claiming or to claim the same or any part thereof, by, from or under it, them or any of them, shall and will, WARRANT and forever DEFEND.

IN WITNESS WHEREOF, the party of the first part has hereunto set its hand and seal. Dated the day and year first above written.

Francine Cappelli

John Cappelli, Jr

Jalu Cappell S

Commonwealth of Pennsylvania

County of Montgomuy

On this 15th day of August, 2011, before me, the undersigned officer, personally appeared Francine Cappelli and John Cappelli Jr, known to me (or satisfactorily proven) to be the persons whose names are subscribed to the within instrument and acknowledged that they executed the same for the purposes therein contained.

IN WITNESS WHEREOF, I hereunto set my hand and official seal.

COMMONWEALTH OF PENNSYLVANIA

NOTARIAL SEAL DANIELLE DELLETO, Notary Public Norristona Barata \ Stateomery Co. ly Commission Empires September 2, 2014

Eagle Green, LP,

TO

OMMONWEALTH OF PENNSYLVANIA

Notary Public

NOTARIAL SEAL
DANIELLE DELUZIO, Notzay Public
Norristown Borough, Montgomery Co. My Commission Expires September 2, 2014

Francine Cappelli and John Cappelli Jr a Pennsylvania Limited **Partnership** 

Recorded in Deed Book

GIVEN under my hand and the seal of the said office, the date above written.

Recorder of Deeds

On behalf of the Grantee:

Robert Chalphin Associates, Inc.

515 Swede Street

Norristown, Pa 19401

(610) 279-8290

145698-NFA

The address of the above-named

620 Righters Ferry Road, Bala Cynwyd, PA 19004



#### Excellence Delivered As Promised

#### **MEMORANDUM**

Date: May 28, 2014

To: Radnor Township Planning Commission

From: Roger Phillips, PE

cc: Stephen Norcini, P.E. - Director of Public Works

Kevin W. Kochanski, RLA, CZO - Director of Community Development

Peter Nelson, Esq. – Grim, Biehn, and Thatcher Amy B. Kaminski, P.E. – Gilmore & Associates, Inc. Suzan Jones – Radnor Township Engineering Department

William Miller – Radnor Township Codes Official Ray Daly – Radnor Township Codes Official

RE: Ithan Elementary School

Radnor Township School District - Applicant

Date Accepted: May 5, 2014 90 Day Expiration: August 8, 2014

Gannett Fleming, Inc. has completed a review of the Ithan Elementary School Preliminary/Final Land Development Plans for compliance with the Radnor Township Code.

The existing property is located in the PLU zoning district. The applicant is proposing to construct a building addition to the Ithan Elementary School and relocate a walkway on the property.

This Land Development Application is subject to Zoning, Subdivision and Land Development, Stormwater Management, and other applicable codes of the Township of Radnor.

The applicant has indicated that the following waivers will be requested from the Subdivision and Land Development Code:

- §255-12 Formal request from the land development process
- §255-20.B.5 To not provide the transportation impact study
- §255-21(n) Modification to allow an aerial photograph to depict features within 500' of property

Plans Prepared By: Momenee & Associates, Inc. Dated: 05/02/2014, No Revisions

#### **Gannett Fleming**

#### I. Zoning

1. §280-103 – Off-street parking calculations should be provided that indicate the number of additional parking spaces required for this project.

#### II. Stormwater Management

- A general note shall be added to the plans indicating that a grading plan and erosion sediment and control plans will be submitted and approved prior to issuing any building permits. Any revisions to the size or location of the individual structures or other features will be addressed at that time, and a final approval of the stormwater management plan will be required as part of the Grading Permit process.
- 2. Percolation tests must be provided to indicate that the stormwater facility will be able to drain within 96 hours. Final design and sizing of the stormwater facility should be based on the results of the percolation tests.

Should the Planning Commission consider recommending approval of this project, we recommend that the recommendation be conditioned on requiring the applicant to satisfactorily address the above comments.

If you have any questions or require any additional information, please contact me.

Very truly yours,

GANNETT FLEMING, INC.

Roger A. Phillips, P.E. Senior Project Manager



## GILMORE & ASSOCIATES, INC.

ENGINEERING & CONSULTING SERVICES

#### MEMORANDUM

Date:

May 23, 2014

To:

Steve Norcini, P.E.

Radnor Township Public Works Director

From:

Damon Drummond, P.E., PTOE G&A Senior Transportation Engineer

cc:

Roger Phillips, P.E. - Gannett Fleming, Inc., Senior Project Manager Amy Kaminski, P.E., PTOE - G&A Department Manager of Transportation

Kristin Norwood, P.E. - G&A Senior Transportation Engineer

Reference:

The Ithan Elementary School (TMP 36-45-054-000)

Preliminary/Final Land Development Review

G&A Job #14-05022

Pursuant to your request, Gilmore & Associates, Inc. has completed a transportation review of the referenced Preliminary/Final Land Development Plans for Ithan Elementary School. The applicant proposes to construct an one-story building addition and walkway improvements at the existing elementary school situated on a 46.99 acre parcel. We offer the following for Radnor Township's consideration:

#### A. REVIEWED MATERIALS

1. Preliminary/Final Land Development Plans for The Ithan Elementary School dated May 02, 2014, prepared for Radnor Township School District by Momenee and Associates, Inc. (8 sheets).

#### B. REQUESTED SALDO WAIVERS

- 1. §255-12: Waiver request from the formal land development process.
- 2. §255-20.B.5: Waiver request from providing a Transportation Impact Study.
- 3. §255-21(n): Waiver request to use aerial photograph to depict features within 500' of the property.

#### C. PRELIMINARY/FINAL LAND DEVELOPMENT PLAN REVIEW COMMENTS

1. §255-20.A(5): The plan should clearly indicate which features are existing and which are proposed. Provide shading or hatching or another technique to clearly indicate the proposed building construction.

Steve Norcini, P.E. The Ithan Elementary School May 23, 2014

- 2. §255-20.B(5): Provide clarification as to whether the expansion is to accommodate additional students and/or staff and therefore generating additional trips.
- 3. §255-37: Ensure that the proposed walkway is ADA compliant. Provide a detail of the walkway indicating the width, grades, and cross-slopes.
- 4. Provide a R5-1 Do Not Enter at the end of the one-way circular driveway.
- 5. The proposed expansion is to be located in the vicinity of an existing playground. The applicant should indicate if this playground will be relocated and show the new location on the plans.
- 6. Provide existing driveway widths and radii. Include arrows showing the existing traffic circulation within the site distinguishing between bus and auto/carpool traffic to verify that adequate access is provided for the existing building and new expansion. Ensure that adequate access can be maintained for both vehicular and pedestrian traffic.

If you have any questions regarding the above, please contact this office.

ELAINE P. SCHAEFER

President

JAMES C. HIGGINS Vice-President

WILLIAM A. SPINGLER DONALD E. CURLEY JOHN FISHER JOHN NAGLE

RICHARD F. BOOKER



RADNOR TOWNSHIP
301 IVEN AVENUE
WAYNE, PENNSYLVANIA 19087-5297

Phone (610) 688-5600 Fax (610) 971-0450 www.radnor.com ROBERT A. ZIENKOWSKI

Township Manager Township Secretary

JOHN B. RICE, ESQ. Solicitor

JOHN E. OSBORNE
Treasurer

May 13, 2014

Leo Bernabei Radnor Township School District 135 S. Wayne Ave. Wayne, PA 19087

RE: Ithan Elementary School

Land Development Application #2014-D-05 Preliminary Plan

Dear Mr. Bernabei:

In accordance with Section 255-18 of the Code of the Township of Radnor, we have performed a completeness review of your land development application to construct a building addition to the Ithan Elementary School and relocate a walkway on the property, and have determined your application to be administratively complete. Therefore, I have accepted the application for preliminary revised plan for review by the Township Staff, Shade Tree Commission, Planning Commission, and Board of Commissioners.

These plans are available for public viewing in the Engineering Department. These plans will be reviewed by the Planning Commission at their meeting on **Monday June 2, 2014**. Subsequent to the Planning Commission meeting, your plan will be reviewed by the Board of Commissioners. You or your representative should plan to attend all scheduled meetings.

If the Planning Commission takes action, your plan will then be reviewed by the Board of Commissioners at a future meeting. These dates will be provided to you once it is placed on the agenda.

If you have any questions or require any additional information, please contact me.

Sincerely.

Roger A. Phillips, PE Township Engineer

CC: Momenee & Associates, Inc.

924 COUNTY LINE ROAD • BRYN MAWR, PENNSYLVANIA 19010 (610) 527-3030 • FAX (610) 527-9008

E-MAIL: info@momenee.com

www.momenee.com

May 2, 2014

Mr. Roger Phillips, P.E., Township Engineer Radnor Township 301 Iven Avenue Wayne, PA 19087

RE: Ithan Elementary School Wayne Elementary School Preliminary / Final Land Development Applications Radnor Township, Delaware County Our File No. 14-041 Our File No. 14-042

Dear Mr. Phillips:

On behalf of the Radnor Township School District, we are submitting land development applications for improvements associated with the Ithan Elementary School property and the Wayne Elementary School property. Along with this letter please find the following:

#### Ithan Elementary School

- One (1) copy of the signed Land Development Application,
- One (1) copy of the Delaware County Planning Commission review application,
- One (1) copy of the deed for the property,
- One (1) copy of the title report,
- A check in the amount of \$300 payable to "Treasurer of Delaware County",
- A check in the amount of \$1,550 payable to "Radnor Township",
- A check in the amount of \$10,000 payable to "Radnor Township",
- Two (2) copies of the Post Construction Stormwater Management Report,
- 35 copies of the Preliminary/Final Land Development Plans.

The Radnor Township School District proposes to construct a building addition to the Ithan Elementary School and to relocate a walkway on the property. The new one-story addition will consist of two new classrooms. The new improvements will create a slight increase in the total impervious cover on the property.

#### Wayne Elementary School

- One (1) copy of the signed Land Development Application,
- One (1) copy of the Delaware County Planning Commission review application,
- One (1) copy of the deed for the property,
- A check in the amount of \$400 payable to "Treasurer of Delaware County",
- A check in the amount of \$1,550 payable to "Radnor Township",
- A check in the amount of \$10,000 payable to "Radnor Township",
- Two (2) copies of the Post Construction Stormwater Management Report
- 35 copies of the Preliminary/Final Land Development Plans.

The Radnor Township School District proposes to construct a building addition to the Wayne Elementary School. The new one-story addition will consist of a new classroom and other multipurpose rooms. In addition, the existing one-story building currently used for overflow classrooms will be removed. The new improvements will create an overall decrease in the total impervious cover on the property.

By filing these applications, the Radnor Township School District wishes to have these matters placed on the June 2, 2014 agenda of the Planning Commission meeting and the June meetings of the Board of Commissioners. If you have any questions or require any further information, please do not hesitate to contact me. Thank you for your attention to this matter.

Very truly yours,

MOMENEE AND ASSOCIATES, INC.

Kevin R. Momenee, P.E., P.L.S.

14042L01.doc

cc: Leo Bernabei - Radnor Township School District

RADNOR TOWNSHIP 301 IVEN AVE WAYNE PA 19087 P) 610 688-5600 F) 610 971-0450 WWW.RADNOR.COM

## SUBDIVISION ~~ LAND DEVELOPMENT

Location of Property 695 C	llyde Road, Bryn Maw	r, Pa 19010
Zoning District PLU	App	plication No
		(Twp. Use)
Fee \$1,550.00	Ward No. <u>4-1</u>	Is property in HARB District No
Applicant: (Choose one)	Owner 📝	Equitable Owner
Name RADNIR To	wvship School	DISTRICT
Address 135 5. w	ATINE AVE. W	144NE 74 19067
Telephone 610 . 6 %8.	8100 Fax 610.9	102.0207 Ceil
Email LEO. BERN	IABET C RTSD.	076
Designer: (Choose one)	Engineer 🛛	Surveyor
Name <u>Kevin R. Momenee,</u>	P.E., P.L.S.	
Address 924 County Line I	Road, Bryn Mawr, Pa 1	9010
Telephone 610-527-3030	Fax 610-527	-9008 Cell
Email <u>kmomenee@momen</u>	ee.com	
Area of property 46.99 ac	A	rea of disturbance 0.5 ac
Number of proposed buildi	ngs <u>1</u> P	roposed use of property Institutional
Number of proposed lots 1		
Plan Status: Sketch Plan	Preliminary	

Are there any requirements of Chapter 255 (SALDO) not being adhered to?	
Explain the reason for noncompliance.	
255-12- Waiver request from the formal land development Process 255-12- Waiver request from the formal land development Process 255-20.B.5- To not provide at Transportation Impact Study 255-21(n)- Modification to allow an aerical Physiograph to depict features within 500' of property.	
255. 20.8.5. To not provide at Transportation Impact Study	
255-21(n) - modification to allow an aerial photograph to depict	
forming within copy of property.	
Are there any infringements of Chapter 280 (Zoning), and if so what and why?	
NO	
ndividual/Corporation/Partnership Name	
RADNOR TOUNSHIP SCHOOL DISTAILS	
RAPNOR TOHNSHIP SCHOOL DISTRICT	
do hereby certify that I am the owner, equitable owner or authorized representative of the	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	•
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	
do hereby certify that I am the owner, equitable owner or authorized representative of the property which is the subject of this application.	

By filing this application, you are hereby granting permission to Township officials to visit the site for review purposes.

NOTE:

All requirements of Chapter 255 (Subdivision of Lane) of the Code of the Township of Radnor must be complied with whether or not indicated in this application.

# DELAWARE COUNTY PLANNING COMMISSION

# APPLICATION FOR ACT 247 REVIEW

Incomplete applications will be returned and will not be considered "received" until all required information is provided.

Please type or print legibly

DEVELOPER/APPLI	CANT			
Name Radnor Towship S	chool District	E-mail leo,ber	rnabei@rtsd.org	
Address 135 S. Wayne	Avenue Wayne, I	PA 19087	Phone 610-688-	8100 Ext 6103
Name of Development	than Elementary Scho	pol		
Municipality Radnor Tow	nship			AAD V
ARCHITECT, ENGIN			e 610-527-3030	
Address 924 County Li Contact Kevin R. Momen	ne Road, Bryn M	awr, Pa 19010	menee@momenee.com	
Type of Review	Plan Status	Utilities Existing	Proposed	Environmental Characteristics
Zoning Change	☐ Sketch	☑ Public Sewerage	☑ Public Sewerage	
✓ Land Development	✓ Preliminary	☐ Private Sewerage	Private Sewerage	☐ Wetlands
Subdivision	☐ Final	✓ Public Water	☑ Public Water	☐ Floodplain
□PRD	☐ Tentative	Private Water	Private Water	✓ Steep Slopes
Zoning District PLU			ax Map # 36/45 / 054	4.00
		T	ax Folio # 36 / 04 / 02120	/ 50

WRITING "SEE ATTACHED PI Existing and/or Proposed Use of S Existing elementary school to be expand	Site/Buildings:		
	, 19.93	Acres	
Total Site Area			
Size of All Existing Buildings	89,213	Square Feet	
Size of All Proposed Buildings	91,983	Square Feet	
Size of Buildings to be Demolish	ed_0	Square Feet	
		A MUNICIPAL RESPONSIBILITY.	
Local Planning Commission	Regular Meeting_		
Local Governing Body	Regular Meeting_		
Municipal request for DCPD staf	f comments prior to D	CPC meeting, to meet municipal meeting	date:
Actual Date Needed			
IMPORTANT: If previously sub	mitted, show assigned	DCPD File#	
Print Name and Title of Designat	ed Municipal Official	Phone Number	(Amazon and Amazon and
Official's Signature		Date	<u>-</u>
FOR DCPD USE ONLY			
Review Fee: Check	r#	Amount \$ Date Received	

STATEMENT OF INTENT

Applications with original signatures must be submitted to DCPD.

# POST CONSTRUCTION STORMWATER MANAGEMENT REPORT FOR

# ITHAN ELEMENTARY SCHOOL

TOWNSHIP OF RADNOR


**JOB #14-041** 

MOMENEE AND ASSOCIATES, INC, 924 COUNTY LINE ROAD

**BRYN MAWR, PA 19010** 

 $\mathbf{BY}$ 

**MAY 2, 2014** 



# PROJECT NARRATIVE ITHAN ELEMENTARY SCHOOL

The Ithan Elementary School is a 46.99-acre development located northeast of the intersection of Sproul Road and South Bryn Mawr Avenue in Radnor Township. It is proposed to construct an addition to the existing school building along with other associated improvements. Some existing walkways and other impervious areas are proposed to be removed. The project will create 4,346 SF of new and/or replacement impervious cover. Due to Radnor Township regulations, storm water management will be provided. The site is developed under the provisions of Radnor Township's Regulations. These calculations are included as part of a Grading Permit for the site.


Storm water management is provided by one perforated pipe system sized to control the increase in storm water runoff from the developed sub-basin. This site is located in the Darby Creek watershed District B-2; as a result, several stormwater management guidelines were met. The increase in storm water runoff for the 2-year storm event must be recharged into the ground via percolation. Water quality treatment must be provided based on the township's calculation formula. The rate control through the 100-year storm must be provided as well as making the following reductions: the 2-year post rate shall be reduced to the 1-year pre rate, the 5-year post rate shall be reduced to the 2-year post rate shall be reduced to the 5-year rate, the 50-year post rate shall be reduced to the 10-year rate.


Stormwater management system #1 consists of 20 linear feet of 72" fully perforated corrugated metal pipe. The system will be installed down grade of the new building addition and will collect and control the runoff from the new roof area via roof downspout leaders and conveyance piping. Discharge from the pipe system is piped to an existing inlet downgrade of the system. The pipe system is designed to provide groundwater recharge for the volume generated by the 2-year storm event for the new and/or replacement impervious surfaces.

In order to size the on lot storm facilities to contain the volume of runoff increase for the 2-year storm, the developed portion of the lot was evaluated by the Universal Rational method to determine the volume increase in runoff. C coefficients were assigned to the developed portion of the lot based on soil conditions and vegetation. The subbasin was established based on the location of the proposed storm facilities and the contributory post development watershed. Preliminary system design was based on the volume required to recharge the increase in the 2-year storm runoff generated by the proposed impervious cover. Once the volume increase was calculated, the storm facilities were sized to provide this minimum storage volume. Hydrographs were then calculated for both pre and post development conditions to determine the need for rate control. Times of concentration were established for the subbasin and each development condition and used to determine the peak rates of runoff.

The perforated pipe system was then further refined to provide control of the post development runoff rates. Post development flows were routed through the pipe system and volumes were adjusted along with outlet controls to limit the post development runoff to rates required by township ordinances.

An attached table summarizes the analysis of the lot. Detailed calculations and support data are included as part of this report.





CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

ITHAN ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP

DELAWARE COUNTY

SUMMARY OF SITE RUNOFF:

PRE-DEVELOPMENT CONDITIONS

THE DEVELOR MENT CONSTRONG							
ENTIRE WATERSHED :	1-YR 0.503	2-YR 0.579	5-YR 0.679	10-YR 0.768	25-YR 0.856	50-YR 0.956	100-YR 1.032
ALLOWABLE DISCHARGE :	0.503	0.503	0.579	0.679	0.679	0.768	1.032
POST DEVELOPMENT CONDITIONS							
CONTROLLED SUBAREA #1:	1-YR 0.000	2-YR 0.030	5-YR 0.159	10-YR 0.225	25-YR 0.286	50-YR 0.350	100-YR 0.422
UNCONTROLLED AREA :	0.203	0.230	0.270	0.310	0.345	0.386	0.417
TOTAL POST DEVELOPMENT :	0.203	0.260	0.429	0.535	0.631	0.736	0.839
ACTUAL POST DEVELOPMENT REDUCTION :	0.300	0.319	0.250	0.233	0.225	0.220	0.193
VOLUME CONTROL SUMMARY (2-YR):							
PREDEVELOPMENT:	521	CF					

442 CF CONTROLLED AREA:

210 CF UNCONTROLLED AREA:

131 CF **RECHARGE REQUIRED:** 

CF 442 SWMS VOLUME IN:

CF 0 SWMS VOLUME OUT:

CF 442 **RECHARGE PROVIDED:** 

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

ITHAN ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP DELAWARE COUNTY

C CALCULATIONS FOR PREDEVELOPMENT AREA:

PRE-DEVELOPMENT C:

0.55

PRE-DEVELOPMENT AREA:

9976 **SF** 

0.229 ACRES

SOIL TYPE B - MEADOW

C = 0.25

5938 SF

**IMPERVIOUS** 

C = 0.99

4038 SF

CONTROLLED SUBAREA #1 C:

CONTROLLED SUBAREA #1 AREA:

0.99

4692 **SF** 

0.108 ACRES

SOIL TYPE B - LAWN

**IMPERVIOUS** 

C = 0.25C = 0.99

0 SF 4692 SF

100.0%

UNCONTROLLED C:

UNCONTROLLED AREA:

0.42

5284 **SF** 

0.121 ACRES

SOIL TYPE B - LAWN

**IMPERVIOUS** 

C = 0.25

4066 SF

C = 0.99

1218 SF

POST-DEVELOPMENT C:

POST-DEVELOPMENT AREA:

0.69

9976 **SF** 

0.229 ACRES

SOIL TYPE B - LAWN

**IMPERVIOUS** 

C = 0.25

4066 SF

C = 0.99

5910 SF

NET INCREASE

1872 SF

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

ITHAN ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP

**DELAWARE COUNTY** 

#### WATER QUALITY VOLUME

 $WQ_V = [P*R_V*A]/12$ 

P = 1 INCH

A = AREA OF PROJECT CONTRIBUTING TO WATER QUALITY BMP's

 $R_V = 0.05 + 0.0091$ 

I = PERCENT OF IMPERVIOUS COVERAGE

**A** =

0.108 ACRES

| = |100.00 %

R<sub>V</sub> =

0.9500

 $WQ_V =$ 

0.0086 ACRE-FEET

 $WQ_V =$ 

372 CF

# RECHARGE CALCULATIONS FOR THE FIRST INCH OF RUNOFF GENERATED FROM THE PROPOSED IMPROVEMENTS

FORMULA USED:

Rev = I \* Proposed Impervious Area (square feet) / 12 (inches/foot)

WHERE:

|=

1.0 inch

Proposed Impervious Area =

4346 square feet

Rev =

362 cubic feet

## INFILTRATION VOLUME PROVIDED (FT^3):

| Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | Volume | V

TOTAL:

442

## Time of Concentration (Tc) Worksheet

Project	ITHAN ELEMENTARY		Ву	JRM	Date	5/2/2014			
Location	RADNOR TOWNSHIP, DELA	WARE COUNTY	Checked		Date				
DDE DE	VELOPMENT To:								
PKE-DC	VELOFIVIENT TO.								
Flow Path			Segment ID						
	escription		0	LAWN	ļ				
	gth, L		ft ft/ft	76			i		
	rse Slope, s Velocity, V (Table 2.10.4.2)		ft/sec	1.50					
T = L / 60	** *	mpute 'Fc	min	0.84					= 0.84
		•					,		
	e of Concentration		min						0.84
*USE TE	IE MINIMUM TIME OF	CONCENTRATION (	)F 5 MINU	TES					
CONTR	OLLED #1 Te:								
COMIN	JEED WI IV.								
Flow Path	1		Segment ID		В				
	Description			PAVED	PIPE				
	gth, L		ft	44	73				
	rse Slope, s		ft/ft	0.08	5.00		ł		
_	Velocity, V (Table 2.10.4.2)	) ompute Tc,	ft/sec min	0.05	0.24				= 0.29
T = L / 60	JV Co	mpute rc,	111111	0.00	0.24		J		
Total Tim	ne of Concentration		min						0.29
*USE TI	IE MINIMUM TIME OF	CONCENTRATION	OF 5 MINU	TES					
UNCON	ITROLLED Te:								
Flow Path	h		Segment II	O A	1		1		
	nescription			LAWN			]		
	igth, L		ft	76					
	ırse Slope, s		ſt/ft	0.06					
	Velocity, V (Table 2.10.4.2		ft/sec	1,50			_	•	
T = L/6	0V Co	ompute Tc	min	0.84			J		= 0.84
m . 1	60 ( 1)		mir						0.84
	ne of Concentration	n zionicirinimin ( megan)	min OF 5 MINU	PP126					0.01
*USE T	HE MINIMUM TIME OF	F CUNCENTRATION	OF 5 MILINU	TES					

## MOMENEE AND ASSOCIATES, INC. 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

## 6' DIAMETER PERFORATED CMP

LENGTH OF

6 FT CMP = 20 FT

TOTAL VOLUME OF STORAGE PROVIDED =

564.2 **CF** 

#### AREA OF STORAGE:

ELEV.	PIPE HEIGHT (FT)	WIDTH OF PIPE (FT)	PIPE STRG. (SF)	VOLUME STRG. (CF)
359.00	0	0	0.0	0.0
359.10	0.1	1.54	30.7	1.5
359.20	0.2	2.15	43.1	5.2
359.30	0.3	2.62	52.3	10.0
359.40	0.4	2.99	59.9	15.6
359.50	0.5	3.32	66.3	21.9
359.60	0.6	3.60	72.0	28.8
359.70	0.7	3.85	77.0	36.3
359.80	8.0	4.08	81.6	44.2
359.90	0.9	4.28	85.7	52.6
360.00	1.0	4.47	89.4	61.3
360.10	1.1	4.64	92.9	70.5
360.20	1.2	4.80	96.0	79.9
360.30	1.3	4.94	98.9	89.6
360.40	1.4	5.08	101.5	99.7
360.50	1.5	5.20	103.9	109.9
360.60	1.6	5.31	106.1	120.4
360.70	1.7	5.41	108.1	131.1
360.80	1.8	5.50	110.0	142.1
360.90	1.9	5.58	111.6	153.1
361.00	2.0	5.66	113.1	164.4
361.10	2.1	5.72	114.5	175.8
361.20	2.2	5.78	115.7	187.3
361.30	2.3	5.83	116.7	198.9
361.40	2.4	5.88	117.6	210.6
361.50	2.5	5.92	118.3	222.4
361.60	2.6	5.95	118.9	234.2
361.70	2.7	5.97	119.4	246.2
361.80	2.8	5.99	119.7	258.1
361.90	2.9	6.00	119.9	270.1
362.00	3	6.00	120.0	282.1
362.10	3.1	6.00	119.9	294.1
362.20	3.2	5.99	119.7	306.1

362.30	3.3	5.97	119.4	318.0
362.40	3.4	5.95	118.9	330.0
362.50	3.5	5.92	118.3	341.8
362.60	3.6	5.88	117.6	353.6
362.70	3.7	5.83	116.7	365.3
362.80	3.8	5.78	115.7	376.9
362.90	3.9	5.72	114.5	388.4
363.00	4	5.66	113.1	399.8
363.10	4.1	5.58	111.6	411.1
363.20	4.2	5.50	110.0	422.1
363.30	4.3	5.41	108.1	433.1
363.40	4.4	5.31	106.1	443.8
363.50	4.5	5.20	103.9	454.3
363.60	4.6	5.08	101.5	464.5
363.70	4.7	4.94	98.9	474.6
363.80	4.8	4.80	96.0	484.3
363.90	4.9	4.64	92.9	493.7
364.00	5	4.47	89.4	502.9
364.10	5.1	4.28	85.7	511.6
364.20	5.2	4.08	81.6	520.0
364.30	5.3	3.85	77.0	527.9
364.40	5.4	3.60	72.0	535.4
364.50	5.5	3.32	66.3	542.3
364.60	5.6	2.99	59.9	548.6
364.70	5.7	2.62	52.3	554.2
364.80	5.8	2.15	43.1	559.0
364.90	5.9	1.54	30.7	562.7
365.00	6	0.00	0.0	564.2

Г		_	1		
OF 1	REMARKS		TYPE		
100 YR STORM SHEET 1 OF 1			13	368.17 367.50	367.50
100	INVERT LOWER END		 	365.50 364.50	359.00 354.84
	ІИЛЕКТ ОРРЕК ЕИD		ᇤ	366.17 365.50	359.00
	YTIOAYAO JJUST FULL CAPACITY	a	CFS	5 5	1.73
	MEAN VELOCITY	>	FPS	7.88	7.24
	PIPE TYPE			PVC PVC	PVC
	BZIS Bdld		Z	9 9	9
5/2/2014 JRM	COEFFICENT ROUGHNESS	z		0.011	0.011
DATE ( BY	SLOPE	တ	FT/FT	0.0515	0.0682
	LENGTH OF PIPE	_1	ㅂ	13 35	61
	DISCHARGE	Ø	CFS	0.85	0.42
	ΣΔCA	S	ACRES	0.10	
<b>&gt;</b>		ΔCA	ACRES	0.10	个
COUNTY	RUNOFF COEFFICENT	U		0.95	Q₁∞ FROM HYDROLOGIC STUDY →
	YTISNƏTNI JJAƏNIAR	_	IN/HR	8.2 8.2	LOGIC
100I   AW	FLOW TIME IN PIPE	-	MIN		YDRO
/ SCI P, DE	SUM OF TIME TO INLET	-	NE Y	ည	NOM H
NTARY	АЭЯА ТИЭМЭЯОМІ	<b>∀</b>	ACRES MIN	0.11	Q <sub>100</sub> FR
ITHAN ELEMENTARY SCHOOL RADNOR TOWNSHIP, DELAWARE			01	SUMP BOX SWM #1	EX. INLET
PROJECT II	LOCATION		FROM	SWM BASIN #1 ROOF SUMP BOX	SWM #1

# **Hydraflow Table of Contents**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

Watershed Model Schematic	1
Hydrograph Return Period Recap	2
1 - Year	
Summary Report	. 3
Hydrograph Reports	. 4
Hydrograph No. 1, Rational, Pre Development	. 4
Hydrograph No. 2, Rational, Post Uncontrolled	5
Hydrograph No. 3, Rational, Controlled SWM Basin #1	. 6
Hydrograph No. 4, Reservoir, SWM BASIN #1	. 7
Pond Report - SWM #1	
Hydrograph No. 5, Combine, Total Post	10
2 - Year	
Summary Report	11
Hydrograph Reports	12
Hydrograph No. 1, Rational, Pre Development	12
Hydrograph No. 2, Rational, Post Uncontrolled	13
Hydrograph No. 3, Rational, Controlled SWM Basin #1	14
Hydrograph No. 4, Reservoir, SWM BASIN #1	15
Hydrograph No. 5, Combine, Total Post	16
Trydrograph No. 3, Combine, Total T Col	•
5 - Year	
Summary Report	17
Hydrograph Reports	18
Hydrograph No. 1, Rational, Pre Development	18
Hydrograph No. 2. Rational, Post Uncontrolled	19
Hydrograph No. 3, Rational, Controlled SWM Basin #1	20
Hydrograph No. 4, Reservoir, SWM BASIN #1	21
Hydrograph No. 5, Combine, Total Post	22
10 - Year	
Summary Report	23
Hydrograph Reports	24
Hydrograph No. 1, Rational, Pre Development	24
Hydrograph No. 2, Rational, Post Uncontrolled	25
Hydrograph No. 3, Rational, Controlled SWM Basin #1	26
Hydrograph No. 4, Reservoir, SWM BASIN #1	27
Hydrograph No. 5, Combine, Total Post	28
OF Warn	
25 - Year	20
Summary Report	3U 73
Hydrograph Reports	3U
Hydrograph No. 1, Rational, Pre Development	21
Hydrograph No. 2, Rational, Post Uncontrolled	აე ა I
Hydrograph No. 3, Rational, Controlled SWM Basin #1	. ひと つつ
Hydrograph No. 4, Reservoir, SWM BASIN #1	. აა

Hydrograph No. 5, Combine, Total Post	34
50 - Year	0.5
Summary Report	35
Hydrograph Reports	
Hydrograph No. 1. Rational, Pre Development	36
Hydrograph No. 2. Rational, Post Uncontrolled	37
Hydrograph No. 3. Rational, Controlled SWM Basin #1#1	აგ
Hydrograph No. 4, Reservoir, SWM BASIN #1	39
Hydrograph No. 5, Combine, Total Post	40
100 - Year	
Summary Report	41
Hydrograph Reports	42
Hydrograph No. 1. Rational, Pre Development	4∠
Hydrograph No. 2, Rational, Post Uncontrolled	43
Hydrograph No. 3, Rational, Controlled SWM Basin #1	44
Hydrograph No. 4, Reservoir, SWM BASIN #1	45
Hydrograph No. 5, Combine, Total Post	46
IDF Report	47

# Watershed Model Schematic Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3







#### <u>Legend</u>

<u>Hyd.</u>	<u>Origin</u>	<u>Description</u>
1	Rational	Pre Development
2	Rational	Post Uncontrolled
3	Rational	Controlled SWM Basin #1
4	Reservoir	SWM BASIN #1
5	Combine	Total Post

Project: 14041.gpw

Thursday, 05 / 1 / 2014

Hydrograph Return Period Recap Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

yd.		Inflow				!	Hydrograph				
0.	type (origin)	hyd(s)	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr	Description
 1	Rational		0.503	0.579		0.679	0.768	0.856	0.956	1.032	Pre Development
2	Rational		0.203	0.234		0.274	0.310	0.345	0.386	0.417	Post Uncontrolled
3	Rational		0.427	0.491		0.576	0.652	0.726	0.812	0.876	Controlled SWM Basin #1
4	Reservoir	3	0.000	0.030		0.159	0.225	0.286	0.350	0.422	SWM BASIN #1
5	Combine	2, 4	0.203	0.234		0.274	0.365	0.460	0.559	0.641	Total Post
										!	
						ļ					
			ļ								
			ļ								
										·	
							i				
					!						
								ļ			
Į											

Proj. file: 14041.gpw

Thursday, 05 / 1 / 2014

# Hydrograph Summary Report Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description		
1	Rational	0.503	1	15	453				Pre Development		
2	Rational	0.203	1	15	183				Post Uncontrolled		
3	Rational	0.427	1	15	384			NA MA AN AN INCIDEN	Controlled SWM Basin #1		
4	Reservoir	0.000	1	367	0	3	362.81	379	SWM BASIN #1		
5	Combine	0.203	1	15	183	2, 4			Total Post		
14	1041.gpw				Retur	Return Period: 1 Year Thursday, 05 / 1 / 2014					

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 3.994 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.503 cfs
Time to peak = 15 min
Hyd. volume = 453 cuft
Runoff coeff. = 0.55
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 2


Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 3.994 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.203 cfs
Time to peak = 15 min
Hyd. volume = 183 cuft
Runoff coeff. = 0.42
Tc by User = 5.00 min

Asc/Rec limb fact

= 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 3.994 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.427 cfs
Time to peak = 15 min
Hyd. volume = 384 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 4

SWM BASIN #1

Peak discharge = 0.000 cfsHydrograph type = Reservoir Time to peak Storm frequency = 1 yrs= 367 min Time interval = 1 min Hyd. volume = 0 cuft Max. Elevation  $= 362.81 \, \mathrm{ft}$ Inflow hyd. No. = 3 - Controlled SWM Basin #1 Max. Storage = 379 cuft Reservoir name = SWM #1

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Pond No. 1 - SWM #1

#### **Pond Data**

UG Chambers -Invert elev. = 359.00 ft, Rise x Span = 6.00 x 6.00 ft, Barrel Len = 20.00 ft, No. Barrels = 1, Slope = 0.00%, Headers = No

Stage	Storage	<b>Table</b>
-------	---------	--------------

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	359.00	n/a	0	0
0.60	359.60	n/a	29	29
1.20	360.20	n/a	51	81
1.80	360.80	n/a	62	143
2.40	361.40	n/a	69	211
3.00	362.00	n/a	72	283
3.60	362.60	n/a	72	354
4.20	363.20	n/a	68	423
4.80	363.80	n/a	62	485
5.40	364.40	n/a	51	536
6.00	365.00	n/a	29	566

#### **Culvert / Orifice Structures**

#### **Weir Structures**

	[A]	[B]	[C]	[PrfRsr]		[A]	[B]	[C]	[D]
Rise (in)	= 6.00	3.50	0.00	0.00	Crest Len (ft)	= 2.62	0.00	0.00	0.00
Span (in)	= 6.00	3,50	0.00	0.00	Crest El. (ft)	= 364.92	0.00	0.00	0.00
No. Barrels	= 1	1	1	0	Weir Coeff.	= 3.33	3.33	3.33	3.33
Invert El. (ft)	= 359.00	363.17	0.00	0.00	Weir Type	= 1			
Length (ft)	= 61.00	0.00	0.00	0.00	Multi-Stage	= Yes	No	No	No
Slope (%)	= 6.80	0.00	0.00	n/a					
N-Value	= .011	.013	.013	n/a					
Orifice Coeff.	= 0.60	0.60	0.60	0.60	Exfil.(in/hr)	= 1.000 (by	Wet area)	١	
Multi-Stage	= n/a	Yes	No	No	TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (ic) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).

Stage /	Storage /	Discharge	Table
---------	-----------	-----------	-------

Stage ft	Storage cuft	Elevation ft	CIv A cfs	Clv B cfs	CIv C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Total cfs
0.00	0	359.00	0.00	0.00			0.00				0.000		0.000
0.06	3	359.06	0.00	0.00			0.00				0.001		0.001
0.12	6	359.12	0.00	0.00			0.00				0.001		0.001
0.18	9	359.18	0.00	0.00			0.00				0.001		0.001
0.24	12	359.24	0.00	0.00			0.00				0.001		0.001
0.30	15	359.30	0.00	0.00			0.00				0.001		0.001
0.36	18	359.36	0.00	0.00			0.00				0.001		0.001
0.42	21	359.42	0.00	0.00			0.00				0.001		0.001
0.48	24	359.48	0.00	0.00			0.00				0.002		0.002
0.54	26	359.54	0.00	0.00			0.00				0.002		0.002
0.60	29	359.60	0.00	0.00			0.00				0.002		0.002
0.66	35	359.66	0.00	0.00			0.00				0.002		0.002
0.72	40	359.72	0.00	0.00			0.00				0.002		0.002
0.78	45	359.78	0.00	0.00			0.00				0.002		0.002
0.84	50	359.84	0.00	0.00			0.00				0.002		0.002
0.90	55	359.90	0.00	0.00			0.00				0.002		0.002
0.96	60	359.96	0.00	0.00			0.00				0.002		0.002
1.02	65	360.02	0.00	0.00			0.00				0.002	-	0.002
1.08	70	360.08	0.00	0.00			0.00				0.002		0.002
1.14	75	360,14	0.00	0.00			0.00				0.003		0.003
1.20	81	360.20	0.00	0.00			0.00				0.003		0.003
1.26	87	360,26	0.00	0.00			0.00				0.003		0.003
1.32	93	360.32	0.00	0.00			0.00				0.003		0.003
1.38	99	360.38	0.00	0.00			0.00				0.003		0.003
1.44	105	360.44	0.00	0.00			0.00				0.003		0.003
1.50	112	360.50	0.00	0.00			0.00				0.003		0.003
1.56	118	360.56	0.00	0.00			0.00				0.003		0.003
1.62	124	360.62	0.00	0.00			0.00				0.003		0.003
1.68	130	360.68	0.00	0.00			0.00				0.003		0.003
1.74	137	360.74	0.00	0.00			0.00				0.003		0.003
1.80	143	360.80	0.00	0.00			0.00	LUA			0.003		0.003
1.86	150	360.86	0.00	0.00			0.00				0.003		0.003
											Continu		vt naga

Continues on next page...

SWM #1 Stage / Storage / Discharge Table

Stage / S	Storage / D	ischarge T	<b>Table</b>										
Stage ft	Storage cuft	Elevation ft	Clv A cfs	Clv B cfs	Clv C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Total cfs
1.92	156	360.92	0.00	0.00			0.00				0.003		0.003
1.98	163	360.98	0.00	0.00			0.00				0.003		0.003
2.04	170	361.04	0.00	0.00			0.00				0.003		0.003
2.10	177	361.10	0.00	0.00			0.00				0.004 0.004		0.004 0.004
2.16	184	361.16	0.00 0.00	0.00 0.00			0.00 0.00				0.004		0.004
2.22 2.28	191 198	361.22 361.28	0.00	0.00	'		0.00				0.004		0.004
2.34	204	361.34	0.00	0.00			0.00				0.004		0.004
2.40	211	361.40	0.00	0.00			0.00	ared.		****	0.004		0.004
2.46	218	361.46	0.00	0.00			0.00				0.004		0.004
2.52	226	361.52	0.00	0.00			0.00				0.004		0.004 0.004
2.58	233	361.58	0.00	0.00			0.00 0.00				0.004 0.004		0.004
2.64 2.70	240 247	361.64 361.70	0.00 0.00	0.00 0.00			0.00				0.004		0.004
2.76	254	361.76	0.00	0.00			0.00				0.004		0.004
2.82	261	361.82	0.00	0.00			0.00				0.004		0.004
2.88	269	361.88	0.00	0.00			0.00				0.004		0.004
2.94	276	361.94	0.00	0.00			0.00				0.004		0.004
3.00	283	362.00	0.00	0.00			0.00				0.004 0.004		0.004 0.004
3.06	290	362.06 362.12	0.00 0.00	0.00 0.00			0.00 0.00				0.004		0.004
3.12 3.18	297 304	362.12	0.00	0.00			0.00				0.005		0.005
3.24	311	362.24	0.00	0.00			0.00				0.005		0.005
3.30	319	362.30	0.00	0.00			0.00				0.005		0.005
3.36	326	362.36	0.00	0.00			0.00				0.005		0.005
3.42	333	362.42	0.00	0.00			0.00				0.005 0.005		0.005 0.005
3.48	340	362.48	0.00 0.00	0.00 0.00			0.00 0.00				0.005		0.005
3.54 3.60	347 354	362.54 362.60	0.00	0.00			0.00				0.005		0.005
3.66	361	362.66	0.00	0.00			0.00				0.005		0.005
3.72	368	362.72	0.00	0.00			0.00				0.005		0.005
3.78	375	362.78	0.00	0.00			0.00				0.005		0.005
3.84	382	362.84	0.00	0.00			0.00				0.005		0.005 0.005
3.90	389	362.90	0.00	0.00			0.00 0.00				0.005 0.005		0.005
3.96 4.02	396 402	362.96 363.02	0.00 0.00	0.00 0.00			0.00				0.005		0.005
4.02	402	363.08	0.00	0.00			0.00				0.005		0.005
4.14	416	363.14	0.00	0.00			0.00				0.005		0.005
4.20	423	363.20	0.00 ic	0.00 ic			0.00				0.006		0.008
4.26	429	363.26	0.02 ic	0.02 ic			0.00				0.006		0.023
4.32	435	363.32	0.05 ic	0.05 ic			0.00				0.006 0.006		0.051 0.087
4.38	442	363.38 363.44	0.08 ic 0.11 ic	0.08 ic 0.11 ic			0.00 0.00				0.006		0.007
4.44 4.50	448 454	363. <del>44</del> 363.50	0.11 ic	0.11 ic			0.00				0.006		0.144
4.56	460	363.56	0.16 lc	0.16 ic			0.00	***			0.006		0.165
4.62	466	363.62	0.18 ic	0.18 ic			0.00				0.006		0.183
4.68	473	363.68	0.19 ic	0.19 ic			0.00				0.006		0.200
4.74	479	363.74	0.21 ic	0.21 ic			0.00				0.006 0.006		0,216 0,230
4.80	485	363.80 363.86	0.22 ic 0.24 ic	0.22 ic 0.24 ic			0.00 0.00				0.006		0.244
4.86 4.92	490 495	363.92	0.24 ic	0.24 ic			0.00				0.006		0.256
4.98	500	363.98	0.26 ic	0.26 ic			0.00				0.006		0.269
5.04	506	364.04	0.27 ic	0.27 ic			0.00				0.006		0.280
5.10	511	364.10	0.28 ic	0.28 ic			0.00				0.007		0.291
5.16	516	364.16	0.30 ic	0.30 ic			0.00				0.007 0.007		0.302 0.313
5.22	521	364.22	0.31 ic	0.31 ic			0.00 0.00				0.007		0.323
5.28 5.34	526 531	364.28 364.34	0.32 ic 0.33 ic	0.32 ic 0.33 ic			0.00				0.007		0.332
5.40	536	364.40	0.34 ic	0.33 ic			0.00				0.007		0.342
5.46	539	364.46	0.34 ic	0.34 ic			0.00				0.007		0.351
5.52	542	364.52	0.35 ic	0.35 ic			0.00				0.007		0.360
5.58	545	364.58	0.36 ic	0.36 ic			0.00				0.007		0.369
5.64	548	364.64	0.37 ic	0.37 ic			0.00 0.00				0.007 0.007		0.378 0.386
5.70 5.76	551 554	364.70 364.76	0.38 ic 0.39 ic	0.38 ic 0.39 ic			0.00				0.007		0.394
5.76 5.82	557	364.76 364.82	0.39 ic 0.40 ic	0.39 ic			0.00				0.008		0.402
5.88	560	364.88	0.40 ic	0.40 ic			0.00				0.008	}	0.410
5.94	563	364.94	0.43 ic	0.41 ic			0.02				0.008		0.443
6.00	566	365.00	0.61 ic	0.42 ic			0.20				0.009	)	0.624

...End

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 5

**Total Post** 

Hydrograph type Storm frequency Time interval Inflow hyds. = Combine


= 1 yrs = 1 min = 2, 4 Peak discharge Time to peak = 0.203 cfs = 15 min

Hyd. volume

= 183 cuft

Contrib. drain. area =

= 0.121 ac



# Hydrograph Summary Report Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.579	1	15	521				Pre Development
2	Rational	0.234	1	15	210			ngo man ang man lan 🚾	Post Uncontrolled
3	Rational	0.491	1	15	442				Controlled SWM Basin #1
4	Reservoir	0.030	1	29	11	3	363.29	432	SWM BASIN #1
5	Combine	0.234	1	15	222	2, 4		•	Total Post
<b> </b>									
1	4041.gpw				Retu	rn Period: 2	Year	Thursda	y, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 4.596 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.579 cfs
Time to peak = 15 min
Hyd. volume = 521 cuft
Runoff coeff. = 0.55
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 2

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 4.596 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.234 cfs
Time to peak = 15 min
Hyd. volume = 210 cuft
Runoff coeff. = 0.42
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 4.596 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.491 cfs
Time to peak = 15 min
Hyd. volume = 442 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir

= 2 yrs = 1 min

= 3 - Controlled SWM Basin #1 Max. Elevation

= SWM #1


Peak discharge Time to peak = 0.030 cfs = 29 min

Hyd. volume = 11 cuft

Max. Elevation = 363.29 ft

Max. Storage = 432 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 5

**Total Post** 

Hydrograph type Storm frequency Time interval

Inflow hyds.

= Combine

= 2 yrs = 1 min = 2, 4 Peak discharge


= 0.234 cfs

Time to peak Hyd. volume

= 15 min = 222 cuft

Contrib. drain. area

= 0.121 ac



# Hydrograph Summary Report Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

lyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.679	1	15	611				Pre Development
2	Rational	0.274	1	15	247				Post Uncontrolled
3	Rational	0.576	1	15	519				Controlled SWM Basin #1
4	Reservoir	0.159	1	26	86	3	363.56	460	SWM BASIN #1
5	Combine	0.274	1	15	332	2, 4	_ n,		Total Post
ı									
									y, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 5 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 5.390 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.679 cfs
Time to peak = 15 min
Hyd. volume = 611 cuft
Runoff coeff. = 0.55
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 2

Post Uncontrolled

Hydrograph type Storm frequency Time interval Drainage area

Intensity **IDF** Curve = Rational

= 5 yrs= 1 min = 0.121 ac= 5.390 in/hr = reg5.IDF


Peak discharge Time to peak

= 0.274 cfs= 15 min Hyd. volume = 247 cuft

Runoff coeff. Tc by User

= 0.42 $= 5.00 \, \text{min}$ 

Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 5 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 5.390 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.576 cfs
Time to peak = 15 min
Hyd. volume = 519 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval Inflow hyd. No.

Reservoir name

= Reservoir = 5 yrs

= 1 min = 3 - Controlled SWM Basin #1 Max. Elevation


= SWM #1

Peak discharge = 0.159 cfs

Time to peak = 26 min Hyd. volume = 86 cuft  $= 363.56 \, \mathrm{ft}$ 

Max. Storage = 460 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 5

Inflow hyds.

**Total Post** 

Hydrograph type Storm frequency Time interval = Combine

= 5 yrs = 1 min

 $= 1 \, \text{min}$ = 2, 4


Peak discharge

= 0.274 cfs = 15 min

Time to peak Hyd. volume

= 332 cuft

Contrib. drain. area = 0.121 ac



# Hydrograph Summary Report Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.768	1	15	691				Pre Development
2	Rational	0.310	1	15	279				Post Uncontrolled
3	Rational	0.652	1	15	587				Controlled SWM Basin #1
4	Reservoir	0.225	1	25	153	3	363.81	486	SWM BASIN #1
5	Combine	0.365	1	22	432	2, 4			Total Post
i									
						urn Period:			ay, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 6.096 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.768 cfs
Time to peak = 15 min
Hyd. volume = 691 cuft
Runoff coeff. = 0.55
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 2

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 6.096 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.310 cfs
Time to peak = 15 min
Hyd. volume = 279 cuft
Runoff coeff. = 0.42
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 6.096 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.652 cfs
Time to peak = 15 min
Hyd. volume = 587 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

= 0.225 cfs

= 25 min

### Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir

= 10 yrs

 $= 1 \min$ 

= 3 - Controlled SWM Basin #1 Max. Elevation


= SWM #1

Hyd. volume

Peak discharge Time to peak

= 153 cuft  $= 363.81 \, \mathrm{ft}$ = 486 cuft Max. Storage

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 5

**Total Post** 

Hydrograph type = Combine
Storm frequency = 10 yrs
Time interval = 1 min
Inflow hyds. = 2, 4

Peak discharge = 0.365 cfs
Time to peak = 22 min
Hyd. volume = 432 cuft
Contrib. drain. area = 0.121 ac



# Hydrograph Summary Report Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description	
1	Rational	0.856	1	15	770				Pre Development	
2	Rational	0.345	1	15	311				Post Uncontrolled	
3	Rational	0.726	1	15	654				Controlled SWM Basin #1	
4	Reservoir	0.286	1	24	219	3	364.11	511	SWM BASIN #1	
5	Combine	0.460	1	21	530	2, 4	The state of the s	<b>G</b> proposed <b>G</b>	Total Post	
	14041.gpw				Retu	Return Period: 25 Year			Thursday, 05 / 1 / 2014	

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

= 0.856 cfs

= 15 min

= 0.55

= 3/3


= 770 cuft

 $= 5.00 \, \text{min}$ 

#### Hyd. No. 1

Pre Development

Hydrograph type = Rational Peak discharge Storm frequency Time to peak = 25 yrsTime interval Hyd. volume = 1 min Runoff coeff. Drainage area = 0.229 acTc by User = 6.794 in/hrIntensity **IDF** Curve = reg5.IDF Asc/Rec limb fact



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 2

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 25 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 6.794 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.345 cfs
Time to peak = 15 min
Hyd. volume = 311 cuft
Runoff coeff. = 0.42
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 25 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 6.794 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.726 cfs
Time to peak = 15 min
Hyd. volume = 654 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval Inflow hyd. No.

Reservoir name

= Reservoir = 25 yrs

= 1 min


= SWM #1

Peak discharge Time to peak

= 0.286 cfs= 24 min

Hyd. volume = 219 cuft = 3 - Controlled SWM Basin #1 Max. Elevation = 364.11 ftMax. Storage = 511 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 5

**Total Post** 

Hydrograph type Storm frequency Time interval Combine25 yrs

Time interval = 1 min Inflow hyds. = 2, 4


Peak discharge Time to peak = 0.460 cfs = 21 min

Hyd. volume

= 530 cuft

Contrib. drain. area

= 0.121 ac



# Hydrograph Summary Report Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.956	1	15	861				Pre Development
2	Rational	0.386	1	15	347		,		Post Uncontrolled
3	Rational	0.812	1	15	731				Controlled SWM Basin #1
4	Reservoir	0.350	1	23	295	3	364.51	541	SWM BASIN #1
5	Combine	0.559	1	20	642	2, 4	artica service		Total Post
14	-041.gpw				Retur	n Period: 50	) Year	Thursday	7, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 7.592 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.956 cfs
Time to peak = 15 min
Hyd. volume = 861 cuft
Runoff coeff. = 0.55
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 2

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 7.592 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.386 cfs
Time to peak = 15 min
Hyd. volume = 347 cuft
Runoff coeff. = 0.42
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 3

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 7.592 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.812 cfs
Time to peak = 15 min
Hyd. volume = 731 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

## Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir = 50 yrs

 $= 1 \, \text{min}$ 

= SWM #1


Peak discharge Time to peak

= 0.350 cfs= 23 min

Hyd. volume = 295 cuft = 3 - Controlled SWM Basin #1 Max. Elevation  $= 364.51 \, \mathrm{ft}$ 

= 541 cuft Max. Storage

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

## Hyd. No. 5

Inflow hyds.

**Total Post** 

Hydrograph type Storm frequency Time interval = Combine = 50 yrs

= 1 min = 2, 4 Peak discharge


= 0.559 cfs = 20 min

Time to peak Hyd. volume

= 642 cuft

Contrib. drain. area

= 0.121 ac



# Hydrograph Summary Report Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

•	•					nyuranow	nyurograpits Ex	erision for Addoor	7.25 CIVII 020 2011 031 Latereet, 1111
Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	1.032	1	15	929				Pre Development
2	Rational	0.417	1	15	375				Post Uncontrolled
3	Rational	0.876	1	15	789				Controlled SWM Basin #1
4	Reservoir	0.422	1	23	352	3	364.93	561	SWM BASIN #1
5	Combine	0.641	1	21	727	2, 4			Total Post
1	4041.gpw				Retu	rn Period: 1	100 Year	I ihursda	y, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014


## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 100 yrs
Time interval = 1 min
Drainage area = 0.229 ac
Intensity = 8.196 in/hr

Intensity = 8.196 in/ IDF Curve = reg5.IDF Peak discharge = 1.032 cfs
Time to peak = 15 min
Hyd. volume = 929 cuft
Runoff coeff. = 0.55

Tc by User = 5.00 minAsc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

= 0.417 cfs

= 15 min

= 0.42

= 3/3

= 375 cuft

= 5.00 min

## Hyd. No. 2


**IDF** Curve

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 100 yrs
Time interval = 1 min
Drainage area = 0.121 ac
Intensity = 8.196 in/le

= 100 yrs Time to peak
= 1 min Hyd. volume
= 0.121 ac Runoff coeff.
= 8.196 in/hr Tc by User
= reg5.IDF Asc/Rec limb fact

Peak discharge



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 3

#### Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 100 yrs
Time interval = 1 min
Drainage area = 0.108 ac
Intensity = 8.196 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.876 cfs
Time to peak = 15 min
Hyd. volume = 789 cuft
Runoff coeff. = 0.99
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 4

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir

= 100 yrs = 1 min

= 3 - Controlled SWM Basin #1


= SWM #1

Peak discharge Time to peak

ge = 0.422 cfs = 23 min

Hyd. volume = 352 cuft
Max. Elevation = 364.93 ft
Max. Storage = 561 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

## Hyd. No. 5

**Total Post** 

Hydrograph type Storm frequency Time interval

Inflow hyds.

= Combine

= 100 yrs = 1 min

= 2, 4

Peak discharge


= 0.641 cfs

Time to peak Hyd. volume

= 21 min = 727 cuft

Contrib. drain. area

= 0.121 ac



# **Hydraflow Rainfall Report**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

Return Period	Intensity-Duration-Frequency Equation Coefficients (FHA)								
(Yrs)	В	D	E	(N/A)					
1	22.1293	5.9000	0.7167	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
2	26.2877	6.4000	0.7166						
3	0.0000	0.000	0.0000						
5	25.3184	5.4000	0.6606	producted to the second					
10	50.7545	9.8000	0.7865						
25	27.8762	5.2000	0.6079						
50	41.8042	8.4000	0.6573						
100	129.6326	19.8000	0.8599						

File name: reg5.IDF

### Intensity = $B / (Tc + D)^E$

Return Period (Yrs)	Intensity Values (in/hr)											
	5 min	10	15	20	25	30	35	40	45	50	55	60
1	3.99	3.05	2.51	2.15	1.89	1.70	1.55	1.43	1.32	1.24	1.16	1.10
2	4.60	3.54	2.93	2.52	2.22	2.00	1.82	1.68	1.56	1.46	1.38	1.30
3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
5	5.39	4.16	3.45	2.99	2.65	2.40	2.20	2.04	1.90	1.79	1.69	1.60
10	6.10	4.85	4.06	3.52	3.11	2.80	2.55	2.35	2.18	2.03	1.91	1.80
25	6.79	5.33	4.48	3.92	3.51	3.20	2.95	2.75	2.58	2.43	2.31	2.20
50	7.59	6.16	5.26	4.63	4.16	3.80	3.51	3.26	3.06	2.88	2.73	2.60
100	8.20	7.00	6.12	5.46	4.93	4.50	4.14	3.84	3.59	3.37	3.17	3.00

Tc = time in minutes. Values may exceed 60.

Precip. file name: LMT.pcp

	Rainfall Precipitation Table (in)									
Storm Distribution	1-yr	2-yr	3-уг	5-уг	10-yr	25-yr	50-yr	100-yr		
SCS 24-hour	2.80	3.20	0.00	4.20	5.00	5.80	6.50	7.20		
SCS 6-Hr	1.40	1.80	0.00	0.00	2.60	0.00	0.00	4.00		
Huff-1st	0.00	1.55	0.00	2.75	4.00	5.38	6.50	8.00		
Huff-2nd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
Huff-3rd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
Huff-4th	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
Huff-Indy	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
Custom	0.00	1.75	0.00	2.80	3.90	5.25	6.00	7.10		



#### Excellence Delivered As Promised

#### **MEMORANDUM**

Date: May 28, 2014

To: Radnor Township Planning Commission

From: Roger Phillips, PE

cc: Stephen Norcini, P.E. – Director of Public Works

Kevin W. Kochanski, RLA, CZO - Director of Community Development

Peter Nelson, Esq. - Grim, Biehn, and Thatcher Amy B. Kaminski, P.E. - Gilmore & Associates, Inc. Suzan Jones - Radnor Township Engineering Department

William Miller – Radnor Township Codes Official Ray Daly – Radnor Township Codes Official

RE: Wayne Elementary School

Radnor Township School District - Applicant

Date Accepted: May 5, 2014

90 Day Expiration: August 8, 2014

Gannett Fleming, Inc. has completed a review of the Wayne Elementary School Preliminary/Final Land Development Plans for compliance with the Radnor Township Code.

The existing property is located in the PLU zoning district. The applicant is proposing to construct a one story building addition to the Wayne Elementary School and the removal of an existing building, walk and deck.

This Land Development Application is subject to Zoning, Subdivision and Land Development, Stormwater Management, and other applicable codes of the Township of Radnor.

The applicant has indicated that the following waivers will be requested from the Subdivision and Land Development Code:

- §255-12 Formal request from the land development process
- §255-20.B.5 To not provide the transportation impact study
- §255-21(n) Modification to allow an aerial photograph to depict features within 500' of property

Plans Prepared By: N

Momenee & Associates, Inc.

Dated:

05/02/2014, No Revisions

#### **Gannett Fleming**

#### I Zoning

1. §280-103 – Off-street parking calculations should be provided that indicate the number of additional parking spaces required for this project.

#### II Stormwater Management

- 1. A general note shall be added to the plans indicating that a grading plan and erosion sediment and control plans will be submitted and approved prior to issuing any building permits. Any revisions to the size or location of the individual structures or other features will be addressed at that time, and a final approval of the stormwater management plan will be required as part of the Grading Permit process.
- 2. Percolation tests must be provided to indicate that the stormwater facility will be able to drain within 96 hours. Final design and sizing of the stormwater facility should be based on the results of the percolation tests.
- 3. The Hydrograph reports for the 1-100 year storm events have inconsistent intensity values with respect to the existing conditions and the controlled post conditions. Provide and explanation of these intensities.

#### III General Comments

1. The cover letter from Momenee and Associates indicates that the new improvements will create an overall decrease of the total impervious cover on the property. Plan sheet 2 indicates that there is a new increase of 6,323 SF and plan sheet 5 indicates and net decrease in impervious coverage of 2,383 SF.

Should the Planning Commission consider recommending approval of this project, we recommend that the recommendation be conditioned on requiring the applicant to satisfactorily address the above comments.

If you have any questions or require any additional information, please contact me.

Very truly yours,

GANNETT FLEMING, INC.

Roger A. Phillips, P.E. Senior Project Manager



#### GILMORE & ASSOCIATES, INC.

ENGINEERING & CONSULTING SERVICES

#### **MEMORANDUM**

Date:

May 23, 2014

To:

Steve Norcini, P.E.

Radnor Township Public Works Director

From:

Damon Drummond P.E., PTOE

**G&A Senior Transportation Engineer** 

cc:

Roger Phillips, P.E. - Gannett Fleming, Inc., Senior Project Manager Amy Kaminski, P.E. PTOE- G&A Department Manager of Transportation

Kristin Norwood, P.E. - G&A Senior Transportation Engineer

Reference:

Wayne Elementary School (TMP 36-19-230-000)

651 West Wayne Avenue

Preliminary/Final Land Development Review

G&A# 14-05021

Pursuant to your request, Gilmore & Associates, Inc. has completed a transportation review of the referenced Preliminary/Final Land Development Plan for Wayne Elementary School. The applicant proposes to construct a building addition and walkway improvements at the existing school situated on a 19.939 acre parcel. In addition, the applicant proposes to remove the current building being used for overflow classrooms. We offer the following for Radnor Township's consideration:

#### A. REVIEWED MATERIALS

 Preliminary/Final Land Development Plans for Wayne Elementary School dated May 02, 2014, prepared for Radnor Township School District by Momenee and Associates, Inc. (8 sheets).

#### B. REQUESTED SALDO WAIVERS

- 1. §255-12: Waiver request from the formal land development process.
- 2. §255-20.B.5: Waiver request from providing a Transportation Impact Study.
- 3. §255-21(n): Waiver request to use aerial photograph to depict features within 500' of the property.

#### C. PRELIMINARY/FINAL LAND DEVELOPMENT PLAN REVIEW COMMENTS

1. §255-20.A(5): The plan should clearly indicate which features are existing and which are proposed. Provide shading or hatching or another technique to clearly indicate the proposed building construction.

Steve Norcini, P.E. Wayne Elementary School May 23, 2014

- 2. §255-20.B(5): Provide clarification as whether the expansion is to accommodate additional students and/or staff and therefore generating additional trips.
- 3. §255-37: Ensure that the proposed walkway is ADA compliant. Provide a detail of the walkway indicating the width, grades and cross-slopes.
- 4. Provide existing driveway widths and radii. Include arrows showing the existing traffic circulation within the site and distinguish between bus and auto/carpool traffic. Ensure that adequate access can be maintained for both vehicular and pedestrian traffic.
- 5. The existing parking lot on the eastern corner of the site does not provide circulation with dead end parking. Consider removing parking stalls at the end the middle of the aisle near Meadowood Avenue to complete circulation through the lot.

If you have any questions regarding the above, please contact this office.

ELAINE P. SCHAEFER

President

JAMES C. HIGGINS

Vice-President

WILLIAM A. SPINGLER

DONALD E. CURLEY

JOHN FISHER

JOHN NAGLE

RICHARD F. BOOKER



# RADNOR TOWNSHIP 301 IVEN AVENUE WAYNE, PENNSYLVANIA 19087-5297

Phone (610) 688-5600 Fax (610) 971-0450 www.radnor.com ROBERT A. ZIENKOWSKI

Township Manager Township Secretary

JOHN B. RICE, ESQ. Solicitor

JOHN E. OSBORNE
Treasurer

May 13, 2014

Leo Bernabei Radnor Township School District 135 S. Wayne Ave. Wayne, PA 19087

**RE:** Wayne Elementary School

Land Development Application #2014-D-06 Preliminary Plan

Dear Mr. Bernabei:

In accordance with Section 255-18 of the Code of the Township of Radnor, we have performed a completeness review of your land development application to construct a building addition to the Wayne Elementary School, and have determined your application to be administratively complete. Therefore, I have accepted the application for preliminary revised plan for review by the Township Staff, Shade Tree Commission, Planning Commission, and Board of Commissioners.

These plans are available for public viewing in the Engineering Department. These plans will be reviewed by the Planning Commission at their meeting on **Monday June 2, 2014**. Subsequent to the Planning Commission meeting, your plan will be reviewed by the Board of Commissioners. You or your representative should plan to attend all scheduled meetings.

If the Planning Commission takes action, your plan will then be reviewed by the Board of Commissioners at a future meeting. These dates will be provided to you once it is placed on the agenda.

If you have any questions or require any additional information, please contact me.

Sincerely,

Roger A. Phillips, PE Township Engineer

CC: Momenee & Associates, Inc.

924 COUNTY LINE ROAD • BRYN MAWR, PENNSYLVANIA 19010 (610) 527-3030 • FAX (610) 527-9008

E-MAIL: info@momenee.com

www.momenee.com

May 2, 2014

Mr. Roger Phillips, P.E., Township Engineer Radnor Township 301 Iven Avenue Wayne, PA 19087

RE: Ithan Elementary School
Wayne Elementary School
Preliminary / Final Land Development Applications
Radnor Township, Delaware County

Our File No. 14-041 Our File No. 14-042

Dear Mr. Phillips:

On behalf of the Radnor Township School District, we are submitting land development applications for improvements associated with the Ithan Elementary School property and the Wayne Elementary School property. Along with this letter please find the following:

#### Ithan Elementary School

- One (1) copy of the signed Land Development Application,
- One (1) copy of the Delaware County Planning Commission review application,
- · One (1) copy of the deed for the property,
- One (1) copy of the title report,
- A check in the amount of \$300 payable to "Treasurer of Delaware County",
- A check in the amount of \$1,550 payable to "Radnor Township",
- A check in the amount of \$10,000 payable to "Radnor Township",
- Two (2) copies of the Post Construction Stormwater Management Report,
- 35 copies of the Preliminary/Final Land Development Plans.

The Radnor Township School District proposes to construct a building addition to the Ithan Elementary School and to relocate a walkway on the property. The new one-story addition will consist of two new classrooms. The new improvements will create a slight increase in the total impervious cover on the property.

#### Wayne Elementary School

- One (1) copy of the signed Land Development Application,
- One (1) copy of the Delaware County Planning Commission review application,
- One (1) copy of the deed for the property,
- A check in the amount of \$400 payable to "Treasurer of Delaware County",
- A check in the amount of \$1,550 payable to "Radnor Township",
- A check in the amount of \$10,000 payable to "Radnor Township",
- Two (2) copies of the Post Construction Stormwater Management Report
- 35 copies of the Preliminary/Final Land Development Plans.

The Radnor Township School District proposes to construct a building addition to the Wayne Elementary School. The new one-story addition will consist of a new classroom and other multipurpose rooms. In addition, the existing one-story building currently used for overflow classrooms will be removed. The new improvements will create an overall decrease in the total impervious cover on the property.

By filing these applications, the Radnor Township School District wishes to have these matters placed on the June 2, 2014 agenda of the Planning Commission meeting and the June meetings of the Board of Commissioners. If you have any questions or require any further information, please do not hesitate to contact me. Thank you for your attention to this matter.

Very truly yours,

MOMENEE AND ASSOCIATES, INC.

Kevin R. Momenee, P.E., P.L.S.

14042L01.doc

ce: Leo Bernabei - Radnor Township School District

RADNOR TOWNSHIP 301 IVEN AVE WAYNE PA 19087 P) 610 688-5600 F) 610 971-0450 WWW.RADNOR.COM

## SUBDIVISION ~~ LAND DEVELOPMENT

Location of Property Wayne	Elementary School	, 651 West Wayne Avenue, Wayne.	<u>, Pa 19087</u>
Zoning District PLU		pplication No.	
		(Twp.	Use)
Fee \$1,550.00	_Ward No. <u>6-2</u>	Is property in HARB D	istrict <u>No</u>
Applicant: (Choose one)	Owner 🔽	Equitable Owner	
Name ZAONOR T	bwasme Se	HOOL DISTRICT	
Address 35 S.	mayne ave	. WAYNE, PA 19087	1
		· 902 · 0207 Cell	
-			
Email LED. BER	NAVE I B ICA	5D. 07-G	-101
Designer: (Choose one)	Engineer 🛚	Surveyor	
Name Kevin R. Momenee, I	P.E., P.L.S.		····
Address 924 County Line R	oad, Bryn Mawr, Pa	19010	
Telephone 610-527-3030	Fax_610-52	27-9008 Cell	
		Area of disturbance 0.4 ac	
Area or property 19.939 ac		The of distalbance of the	
Number of proposed building	gs <u>1</u>	Proposed use of property <u>Institution</u>	nal
Number of proposed lots 1		-	
Plan Status: Sketch Plan	Preliminar	y 🛛 Final 🗌 Revise	d 🗌

Are there any requirements of Chapter 255 (SALDO) not being adhered to?
Explain the reason for noncompliance.
255-12: Waiver request from the formal land Levelopment process
255-20, B.S. To not provide a Transportation Impact Study
255-12: Waiver request from the formal land development process 255-20.B.B. To not provide a Transportation Impact Study 255-20.Cn) - modification to allow an aerial Photograph to defice features
Within SUD of Devocale
Are there any infringements of Chapter 280 (Zoning), and if so what and why?
7 ( 3/)
ND
Individual/Corporation/Partnership Name
RADNOR TOWNSHIP SCHOOL DISTRICT
I do hereby certify that I am the owner, equitable owner or authorized representative of the
property which is the subject of this application.
Print Name //mothy E. Vail
Digital Taxas Constitution of the Constitution
Print Name //Mothy E. Vai
Time traine
By filing this application, you are hereby granting permission to Township officials to visit
the site for review purposes.

All requirements of Chapter 255 (Subdivision of Lane) of the Code of the Township of Radnor must be complied with whether or not indicated in this

NOTE:

application.

## **DELAWARE COUNTY PLANNING COMMISSION**

## **APPLICATION FOR ACT 247 REVIEW**

Incomplete applications will be returned and will not be considered "received" until all required information is provided.

Please type or print legibly

DEVELOPER/APPL	ICANT						
Name Radnor Township	School District	E-mail leo	E-mail leo.bernabel@rtsd.org				
Address_135 S. Wayne	Avenue Wayne, I	PA 19087	Phone 610-688	-8100 Ext 6103			
Name of Development	Wayne Elementary Sch	ool					
Municipality_Radnor Tow	mship						
ARCHITECT, ENGIN	·		one 610-527-3030				
Address 924 County Li	ne Road, Bryn M	awr, Pa 19010	nomenee@momenee.com				
Contact Town Williams	30, 1, 12, 1, 12, 12, 1	Utilitie					
Type of Review	Plan Status	Existing	Proposed	Environmental			
Zoning Change	☐ Sketch	☑ Public Sewerage	Public Sewerage	Characteristics			
✓ Land Development	✓ Preliminary	☐ Private Sewerag	e Private Sewerage	☐ Wetlands			
Subdivision	☐ Final	☑ Public Water	☑ Public Water	☐ Floodplain			
☐ PRD	☐ Tentative	☐ Private Water	Private Water	☑ Steep Slopes			
Zoning District PLU			Tax Map # 3 6 / 19 / 230  Tax Folio # 3 6 / 06 / 03988	_ / 50_			

## WRITING "SEE ATTACHED PLAN" IS NOT ACCEPTABLE. Existing and/or Proposed Use of Site/Buildings: Existing elementary school to be expanded by the construction of an addition to the existing school building consisting of new classrooms and other facilities along with new walkways and associated improvements. Total Site Area Acres 58,528 Square Feet Size of All Existing Buildings 65,728 Size of All Proposed Buildings Square Feet Size of Buildings to be Demolished 0 Square Feet LED BERNADES Print Developer's Name MUNICIPAL SECTION ALL APPLICATIONS AND THEIR CONTENT ARE A MUNICIPAL RESPONSIBILITY. Local Planning Commission Regular Meeting\_ Local Governing Body Regular Meeting Municipal request for DCPD staff comments prior to DCPC meeting, to meet municipal meeting date: Actual Date Needed IMPORTANT: If previously submitted, show assigned DCPD File #\_\_\_\_\_ Print Name and Title of Designated Municipal Official Phone Number Official's Signature Date FOR DCPD USE ONLY Review Fee: Check # Amount \$ Date Received

STATEMENT OF INTENT

Applications with original signatures must be submitted to DCPD.

924 COUNTY LINE ROAD • BRYN MAWR, PENNSYLVANIA 19010 (610) 527-3030 • FAX (610) 527-9008

E-MAIL: info@momenee.com

www.momenee.com

# POST CONSTRUCTION STORMWATER MANAGEMENT REPORT FOR

# WAYNE ELEMENTARY SCHOOL

TOWNSHIP OF RADNOR

**JOB #14-042** 

 $\mathbf{BY}$ 

MOMENEE AND ASSOCIATES, INC,

924 COUNTY LINE ROAD

BRYN MAWR, PA 19010

MAY 2, 2014

# PROJECT NARRATIVE WAYNE ELEMENTARY SCHOOL

The Wayne Elementary School is a 19.939-acre development located northwest of the intersection of Maplewood Avenue and Wayne Avenue in Radnor Township. It is proposed to construct an addition to the existing school building along with other associated improvements. Some existing walkways and other impervious areas are proposed to be removed. The project will create 7,264 SF of new and/or replacement impervious cover. Due to Radnor Township regulations, storm water management will be provided. The site is developed under the provisions of Radnor Township's Regulations. These calculations are included as part of a Grading Permit for the site.

Storm water management is provided one perforated pipe system sized to control the increase in storm water runoff from the developed sub-basin. This site is located in the Darby Creek watershed District A; as a result, several stormwater management guidelines were met. The increase in storm water runoff for the 2-year storm event must be recharged into the ground via percolation. Water quality treatment must be provided based on the township's calculation formula. The rate control through the 100-year storm must be provided as well as making the following reductions: the 2-year post rate shall be reduced to the 1-year pre rate. The stormwater management facilities are designed for the new and/or replacement impervious coverage plus an additional 736 square feet of additional impervious area to allow for future development. If this impervious cover is developed in the future 286 SF may be directed to the SWM system, and 450 SF may remain uncontrolled.


The lot is graded so that all developed portions are controlled by the perforated pipe system. Stormwater management system #1 consists of 90 linear feet of 48" fully perforated corrugated metal pipe. The system will be installed down grade of the new building addition and will collect and control the runoff from the new roof area and some grass areas via roof downspout leaders, a small park grate, and conveyance piping. In addition to the proposed improvements an additional impervious area of 736 square feet was included in the calculations to allow for possible future development. Discharge from the pipe system is piped to a proposed bubble-up spreader where it may be dissipated to grade in an un-concentrated manner. The pipe system is designed to provide groundwater recharge for the volume generated by the 2-year storm event for the new and/or replacement impervious surfaces.

In order to size the on lot storm facilities to contain the volume of runoff increase for the 2-year storm, the developed portion of the lot was evaluated by the Universal Rational method to determine the volume increase in runoff. C coefficients were assigned to the developed portion of the lot based on soil conditions and vegetation. The subbasin was established based on the location of the proposed storm facilities and the contributory post development watershed. Preliminary system design was based on the volume required to recharge the increase in the 2-year storm runoff generated by the proposed impervious cover. Once the volume increase was calculated, the storm facilities were sized to provide this minimum storage volume. Hydrographs were then calculated

for both pre and post development conditions to determine the need for rate control. Times of concentration were established for the subbasin and each development condition and used to determine the peak rates of runoff.

The perforated pipe system was then further refined to provide control of the post development runoff rates. Post development flows were routed through the pipe system and volumes were adjusted along with outlet controls to limit the post development runoff to rates required by township ordinances.

An attached table summarizes the analysis of the lot. Detailed calculations and support data are included as part of this report.




PRE DEVELOPMENT DRAINAGE AREA MAP WAYNE ELEMENTARY SCHOOL

ASSOCIATES, IN C MOMENEE &

ENGINEERS AND LAND SURVEYORS CIVIL 924 COUNTY LINE ROAD, BRYN MAWR, PA 19010 PHONE: (610) 527-3030 FAX: (610) 527-9008

SHEET NO. OF SCALE: 1" = 50"FILE NO.: 14-042



WAYNE ELEMENTARY SCHOOL

ASSOCIATES, IN C MOMENEE &

ENGINEERS AND LAND SURVEYORS CIVIL 924 COUNTY LINE ROAD, BRYN MAWR, PA 19010 PHONE: (610) 527-3030 FAX: (610) 527-9008

		_
DATE:	MAY 2, 2014	
	SHEET NO.	
	2	
	_	
	OF 2	
SCA	LE: 1" = 50'	
FILE	NO.: 14-042	

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

WAYNE ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP

**DELAWARE COUNTY** 

SUMMARY OF SITE RUNOFF:

PRE-DEVELOPMENT CONDITIONS

25-YR 50-YR 100-YR 1-YR 2-YR 5-YR 10-YR 0.88 0.42 0.48 0.57 0.64 0.71 0.81 **ENTIRE WATERSHED:** 0.88 0.64 0.71 0.81 0.42 0.42 0.57 ALLOWABLE DISCHARGE:

POST DEVELOPMENT CONDITIONS

10-YR 25-YR 50-YR 100-YR 2-YR 5-YR 1-YR 0.45 0.00 0.10 0.22 0.31 0.00 0.00 CONTROLLED SUBAREA #1: 0.36 0.40 0.19 0.22 0.26 0.29 0.32 **UNCONTROLLED AREA:** 0.54 0.67 0.85 0.39 0.22 0.26 0.19 TOTAL POST DEVELOPMENT: 0.03 0.25 0.17 0.14 ACTUAL POST DEVELOPMENT REDUCTION: 0.23 0.26 0.31

**VOLUME CONTROL SUMMARY (2-YR):** 

PREDEVELOPMENT:

520 CF

CONTROLLED AREA:

744 CF

**UNCONTROLLED AREA:** 

235 CF

**RECHARGE REQUIRED:** 

459 CF

SWMS VOLUME IN:

744 CF

SWMS VOLUME OUT:

0 CF

**RECHARGE PROVIDED:** 

744 CF

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

WAYNE ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP DELAWARE COUNTY

C CALCULATIONS FOR PREDEVELOPMENT AREA: SITE 0.30 PRE-DEVELOPMENT C: 16182 SF 0.371 ACRES PRE-DEVELOPMENT AREA: 15136 SF C = 0.25SOIL TYPE B - MEADOW C = 0.991046 SF **IMPERVIOUS** 0 SF C = 0.99IMPERVIOUS (WITHIN R/W) 0.84 CONTROLLED SUBAREA #1 C: 0.214 ACRES 9341 SF CONTROLLED SUBAREA #1 AREA: C = 0.251949 SF SOIL TYPE B - LAWN C = 0.9976.1% 7106 SF **IMPERVIOUS** C = 0.990 SF 0.0% IMPERVIOUS (WITHIN R/W) 286 SF 3.1% C = 0.99IMPERVIOUS (FUTURE) 0.32 UNCONTROLLED C: 0.157 ACRES 6841 SF UNCONTROLLED AREA: 6233 SF C = 0.25SOIL TYPE B - LAWN 158 SF C = 0.99**IMPERVIOUS** 0 SF C = 0.99IMPERVIOUS (WITHIN R/W) C = 0.99450 SF IMPERVIOUS (FUTURE) 0.62 POST-DEVELOPMENT C: 0.371 ACRES 16182 SF POST-DEVELOPMENT AREA: C = 0.25 8182 SF SOIL TYPE B - LAWN 7264 SF C = 0.99**IMPERVIOUS** C = 0.990 SF IMPERVIOUS (WITHIN R/W) 736 SF C = 0.99IMPERVIOUS (FUTURE)

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

WAYNE ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP

DELAWARE COUNTY

#### WATER QUALITY VOLUME

 $WQ_V = [P*R_V*A]/12$ 

P = 1 INCH

A = AREA OF PROJECT CONTRIBUTING TO WATER QUALITY BMP's

 $R_V = 0.05 + 0.0091$ 

I = PERCENT OF IMPERVIOUS COVERAGE

A≔

0.214 ACRES

|=

79.30 %

 $R_V =$ 

0.7637

 $WQ_V =$ 

0.0136 ACRE-FEET

 $WQ_V =$ 

593 CF

### RECHARGE CALCULATIONS FOR THE FIRST INCH OF RUNOFF GENERATED FROM THE PROPOSED IMPROVEMENTS

FORMULA USED: Rev = I \* Proposed Impervious Area (square feet) / 12 (inches/foot)

WHERE:

| =

1.0 inch

Proposed Impervious Area =

8000 square feet

Rev =

667 cubic feet

#### INFILTRATION VOLUME PROVIDED (FT^3):

Volume In (ft^3) Volume

Recharge Volume (ft^3)

SWM #1

744

Out (ft<sup>3</sup>) 0

744

TOTAL:

744

924 COUNTY LINE ROAD BRYN MAWR, PA 19010

#### 4' DIAMETER PERFORATED CMP

LENGTH OF

4 FT CMP = 90 FT

TOTAL VOLUME OF STORAGE PROVIDED = 1126.2 CF

#### AREA OF STORAGE:

ELEV.	PIPE HEIGHT (FT)	WIDTH OF PIPE (FT)	PIPE STRG. (SF)	VOLUME STRG. (CF)
375.00	Q	0	0.0	0.0
375.10	0.1	1.25	112.4	5.6
375.20	0.2	1.74	156.9	19.1
375.30	0.3	2.11	189.6	36.4
375.40	0.4	2.40	216.0	56.7
375.50	0.5	2.65	238.1	79.4
375.60	0.6	2.86	257.1	104.2
375,70	0.7	3,04	273.6	130.7
375.80	8.0	3,20	288.0	158.8
375.90	0.9	3.34	300.7	188.2
376.00	1.0	3,46	311.8	218.8
376.10	1.1	3.57	321.5	250.5
376.20	1.2	3.67	329.9	283.1
376.30	1.3	3.75	337.2	316.4
376.40	1.4	3,82	343.4	350.5
376.50	1.5	3,87	348.6	385.1
376.60	1.6	3,92	352.7	420.1
376.70	1.7	3.95	355.9	455.6
376.80	1.8	3,98	358.2	491.3
376.90	1.9	3.99	359.5	527.1
377.00	2.0	4.00	360.0	563.1
377.10	2.1	3,99	359,5	599.1
377.20	2.2	3.98	358.2	635.0
377.30	2.3	3.95	355.9	670.7
377.40	2.4	3.92	352.7	706.1
377.50	2.5	3.87	348.6	741.2
377.60	2.6	3.82	343.4	775.8
377,70	2.7	3.75	337.2	809.8
377.80	2.8	3,67	329.9	843.2
377.90	2.9	3.57	321.5	875.8
378,00	3	3.46	311.8	907.4
378.10	3.1	3.34	300.7	938.0
378.20	3.2	3.20	288.0	967.5

378.30	3.3	3.04	273.6	995.6
378.40	3.4	2.86	257.1	1022.1
378.50	3,5	2.65	238.1	1046.8
378.60	3.6	2.40	216.0	1069.6
378.70	3.7	2.11	189.6	1089.8
378.80	3.8	1.74	156.9	1107.2
378.90	3.9	1.25	112.4	1120.6
379.00	4	0.00	0.0	1126.2

#### Time of Concentration (Te) Worksheet

Project	WAYNE ELEMENT.	ARY SCHOOL	_By	BDM	_Date	4/30/2014		
Location	RADNOR TOWNSHIP, D	ELAWARE COUNTY	Checked		Date			
			_		-			
PRL-DEV	VELOPMENT To:							
Flow Path			Segment ID	A				
	escription			LAWN				
	rth, L		ft	290				
	se Slope, s		n/n	0.03				
	elocity, V (Table 2.10.4		fl/sec	0.80				
T = L/60	V	Compute Te	min	6.04	<u> </u>	<u></u>		= 6.04
								204
Total Time	e of Concentration		min					6.04
CONTRO	OLLED #1 Te:							
CONTRU	)LL::D #1 10.							
Flow Path			Segment ID	A	В			
	escription		(JUBILIUM)	LAWN	PIPE			
	th, L		ft	40	215			
_	se Slope, s		n/n	0.03				
	elocity, V (Table 2.10.4		ft/sec	0.80	5.00			
T=L/60		Compute Tc	min	0.83	0.72			= 1,55
Total Time	e of Concentration		min					1.55
UNCONT	TROLLED To:							
							Ì	
Flow Path			Segment ID	<del></del>	ļ	ļ		
	escription		•	LAWN	<u> </u>		•	
-	th, L		ft	265	1			
	se Slope, s		ft/ft ft/sec	0.03				
	elocity, V (Table 2.10.4	4.2) Compute Tc		5.52	<del> </del>			= 5.52
T=L/60	A	Compare 10,	min	J.J2		1	I	5.02
Total Time	e of Concentration		min					5.52
rotat I mit	2 OF CONCOUNTRIOR		41111					0.02

#### TABLE 2.10.4.1 RUNOFF FACTORS FOR THE RATIONAL EQUATION

	RUNOFF FACTOR "C"		
TYPE OF DRAINAGE AREA OR SURFACE	MINIMUM	MAXIMUM	
Pavement, concrete or bituminous concrete	0.75	0.95	
Pavement, bituminous macadam or surface-treated gravel	0.65	0.80	
Pavement, gravel, macadam, etc.	0.25	0.60	
Sandy soil, cultivated or light growth	0.15	0.30	
Sandy soil, woods or heavy brush	0.15 .	0.30	
Gravel, bare or light growth	0.20 ,	0,40	
Gravel, woods or heavy brush	0.15 ,	0.35	
Clay soil, bare or light growth	0.35 .	0.75	
Clay soil, woods or heavy growth	0, 25 、	0.60	
City business sections	0.60	0.80	
	0.50	0.70	
Dense residential sections	0.35	0.60	
Suburban, normal residential areas Rural areas, parks, golf courses	0.15	0.30	

#### NOTES

- I. Higher values are applicable to denser soils and steep slopes.
- 2. Consideration should be given to future land use changes in the drainage area in selecting the "C" factor.
- 3. For drainage area containing several different types of ground cover, a weighted value of "C" factor shall be used.
- 4. In special situations where slokkholes, stripped abandoned mines, etc. exist, careful evaluation shall be given to the selection of a suitable runoff factor with consideration given to possible reclamation of the land in the future.

#### TABLE 2.10.4.2 RECOMMENDED AVERAGE VELOCITIES OF OVERLAND FLOW FOR DETERMINING TIME OF CONCENTRATION

DESCRIPTION OF COURSE OF RUNOFF WATER	SLOPE (%)							
	VELOCITIES (F.P.S.)							
	0-3		8-10			21-25	26-30	
Woodland	0.5	1.0	1.5	1.7	2.0	2.7	3.5	
Pasture	0.8	1.5	2.2	2.6	3.0	4.1	4.5	
Cultivated (Row Crop)	1.0	2.0	3.0	3.5	4.0	4.5	5.0	
Pavement	5.0	12.0	15.5	18.0				
Natural Draw (Not Well Defined)	0.8	2.5	4.0	6.0	*******			

			MISC						
0F 1	REMARKS		TYPE			YARD	YARD		
SHEET 1 OF 1			D_			383.75		ı	
ORM	INVERT LOWER END		<u> </u>			379.00		376.42	
100 YR STORM	илевт пррек емб		F			381.50	379.00	377.50	
100	YTIOAYAO JUUST FULL	AUSTFULL Q			1,43	2.76	3.82	4.66	
	MEAN VELOCITY	>	FPS		4.62	5,11	6.44	5.27	
	blbE 1AbE				₽VC	HDPE	HOPE	HOPE	
914 3DM	EZIS Edid		2		ထ	10	2	5	
4/30/2014 BDM	ROUGHNESS COEFFICENT	z			0.011	0.012	0.012	0.012	
DATE BY	SLOPE	ဟ	FT/FT		0.0100	0.0135	0.0259	0.0386	
	TENCTH OF PIPE	٦	FI			185	32	28	
	DISCHARGE	ø	CFS		1.26	1.43	1.43	0.45	
λL	ZACA	ð	ACRES		0.15	0.17	0.17		
HOOL COUNTY		ACA	ACRES	İ	0.15	0.02	0.00		
RY SCI	RUNOFF COEFFICENT	O			0.95	0.40	0.50		
WAYNE ELEMENTARY SCH RADNOR TWP, DELAWARE	YTISNƏTNI JJAHNIAA		IN/HR		8.20	8.20	8.20		
LEMI	FLOW TIME IN PIPE	۲	MIN						
IE EI IOR '	SUM OF TIME TO INLET	<u>-</u>	MIN		5.0	5.0	5.0		
WAYN	INCREMENT AREA	\$	ACRES		0.16	0.05	0.00		
_		the state of the s	TO	IN #1	<u>,,</u>	S-1	SWM#1	SPREADER	
PROJECT LOCATION	FOCATION		FROM	SWIN BASIN #1	ROOF	<u></u>	₽.	SWM#1	

#### MOMENEE AND ASSOCIATES, INC.

CONSULTING ENGINEERS 924 COUNTY LINE ROAD BRYN MAWR, PA 19010

JOB NAME:

WAYNE ELEMENTARY SCHOOL

LOCATION:

RADNOR TOWNSHIP

**DELAWARE COUNTY** 

#### LEVEL SPREADER LENGTH CALCULATIONS - SPREADER #1

(C.F. 2006 PA DEP BMP 6.8.1; ROCCO, 2007)

PERFORATION DIAMETER, D:

(IN)

0.75

PIPE PERFORATION AREA, A:

(IN<sup>2</sup>)0.44  $A = \pi * (\frac{D}{2})^2$ 

SW SYS OUTLET INVERT:

(FT) 377.90

LEVEL SPREADER GRADE ELEVATION: HEAD LOSS, H:

377.75 (FT) (FT) 0.15

ORIFICE COEFFICIENT, Cd:

0.60 (-)

GRAVITY, g:

32.2  $(FT/S^2)$ 

20

0.45

OUTFLOW/PERFORATION, Qo:

(CFS) 0.01

 $Q_0 = C_d * A * (2 * g * H)^{0.5}$ 

No. OF PERFORATIONS / LINEAR FOOT:

(-)

OUTFLOW/LINEAR FOOT, QL: (CFS/FT)

 $Q_L = Q_o * No./LF$ 0.11

 $L = (Q/Q_L) * F_s$ 

100-YR CONTROLLED OUTFLOW, Q:

(CFS)

SAFETY FACTOR, Fs:

1.00 (CFS)

MINIMUM LEVEL SPREADER LENGTH, L:

3.93 (FT)

PROPOSED SPREADER LENGTH, L:

16.00 (FT)

SPREADER COVER:

(-) **GRASS** 

WEIR COEFFICIENT, Cw:

3.00 (-)

MAXIMUM ALLOWED VELOCITY, V<sub>max</sub>:

4.00 (FPS)

ACTUAL VELOCITY, V:

(FPS)

 $V = (^3I_2) * C_w^{(2/3)} * (^QI_L)^{(1/3)}$ 

PROPOSED SPREADER LENGTH, L:

(FT)

16.00

0.95

#### Wayne Elementary School

PERMANENT SWALE											
BERM DESIGNATION	VEG 1	VEG 1	<del>-</del>								
DRAINAGE AREA (ACRES)	1.41	1.41									
		1.41									
INTENSITY (IN/HR)	8.20	8.20									
RUNOFF COEFFICIENT	0.35	0.35									
Qr (REQUIRED CAPACITY)	4.05	4.05									
S (BED SLOPE FT/FT) *	0.025	0.025									
PROTECTIVE LINING **	GRASS	CURLEX		-,,							
n (MANNING'S COEFFICIENT) **	0.050	0.034									
FREEBOARD	0.50	0.50									
d (DEPTH OF FLOW)	0.50	0.50									
BERM SIDE SLOPE (_)H:(1)V	8.0	8.0									
BERM SIDE SLOPE (_)H:(1)V CHANNEL BOTTOM WIDTH (FT)	3.00	7.0									
CHARAGE BOT LOW AND LU (L.t.)		3,00	34.00								
A (AREA)	3,38	3.38									
P (WETTED PERIMETER)	10.57	10.57									
R (HYDRAULIC RADIUS)	0.32	0.32									
Q full	7.38	10.86									
V (VELOCITY BASED ON Q full)	2.19	3.22									
				\$70.0 70.00 000.00							
Sc (CHANNEL'S CRITICAL SLOPE)	0.053	0.025									
STABLE FLOW (Y/N)	Y	N									
USS (LB/SQ FT)	0.78	0.78									
(UNIT SHEAR STRESS)				7. 1151							
100											
		010/14/14									

# **Hydraflow Table of Contents**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

Hydrograph Return Period Recap	. 1
1 - Year	
Summary Report	. 2
Hydrograph Reports	. 3
Hydrograph No. 1, Rational, Pre Development	3
Hydrograph No. 3, Rational, Post Uncontrolled	4
Hydrograph No. 4, Rational, Controlled SWM Basin #1	5
Hydrograph No. 5, Reservoir, SWM BASIN #1	. ค
Hydrograph No. 5, Reservoir, Syvivi BASIN #1	7
Pond Report - SWM #1	10
Hydrograph No. 6, Combine, Total Post	10
2 - Year	4.4
Summary Report	11
Hydrograph Reports	12
Hydrograph No. 1, Rational, Pre Development	12
Hydrograph No. 3, Rational, Post Uncontrolled	13
Hydrograph No. 4, Rational, Controlled SWM Basin #1	14
Hydrograph No. 5, Reservoir, SWM BASIN #1	15
Hydrograph No. 6, Combine, Total Post	16
5 - Year	
Summary Report	17
Hydrograph Reports	10
Hydrograph No. 1, Rational, Pre Development	18
Hydrograph No. 3, Rational, Post Uncontrolled	19
Hydrograph No. 4, Rational, Controlled SWM Basin #1	20
Hydrograph No. 5, Reservoir, SWM BASIN #1	21
Hydrograph No. 6, Combine, Total Post	22
10 - Year	
Summary Report	23
Hydrograph Reports	24
Hydrograph No. 1. Rational, Pre Development	24
Hydrograph No. 3, Rational, Post Uncontrolled	25
Hydrograph No. 4, Rational, Controlled SWM Basin #1#1	26
Hydrograph No. 5, Reservoir, SWM BASIN #1	27
Hydrograph No. 6, Combine, Total Post	28
25 - Year	
Summary Report	29
Hydrograph Reports	30
Hydrograph No. 1 Rational Pre Development	-30
Hydrograph No. 3, Rational, Post Uncontrolled	31
Hydrograph No. 4, Rational, Controlled SWM Basin #1	32
Hydrograph No. 5, Reservoir, SWM BASIN #1	33

Hydrograph No. 6, Combine, Total Post	34
50 - Year	
Summary Report	35
Hvdrograph Reports	
Hydrograph No. 1, Rational, Pre Development	36
Hydrograph No. 3, Rational, Post Uncontrolled	37
Hydrograph No. 4. Rational. Controlled SWM Basin #1	38
Hydrograph No. 5, Reservoir, SWM BASIN #1	39
Hydrograph No. 6, Combine, Total Post	40
100 - Year	
Summary Report	41
Hydrograph Reports	42
Hydrograph No. 1. Rational, Pre Development	42
Hydrograph No. 3, Rational, Post Uncontrolled	43
Hydrograph No. 4, Rational, Controlled SWM Basin #1	44
Hydrograph No. 5 Reservoir, SWM BASIN #1	45
Hydrograph No. 6, Combine, Total Post	46
IDF Report	47

Hydrograph Return Period Recap Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

	Hydrograph	Inflow		Peak Outflow (cfs)							Hydrograph
0.	type (origin)	hyd(s)	1-yr	2-yr	3-уг	5-yr	10-yr	25-yr	50-yr	100-y <del>r</del>	Description
1	Rational		0.417	0.482	passes W	0,565	0.644	0.714	0.806	0.882	Pre Development
3	Rational		0.188	0.217		0.255	0.291	0.322	0.364	0,398	Post Uncontrolled
4	Rational		0.718	0.826		0.969	1.096	1.221	1.365	1.473	Controlled SWM Basin #1
5.	Reservoir	4	0.000	0.000		0.000	0.096	0.219	0.311	0.452	SWM BASIN #1
6	Combine	3, 5	0.188	0,217		0,255	0.291	0.397	0.533	0.695	Total Post
			200								
		n and an analysis and an analy									
									ļ		
		į									
					المراجعة المستحدة الم						
				THE REAL PROPERTY.							
									:		
				44,00			:				
									į		
										MANAGEMENT OF THE PARTY.	
				į Į							

Proj. file: 14042.gpw

Thursday, 05 / 1 / 2014

Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.417	1	18	451			M	Pre Development
3	Rational	0.188	1	18	204		p. 4-14		Post Uncontrolled
4	Rational	0.718	1	15	646				Controlled SWM Basin #1
5	Reservoir	0.000	1	66	0	4	377.18	630	SWM BASIN#1
6	Combine	0.188	1	18	204	3, 5		·	Total Post
									-
	1								
		1							
				Attitude of the state of the st	9				
								1	
			The state of the s	THE PROPERTY OF THE PROPERTY O				e puller same	
140	14042.gpw				Return	Period: 1 \	Year	Thursday,	05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 1


Pre Development

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 3.751 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.417 cfs
Time to peak = 18 min
Hyd. volume = 451 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min

= 3/3

Asc/Rec limb fact



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 3.751 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.188 cfs
Time to peak = 18 min
Hyd. volume = 204 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 1 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 3.994 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.718 cfs
Time to peak = 15 min
Hyd. volume = 646 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 5

SWM BASIN #1

Hydrograph type Storm frequency Time interval Inflow hyd. No.

Reservoir name

= Reservoir = 1 yrs

= SWM #1

Hyd. volume  $= 1 \, \text{min}$ = 4 - Controlled SWM Basin #1Max. Elevation

Max. Storage


Peak discharge

Time to peak

= 0.000 cfs= 66 min = 0 cuft

= 377.18 ft= 630 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Pond No. 1 - SWM #1

#### Pond Data

UG Chambers -Invert elev. = 375.00 ft, Rise x Span = 4.00 x 4.00 ft, Barrel Len = 90.00 ft, No. Barrels = 1, Slope = 0.00%, Headers = No

#### Stage / Storage Table

Stage (ft)	Elevation (ft)	Contour area (sqft)	Incr. Storage (cuft)	Total storage (cuft)
0.00	375.00	n/a	0	0
0,40	375.40	n/a	59	59
0.80	375.80	n/a	102	161
1.20	376.20	n/a	124	286
1.60	376.60	n/a	137	423
2.00	377.00	n/a	143	566
2.40	377.40	n/a	143	709
2.80	377.80	n/a	137	846
3,20	378.20	n/a	124	970
3,60	378.60	n/a	1 <b>02</b>	1,072
4.00	379.00	n/a	59	1,131

#### **Culvert / Orifice Structures**

#### **Weir Structures**

	[A]	[B]	[C]	[PrfRsr]		[A]	[B]	[C]	[D]
Rise (in)	= 10.00	4.00	0.00	0.00	Crest Len (ft)	= 4.71	0.00	0.00	0.00
Span (in)	= 10.00	4.00	0,00	0.00	Crest El. (ft)	= 378.90	0.00	0.00	0.00
No. Barrels	= 1	1	1	0	Weir Coeff.	= 3.33	3.33	3.33	3.33
Invert El. (ft)	= 377.50	377.90	0.00	0.00	Weir Type	= 1			нва
Length (ft)	= 28.00	0.00	0.00	0.00	Multi-Stage	= Yes	No	No	No
Slope (%)	= 3.86	0.00	0.00	n/a					
N-Value	= ,013	.013	.013	n/a					
Orifice Coeff.	= 0.60	0.60	0.60	0.60	Exfil.(in/hr)	= 1.000 (by	Wet area	)	
Multi-Stage	= n/a	Yes	No	No	TW Elev. (ft)	= 0.00			

Note: Culvert/Orifice outflows are analyzed under inlet (to) and outlet (oc) control. Weir risers checked for orifice conditions (ic) and submergence (s).

Stage /	Storage	/ Discharge	Table
---------	---------	-------------	-------

Stage ft	Storage cuft	Elevation ft	Clv A cfs	CIV B cfs	Clv C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Total cfs
0.00	0	375.00	0.00	0.00			0.00		****		0.000		0.000
0.04	6	375.04	0.00	0.00			0.00		~~~		0.002		0.002
80.0	12	375.08	0.00	0.00			0.00				0.002		0.002
0.12	18	375.12	0.00	0.00			0.00				0.002		0.002
0.12	24	375.16	0.00	0.00			0.00	~~~		H==	0.003		0.003
0.20	29	375.20	0.00	0.00			0.00				0.003		0.003
0.24	35	375.24	0.00	0.00			0.00				0.004		0.004
0.28	41	375.28	0.00	0.00			0.00				0.004		0.004
0.20	47	375.32	0.00	0.00			0.00				0.004		0.004
0.36	53	375.36	0.00	0.00			0.00				0.005		
0.30	59	375.40	0.00	0.00		<b>1</b>	0.00				0.005		0.005
0.44	6 <del>9</del>	375.40 375.44	0.00	0.00			0.00						0.005
0.44	79	375.44 375.48	0.00	0.00		b-414	0.00				0.006		0.006
0.40	90	375.46 375.52								***	0.006		0.006
0.56	100	375.52 375.56	0.00	0.00		****	0.00		u		0.006		0.006
0.00			0.00	0.00			0.00				0.006		0.006
	110	375.60	0.00	0.00		***	0.00				0.007		0.007
0.64	120	375.64	0.00	0.00			0.00				0.007		0.007
0.68	130	375.68	0.00	0.00			0.00				0.007		0.007
0.72	141	375.72	0.00	0.00			0.00	p and			0.007		0.007
0.76	151	375.76	0.00	0.00		TAM	0.00				0.008		0.008
0.80	161	375.80	0.00	0.00			0.00	***			0.008	***	0.008
0.84	174	375.84	0.00	0.00		***	0.00				800.0		800.0
0.88	186	375.88	0.00	0.00			0.00				0.008		0.008
0.92	198	375.92	0.00	0.00		***	0.00				0.008		0.008
0.96	211	375.96	0.00	0.00			0.00				0.009		0.009
1.00	223	376.00	0.00	0.00			0.00				0.009		0.009
1.04	236	376.04	0.00	0.00			0.00		700	-	0.009		0.009
1.08	248	376.08	0.00	0.00			0.00				0.009		0.009
1.12	261	376.12	0.00	0.00			0.00				0.009		0.009
1.16	273	376.16	0.00	0.00			0.00				0.009		0.009

Continues on next page...

SWM#1
Stage / Storage / Discharge Table

Stage /	Storage /	Discharge	Table										
Stage ft	Storage cuft	Elevation ft	Clv A cfs	Clv B cfs	Clv C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Total cfs
1,20	286	376.20	0.00	0.00			0.00	***	***		0.010		0.010
1.24	299	376.24	0.00	0,00			0.00				0.010		0.010
1.28	313	376.28	0.00	0.00			0.00		~~~		0.010		0.010
1.32	327	376.32	0.00	0.00			0.00	***			0.010		0.010
1.36	340	376.36	0.00	0.00	*****	***	0.00				0.010		0.010
1.40	354	376,40	0.00	0.00			0.00		***		0.011 0.011		0.011 0.011
1.44 1.48	368 381	376.44 376.48	0.00 0.00	0.00 0.00			0.00 0.00				0.011		0.011
1.52	395	376.52	0.00	0.00	n-n		0.00				0.011		0.011
1.56	409	376,56	0.00	0.00	MM7		0.00				0.011		0.011
1.60	423	376,60	0.00	0.00	A++= +#I		0.00		***		0.011		0.011
1.64	437	376,64	0.00	0.00	~==		0.00				0.012		0.012
1.68	451	376,68	0.00	0.00			0.00				0.012		0.012
1.72	466	376.72	0.00	0.00			0.00				0.012		0.012
1.76	480	376.76	0.00	0.00	time.		0.00				0.012		0.012
1.80	494	376,80	0.00	0.00			0.00				0.012 0.012		0.012 0.012
1.84	508	376.84 376.88	0.00 0.00	0.00 0.00			0.00 0.00				0.012		0.012
1.88 1.92	523 537	376,66 376,92	0.00	0.00			0.00				0.013		0.013
1.96	551	376.96	0.00	0.00			0.00				0.013		0.013
2.00	566	377.00	0.00	0.00			0.00				0.013		0.013
2.04	580	377.04	0.00	0.00			0.00				0.013		0.013
2.08	594	377.08	0.00	0.00			0.00				0.013		0.013
2.12	609	377.12	0.00	0.00			0.00				0.014	****	0.014
2.16	623	377.16	0.00	0.00		***	0.00				0.014		0.014
2.20	637	377.20	0.00	0.00			0.00				0.014 0.014	nw.d	0.014 0.014
2.24	652	377.24	0.00 0.00	0.00 0.00		priorite	0.00 0.00				0.014		0,014
2.28 2.32	666 680	377.28 377.32	0.00	0.00			0.00				0.014		0.014
2.36	695	377.36	0.00	0.00		ec10010	0.00			***	0.015	***	0.015
2.40	709	377.40	0.00	. 0.00			0.00				0.015		0.015
2.44	723	377.44	0.00	0.00			0.00				0.015	~~~	0.015
2.48	736	377.48	0.00	0.00		L-MARIE	0.00				0.015		0.015
2.52	750	377.52	0.00	0.00	***		0.00				0.015		0.015
2.56	764	377.56	0.00	0.00			0.00				0.015	~~~	0.015
2.60	777	377.60	0.00	0.00		404	0.00				0.016 0.016		0,016 0.016
2.64	791	377.64	0.00 0.00	0.00 00.0			0.00 00,0				0.016		0.016
2.68 2.72	805 818	377.68 377.72	0.00	0.00			0.00				0.016		0,016
2.76	832	377.76	0.00	0.00			0,00			2.00	0.016		0.016
2.80	846	377.80	0.00	0.00		***	0.00				0.017		0.017
2.84	858	377.84	. 0.00	00.0		***	0.00				0.017		0.017
2.88	871	377.88	0.00	0.00		M-410	0.00		***		0.017	but Poister	0.017
2.92	883	377.92	0.00 ic	0.00 ic		Warner .	0.00				0.017	****	0.018
2.96	896	377.96	0.01 ic	0.01 ic			0.00		****		0.017 0.017		0.026 0.041
3.00	908	378.00	0.02 ic	0.02 ic			0.00		***		0.017		0.041
3.04 3.08	920 933	378.04 378.08	0.05 ic 0.07 ic	0.04 ic 0.07 ic			0.00				0.018		0.032
3.12	945	378.12	0.07 ic	0.10 ic			0.00		***		0.018		0.116
3.16	958	378.16	0.13 ic	0,13 ic			0.00				0.018		0.145
3.20	970	378.20	0.16 ic	0.15 ic	LANGE		0.00	are bet mill			0.018		0.173
3.24	980	378.24	0.18 ic	0.17 ic			0.00				0.019		0.194
3.28	991	378.28	0.19 ic	0,19 lc	****		0.00				0.019		0.213
3.32	1,001	378.32	0.21 ic	0.21 ic	44.004	***	0.00			-	0.019		0.231
3.36	1,011	378.36	0.23 ic	0,23 ic			0.00				0.019 0.020		0.247 0.262
3,40	1,021	378.40 378.44	0.24 ic 0.2 <del>6</del> ic	0,24 ic 0.26 ic			0.00 0.00				0.020		0.202
3,44 3,48	1,032 1,042	378.48	0,28 ic.	0.26 lc			0.00				0.020		0.290
3.52	1,042	378.52	0.29 ic	0.28 ic			0.00		***	p~-n	0.020		0.303
3.56	1,062	378.56	0.30 ic	0,30 ic	h		0,00			popular.	0.021		0.316
3.60	1,072	378.60	0.31 ic	0,31 ic			0.00				0.021		0.328
3.64	1,078	378.64	0.33 ic	0,32 ic	PE-4		0.00				0.021		0.339
3.68	1,084	378.68	0.33 ic	0.33 lc			0.00				0.021	***	0.350
3.72	1,090	378.72	0.34 ic	0.34 ic		مين	0.00				0.022		0.361
3.76	1,096	378.76	0.35 ic	0,35 ic			0.00				0.022		0.372
3,80	1,102	378.80	0.37 ic	0,36 ic			0.00 0.00				0.022 0.023		0.382 0.392
3,84 3,88	1,108 1.114	378.84 378.88	0.37 ic - 0.38 ic	0,37 ic 0,38 ic	men.		0.00				0.023		0.402
3.88 3.92	1,114 1,119	378.92	-0.36 lc -0.44 lc	0.38 ic	an lating		0.04				0.024		0.457
3.96	1,125	378.96	0.63 ic	0.40 ic		P74	0.23				0.025		0,653
	.,			,						•	Continue		t page

SWM #1

Stage /	Storage /	Discharge	Table										
Stage ft	Storage cuft	Elevation ft	Clv A cfs	Clv B cfs	CIV C cfs	PrfRsr cfs	Wr A cfs	Wr B cfs	Wr C cfs	Wr D cfs	Exfil cfs	User cfs	Totai cfs
4.00	1,131	379.00	0.91 ic	0.41 ic			0.50				0.026		0.928

ε.

...End

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 6

**Total Post** 

Hydrograph type = Combine
Storm frequency = 1 yrs
Time interval = 1 min
Inflow hyds. = 3, 5

Peak discharge = 0.188 cfs
Time to peak = 18 min
Hyd. volume = 204 cuft
Contrib. drain. area = 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.482	1	18	520		<del></del>	la marage per	Pre Development
3	Rational	0.217	1	18	235			lan annua har hiir mil	Post Uncontrolled
4	Rational	0.826	1	15	744				Controlled SWM Basin #1
5	Reservoir	0.000	1	47	0	4	377.45	726	SWM BASIN#1
6	Combine	0.217	4	18	235	3, 5			Total Post
					117.64.17				
			,						
	Manada and an and an and an an an an an an an an an an an an an								
	The state of the s			- Luy					
14	14042.gpw					n Period; 2	Year	Thursday	, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 4.327 in/hr
IDF Curve = reg5.IDF

Hyd No. 1

Peak discharge = 0.482 cfs
Time to peak = 18 min
Hyd. volume = 520 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min

= 3/3

Asc/Rec limb fact

**Pre Development** Q (cfs) Q (cfs) Hyd. No. 1 -- 2 Year 0.50 0.50 0.45 0.45 0.40 0.40 0.35 0.35 0.30 0.30 0.25 0.25 0.20 0.20 0.15 0.15 0.10 0.10 0.05 0.05 0.00 0.00 22 24 26 28 30 32 34 36 2 10 12 16 18 20 6 8 14 Time (min)

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 4.327 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.217 cfs
Time to peak = 18 min
Hyd. volume = 235 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 2 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 4.596 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.826 cfs
Time to peak = 15 min
Hyd. volume = 744 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 5

SWM BASIN #1

= 0.000 cfsPeak discharge Hydrograph type = Reservoir Time to peak = 47 min Storm frequency = 2 yrsHyd. volume = 0 cuft Time interval = 1 min = 4 - Controlled SWM Basin #1 Max. Elevation  $= 377.45 \, \text{ft}$ Inflow hyd. No. Max. Storage = 726 cuft Reservoir name = SWM #1

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 6

**Total Post** 

Hydrograph type Storm frequency Time interval Inflow hyds. = Combine = 2 yrs

 $= 1 \min$ = 3, 5


Peak discharge

= 0.217 cfs

Time to peak Hyd. volume

= 18 min = 235 cuft

Contrib. drain. area = 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description	
1	Rational	0.565	1	18	610		744 e p		Pre Development	
3	Rational	0.255	1	18	275			************	Post Uncontrolled	
4	Rational	0,969	1	15	872		warr	name of ordif	Controlled SWM Basin #1	
5	Reservoir	0,000	1	37	0	4	377.82	853	SWM BASIN#1	
6	Combine	0,255	1	18	275	3, 5		gay an law and has man	Total Post	
					AAAA AAAA AAAAA AAAAAAAAAAAAAAAAAAAAAA					
	·									
									·	
								,		
								in the state of th		
						and definition of the state of				
			-				· ·			
140	)42.gpw				Return	Period: 5	Year	Thursday, 05 / 1 / 2014		

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 5 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 5.073 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.565 cfs
Time to peak = 18 min
Hyd. volume = 610 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 5 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 5.073 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.255 cfs
Time to peak = 18 min
Hyd. volume = 275 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014


#### Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 5 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 5.390 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.969 cfs
Time to peak = 15 min
Hyd. volume = 872 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min

Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

Hyd. No. 5

SWM BASIN #1

Peak discharge = 0.000 cfsHydrograph type = Reservoir Time to peak = 37 min Storm frequency = 5 yrsHyd. volume = 0 cuft Time interval = 1 min = 4 - Controlled SWM Basin #1Max. Elevation = 377.82 ftInflow hyd. No. = 853 cuft Max. Storage Reservoir name = SWM #1

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 6

**Total Post** 

Hydrograph type = Combine
Storm frequency = 5 yrs
Time interval = 1 min
Inflow hyds. = 3, 5

Peak discharge = 0.255 cfs
Time to peak = 18 min
Hyd. volume = 275 cuft
Contrib. drain. area = 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description	
1	Rational	0.644	1	18	696	Northwest relate			Pre Development	
3	Rational	0.291	1	18	314	mhamba.	·	·	Post Uncontrolled	
4	Rational	1.096	1	15	986	# W 19 # W 19 # W			Controlled SWM Basin #1	
5	Reservoir	.0.096	1	28	58	4	378.12	945	SWM BASIN#1	
6	Combine	0.291	1	18	373	3, 5			Total Post	
							į			
		- Try v Commetents								
									• •	
			E							
			i							
									,	
					A. A. L.					
								!		
			1							
							7	,	:	
140	44040					ا مانتا الم	Voor	Thursday 05 / 4 / 004 4		
14042.gpw					Return I	Period: 10	Year	Thursday, 05 / 1 / 2014		

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 5.791 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.644 cfs
Time to peak = 18 min
Hyd. volume = 696 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min

= 3/3

Asc/Rec limb fact

**Pre Development** Q (cfs) Q (cfs) Hyd. No. 1 -- 10 Year 1.00 1.00 0.90 0.90 0.80 0.80 0.70 0.70 0,60 0.60 0.50 0.50 0.40 0.40 0.30 0.30 0.20 0.20 0.10 0.10 0.00 0.00 36 30 . 32 34 18 20 22 24 26 28 8 10 12 14 16 6 Time (min) Hyd No. 1

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 5.791 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.291 cfs
Time to peak = 18 min
Hyd. volume = 314 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

#### Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 10 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 6.096 in/hr
IDF Curve = reg5.IDF

Peak discharge = 1.096 cfs
Time to peak = 15 min
Hyd. volume = 986 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 5

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir

= 10 yrs

= 1 min= 4 - Controlled SWM Basin #1Max. Elevation


Max. Storage = SWM #1

Peak discharge = 28 min Time to peak Hyd. volume = 58 cuft

> = 378.12 ft = 945 cuft

= 0.096 cfs

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

#### Hyd. No. 6

Inflow hyds.

**Total Post** 

Hydrograph type Storm frequency Time interval = Combine = 10 yrs

= 1 min = 3, 5 Peak discharge


= 0.291 cfs

Time to peak Hyd. volume

= 18 min = 373 cuft

Contrib. drain. area

= 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

lyd. Vo.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description	
1	Rational	0.714	1	18	772				Pre Development	
3	Rational	0,322	1	18	348				Post Uncontrolled	
4	Rational	1,221	1	15	1,099				Controlled SWM Basin #1	
5	Reservoir	0.219	1	27	164	4	378.34	1,006	SWM BASIN#1	
6	Combine	0,397	1	25	513	3, 5		the to security	Total Post	
THE PARTY OF THE P										
					THE STATE OF THE S					
						, , , , , , , , , , , , , , , , , , ,			,	
						i e				
						:				
						The state of the s				
14042.gpw					Return	Period: 25	Year	Thursday	Thursday, 05 / 1 / 2014	

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 25 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 6.419 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.714 cfs
Time to peak = 18 min
Hyd. volume = 772 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 25 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 6.419 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.322 cfs
Time to peak = 18 min
Hyd. volume = 348 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 25 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 6.794 in/hr
IDF Curve = reg5.IDF

Peak discharge = 1.221 cfs
Time to peak = 15 min
Hyd. volume = 1,099 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 5

SWM BASIN #1

Hydrograph type Storm frequency Time interval

Inflow hyd. No.

Reservoir name

= Reservoir = 25 yrs

= SVVM #1

Time to peak = 1 min

Hyd. volume = 4 - Controlled SWM Basin #1 Max. Elevation Max. Storage


Peak discharge

= 27 min = 164 cuft = 378.34 ft

= 0.219 cfs

= 1,006 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Flydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3.


Thursday, 05 / 1 / 2014

## Hyd. No. 6

**Total Post** 

Hydrograph type = Combine
Storm frequency = 25 yrs
Time interval = 1 min
Inflow hyds. = 3, 5

Peak discharge = 0.397 cfs
Time to peak = 25 min
Hyd. volume = 513 cuft
Contrib. drain. area = 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.806	1	18	870	******	or had because of the		Pre Development
3	Rational	0.364	1	18	393	p			Post Uncontrolled
	Rational	1.365	1	15	1,228	Hanner		и	Controlled SWM Basin #1
	Reservoir	0.311	1	26	287	4	378.62	1,074	SWM BASIN #1
6	Combine	0.533	1	24	680	3, 5			Total Post
i 				The state of the s			-		
A CONTRACT OF THE PROPERTY OF	Total Control of the								
120	042.gpw				Return	Period: 50	) Year	Thursday	, 05 / 1 / 2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 7.241 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.806 cfs
Time to peak = 18 min
Hyd. volume = 870 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

### Hyd. No. 3


Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 7.241 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.364 cfs
Time to peak = 18 min
Hyd. volume = 393 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min

= 3/3

Asc/Rec limb fact



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type = Rational
Storm frequency = 50 yrs
Time interval = 1 min
Drainage area = 0.214 ac
Intensity = 7.592 in/hr
IDF Curve = reg5.IDF

Peak discharge = 1.365 cfs
Time to peak = 15 min
Hyd. volume = 1,228 cuft
Runoff coeff. = 0.84
Tc by User = 5.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 5

### SWM BASIN #1

Peak discharge = 0.311 cfs= Reservoir Hydrograph type = 26 min Time to peak Storm frequency = 50 yrsHyd. volume = 287 cuft Time interval = 1 min= 4 - Controlled SWM Basin #1Max. Elevation = 378.62 ftInflow hyd. No. Max. Storage = 1,074 cuft= SWM #1 Reservoir name

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 6

**Total Post** 

Hydrograph type = Combine
Storm frequency = 50 yrs
Time interval = 1 min
Inflow hyds. = 3, 5

Peak discharge = 0.533 cfs
Time to peak = 24 min
Hyd. volume = 680 cuft
Contrib. drain. area = 0.157 ac



Hydrograph Summary Report
Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	Rational	0.882	1	18	952	4-1-1-1			Pre Development
3	Rational	0.398	1	18	430	*****	barrania.	and the state of the	Post Uncontrolled
4	Rational	1.473	1	15	1,326	manus and brook	Minute Administrated Mr.		Controlled SWM Basin #1
5	Reservoir	0.452	1	25	381	4	378.93	1,120	SWM BASIN #1
6	Combine	0.695	1	25	811	3, 5	all appropriate in the contract of the contrac		Total Post
		- 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10							
								-	
:									
						viv.			
					,				
								- 1-1-0-4-1	
1/1	)42,gpw	<u> </u>	1	<u> </u>	Return	Period: 10	 )0 Year	Thursday	05/1/2014

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 1

Pre Development

Hydrograph type = Rational
Storm frequency = 100 yrs
Time interval = 1 min
Drainage area = 0.371 ac
Intensity = 7.922 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.882 cfs
Time to peak = 18 min
Hyd. volume = 952 cuft
Runoff coeff. = 0.3
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

### Hyd. No. 3

Post Uncontrolled

Hydrograph type = Rational
Storm frequency = 100 yrs
Time interval = 1 min
Drainage area = 0.157 ac
Intensity = 7.922 in/hr
IDF Curve = reg5.IDF

Peak discharge = 0.398 cfs
Time to peak = 18 min
Hyd. volume = 430 cuft
Runoff coeff. = 0.32
Tc by User = 6.00 min
Asc/Rec limb fact = 3/3




Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

## Hyd. No. 4

Controlled SWM Basin #1

Hydrograph type Peak discharge = Rational = 1.473 cfsStorm frequency = 100 yrsTime to peak  $= 15 \, \text{min}$ Hyd. volume Time interval = 1,326 cuft = 1 minDrainage area = 0.214 acRunoff coeff. = 0.84Tc by User Intensity = 8.196 in/hr $= 5.00 \, \text{min}$ **IDF** Curve Asc/Rec limb fact = reg5.IDF = 3/3



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3


Thursday, 05 / 1 / 2014

## Hyd. No. 5

SWM BASIN #1

= Reservoir Peak discharge = 0.452 cfsHydrograph type Storm frequency = 100 yrs Time to peak = 25 min Time interval = 1 min Hyd. volume = 381 cuft = 4 - Controlled SWM Basin #1 Max. Elevation Inflow hyd. No.  $= 378.93 \, ft$ Reservoir name = SWM #1 Max. Storage = 1,120 cuft

Storage Indication method used. Exfiltration extracted from Outflow.



Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

## Hyd. No. 6

**Total Post** 

Hydrograph type Storm frequency Time interval Inflow hyds. = Combine = 100 yrs


= 1 min = 3, 5 Peak discharge

= 0.695 cfs

Time to peak = 2 Hyd. volume = 8

= 25 min = 811 cuft

Contrib. drain. area = 0.157 ac



# **Hydraflow Rainfall Report**

Hydraflow Hydrographs Extension for AutoCAD® Civil 3D® 2014 by Autodesk, Inc. v10.3

Thursday, 05 / 1 / 2014

Return Period	Intensity-Duration-Frequency Equation Coefficients (FHA)								
(Yrs)	В	D	E	(N/A)					
1	22.1293	5.9000	0.7167						
2	26,2877	6.4000	0.7166						
3	0.0000	0.0000	0.0000	##					
5	25.3184	5.4000	0.6606						
10	50.7545	9.8000	0.7865						
25	27.8762	5.2000	0.6079						
50	41.8042	8.4000	0.6573						
100	129.6326	19.8000	0.8599	lane ja pale sa mung					

File name: reg5.IDF

### Intensity = $B / (Tc + D)^E$

Return	Intensity Values (in/hr)											
Period (Yrs)	5 min	10	15	20	25	30	35	40	45	50	55	60
1	3.99	3.05	2.51	2.15	1.89	1.70	1.55	1.43	1.32	1.24	1.16	1.10
. 2	4.60	3,54	2.93	2.52	2,22	2,00	1,82	1.68	1.56	1.46	1.38	1.30
3	0.00	0.00	0.00	. 0,00	00,0	0.00	0,00	0.00	0.00	0.00	0.00	0.00
5	5,39	4.16	3.45	2,99	2,65	2.40	2,20	2.04	1.90	1.79	1.69	1.60
· 10	6,10	4.85	4.06	3.52	3,11	2.80	2.55	2.35	2.18	2.03	1.91	1.80
25	6.79	5.33	4.48	3.92	3,51	3.20	2.95	2.75	2.58	2.43	2.31	2.20
. 50	7.59	6.16	5.26	4.63	4.16	3.80	3.51	3.26	3.06	2.88	2.73	2.60
. 100	8.20	7.00	6.12	5.46	4.93	4.50	4.14	3.84	3.59	3.37	3,17	3.00

Tc = time in minutes. Values may exceed 60.

Precip. file name: LMT.pcp

•	Rainfall Precipitation Table (in)										
Storm Distribution	1-yr	2-yr	3-yr	5-yr	10-yr	25-уг	50-yr	100-yr			
SCS 24-hour	2.80	3.20	0.00	4.20	5.00	5.80	6.50	7.20			
SCS 6-Hr	1.40	1.80	0.00	0.00	2.60	0.00	0.00	4.00			
Huff-1st	. 0.00	1.55	0.00	2.75	4.00	5.38	6.50	8.00			
Huff-2nd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0,00			
Huff-3rd	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
Huff-4th	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
Huff-Indy	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
Custom	0.00	1.75	0.00	2.80	3.90	5.25	6.00	7.10			



#### Excellence Delivered As Promised

#### **MEMORANDUM**

Date: May 28, 2014

To: Radnor Township Planning Commission

From: Roger Phillips, PE

cc: Stephen Norcini, P.E. – Director of Public Works

Robert Zeinkowski, - Township Manager John Rice, Esq. – Grim, Biehn, and Thatcher

**RE:** Stormwater Management Ordinance Revisions -

Radnor Code Ch 245

Enclosed herein is a revised copy of the proposed ordinance amending Chapter 245 of the Radnor Township Code – Stormwater Management. This ordinance was considered by the Board of Commissioners on May 19, 2014, and is being returned to you for further consideration.

As you recall, the previous version provided a suggested revision to increase the infiltration volume to 1-inch over the entire parcel. The BOC has returned this for consideration of reducing the 1-inch infiltration volume to only the developed area. That suggested requirement is actually in the current ordinance, so no revision to that section is required.

The other portion of the ordinance recommended for revision was 245-26 C.(2) in which it was recommended to return all parcels for redevelopment back to meadow in good condition for the predevelopment runoff calculations. The BOC has returned this for consideration of a revision to return 25% of the existing developed area on the site to "meadow in good condition" and the reminder of the site area to remain as currently exists.

The intent of this proposed ordinance is to provide an immediate impact for the reduction of stormwater discharge from future development. Township staff, in concert with the Stormwater Management Advisory Committee and the Planning Commission, will be undertaking a review of the entire stormwater management ordinance and will be bringing forth for further recommendations in the near future.

Please review this proposed ordinance modifications and provide recommendations.

Very truly yours, GANNETT FLEMING, INC

Roger A. Phillips, P.E. Senior Project Manager

#### **ORDINANCE NO. 2014-03**

#### RADNOR TOWNSHIP

AN ORDINANCE OF RADNOR TOWNSHIP, DELAWARE COUNTY, PENNSYLVANIA, AMENDING CHAPTER 245, STORMWATER MANAGEMENT, OF THE RADNOR CODE, BY AMENDING CERTAIN PROVISIONS REGARDING PURPOSE, AND EXISTING CONDITIONS CONCERNING CALCULATION METHODOLOGY.

The Radnor Township Board of Commissioners does hereby ENACT and ORDAIN, as follows:

#### ARTICLE I Purpose.

Section 245-3, Purpose, of Chapter 245, is amended by adding a new Subsection B and re-lettering the existing subsections "B" - R to "C" - "S". The new Subsection B, shall read as follows:

B. Utilize Green Infrastructure, and Lower Impact Development design and practices to promote infiltration, evapotranspiration and re-use of stormwater.

#### ARTICLE II Calculation Methodology

Section 245-26 C.(2) is revised to read as follows:

C. (2) For redevelopment sites, the ground cover used in determining the existing conditions' flow rates for the developed portion of the site shall be based on actual existing conditions with the exception that a minimum of 25% of existing developed area be considered as "meadow in good condition".

#### ARTICLE III Repealer.

All ordinances or parts of ordinances which are inconsistent herewith are hereby repealed.

#### **ARTICLE IV** Severability.

If any section, paragraph, subsection, clause or provision of this Ordinance shall be declared invalid or unconstitutional by a court of competent jurisdiction, such decision shall not

specifically declar	ared invalid.			
ARTICLE V	Effective Date.			
This Ord Radnor Townshi		ome effective	in accord	lance with the Home Rule Charter of
ENACTI	ED AND ORDAIN	V <b>ED</b> this	_ day of _	, A.D., 2014.
				RADNOR TOWNSHIP BOARD OF COMMISSIONERS
		,	Ву:	
				Name: Elaine P. Schaefer Title: President
ATTEST:		·		Title. Trestaent
Robe	rt A. Zienkowski,	Secretary		

affect the validity of this Ordinance as a whole or any part thereof other than that portion

## ZONING HEARING BOARD APPLICATION

#### TOWNSHIP OF RADNOR

301 IVEN AVENUE WAYNE, PA 19087 610-688-5600

FAX: 610-971-0450

www.radnor.com www.radnor.com

\*

GENERAL INFORMATION: Applicants are strongly encouraged to review the "Requirements and Information for Appeals to the Zoning Hearing Board" that are attached to his application. Ten (10) copies of this application and required attachments must be filed with the Community Development Department not less than thirty (30) calendar days prior to the hearing. INCOMPLETE APPLICATIONS WILL NOT BE ACCEPTED FOR PROCESSING

REQUIRED FEE DUE AT FILING: Please refer to the Consolidated Fee Schedule, as amended, on our website at www.radnor.com for a copy of our current fees.

Our website at www.radior.com for a copy of our current rees.

#### TYPE OR PRINT

Property Address:	240-252 Radr	nor Chester Road, Radnor, PA	
Name of applicant:	Radnor Chester Road	Investement, L.P. & 252 RCR Investments, L.	P
•	267–266–4517	SheldonEGross@gmail.com	
Property Owner (if	different than above):		
Property address: _			
Telephone number:		Email:	

.3 667952

Attorney's 112	nme: Nicholas J. Caniglia, Esquire
Address:	125 Strafford Avenue, Suite 110, Wayne, PA 19087
Telephone m	umber: 610-688-2626 Email: NCaniglia@gmail.com
Relief reques citation to an necessary)	sted and/or basis for appearing before the Zoning Hearing Board including specific ry and all sections of the Zoning Code relevant to the appeal. (attach additional pages if
	See attached
Description copies of de	n of previous decisions by the Zoning Hearing Board pertinent to the property, or atte ecisions: (attach additional pages if necessary)
	See attached

### ZONING APPLICATION 240-252 Radnor Chester Road, Radnor, PA

Relief requested and/or basis for appearing before the Zoning Hearing Board including specific citation to any and all sections of the Zoning Code relevant to the appeal. (attach additional pages if necessary)

Applicant's property is split zoned PB-Planned Business and R-1 Residential. Applicant seeks variances from the following sections of the Zoning Code: (1) §280-60(B) relating to Building Area; (2) §280-60(C) relating to setback along a 50' by 50' parcel owned by the Township; and (3) §280-61(D) relating to buffer along the 50' by 50'Township owned parcel. Applicant seeks a special exception under §280-101(A)(1), a variance from the cited sections, or contends that it is permitted by right or as a decrease in existing non-conformity from the following sections of the Zoning Code: (1) §280-60(C) regarding continuation of the existing Rear Yard setback on the rear property line in common with Radnor Financial Center for the parking structure and (2) §280-4 regarding continuation of the existing size of parking spaces in parking structure. In addition, Applicant seeks any other zoning or alternative relief required pursuant to the Plans presented with this Application.

Description of previous decisions by the Zoning Hearing Board pertinent to the property, or attach copies of decisions: (attach additional pages if necessary)

Appeal Number 2805 dated April 1, 2009 granting relief to construct parking structure within rear yard setback and to reduce size of parking spaces within parking structure to be 8.5' by 19'.

Appeal Number 2911 – Denial of previous Plan of Applicant.

## Brief narrative of proposed improvements:

Applicant intends to merge 240 Radnor Chester Road and 252 Radnor Chester Road into a single lot. 240 Radnor Chester Road is split zoned; mainly PB with a ring of R-1 surrounding it. 252 Radnor Chester Road is zoned R-1 and is a legally non-conforming office use. 240 Radnor Chester Road is legally non-conforming in regards to setback, building coverage, and impervious coverage. To the east of the Premises is a 50' by 50' parcel owned by Radnor Township. Applicant intends to raze the existing office building on 252 Radnor Chester Road in the R-1 Zoning District, which is non-conforming on use and front yard setback. No buildings or structures will be constructed on 252 Radnor Chester Road. Applicant proposed the construction of an additional office building in the PB Zoning District of 240 Radnor Chester Road together with additional structured parking in the existing parking deck only located in the PB Zone. Existing condition will remain unchanged except for the construction of the Building and garage structure within the PB zoned areas. There will be no other changes to the R-1 areas existing on 240 and 252 Radnor Chester Road except for additional plantings and buffering. The overall impervious coverage on the Premises will be less than existing. As a result of the 50' by 50' township owned parcel, the Applicant requires relief from the setback and buffer requirements of the Zoning Code. Applicant requests that the zoning relief granted previously in Appeal Number 2805 extend to the current request to permit 8.5' by 19' parking stall size in the parking structure. The proposed Plan varies from the previous Plan denied by the Zoning Board by the elimination of any additional buildings or structures in any of the R-1 zoned land.

### List of Witnesses and Summary of Testimony:

Sheldon Gross - Principal of Applicant – Regarding Project as described above. Alex Tweedie, P.E. – Site Engineer – Regarding engineering as described above. Timothy Haahs – Parking Designer – Regarding stall size and parking. Applicant reserves the right to present other witnesses at the hearing.

	See attached
<u> </u>	
	·
ATTA	CHMENTS: Ten (10) copies of each of the following must be provided:
1.	Engineered plan or survey of the property drawn to scale, prepared by a registered architect, engineer or surveyor licensed in Pennsylvania, containing the following information:  a) lot lines and lot dimensions described in metes and bounds (in feet);
	<ul> <li>total lot area;</li> <li>location of easements and rights of way, including ultimate rights of way;</li> <li>location of all setback lines for existing and proposed structures;</li> </ul>
	<ul> <li>d) location of all setback lines for existing and proposed structures,</li> <li>e) location of steep slopes, floodplains, riparian buffers, wetlands, and other pertinent features;</li> </ul>
	to location of existing and proposed improvements;
	g) table of zoning data including zoning district, required setbacks, existing and proposed building coverage, impervious coverage, height, and other pertinent zoning restrictions, and any degree of compliance or noncompliance; and
	h) all other features or matters pertinent to the application.
	PLANS SHALL NOT EXCEED 24" X 36", AND MUST BE NEATLY FOLDED TO NO
	GREATER DIMENSION THAN 8 1/2" X 11" AT FILING
2.	List of witnesses and summary of their testimony attached.
3.	Photographs of the property at issue and all adjoining properties.
4.	Copies of any written professional reports, including traffic studies, land planning studies,
.3 667952	3

appraisals, floodplain analyses, economic forecasts or other written reports, which the applicant wishes to present at the hearing (note: the author of the study or a qualified representative of the entity who prepared the study must appear at the meeting and be available for cross-examination).

5. Copy of deed, lease, agreement of sale, or other authorization to file the appeal. (note: leases or agreements of sale either must expressly permit the tenant or buyer to file an appeal, or must be accompanied by a by a letter from the owner clearly authorizing tenant or buyer to file the appeal).

#### ADDITIONAL REQUIREMENTS

- 1. Will this application involve the subdivision of land? Applications that involve the subdivision of land are referred to the Planning Commission for review and recommendation. Applicants will be notified of the date and time of the Planning Commission meeting
- 2. Will briefs or memoranda of law be filed in accordance with requirements of the Zoning Hearing Board? (note 10 copies of any brief or memorandum of law to be submitted by the applicant must be received by the Community Development Department no later than 14 days before the hearing).
- 3. Will the applicant (or duly authorized officer of the applicant, if applicant is not a natural person) be present at the hearing. If not, then power of attorney, notarized and in recordable form, authorizing the person who will testify on behalf of the applicant, and to bind the applicant in any proceedings of the Board must be presented at or before commencement of the hearing. Attorneys, agents, or other representatives of the applicant may not appear and testify on behalf of the applicant without power of attorney. Forms of power of attorney are available in the Community Development Department. (note: failure to provide power of attorney will result either in the appeal being discontinued, or being dismissed, at the discretion of the Board)

SIGNATURE OF APPLICANT

AN ADDITIONAL FEE F \$150 SHALL BE CHARGED FOR ANY CONTINUANCE REQUESTED BY THE APPLICANT. THIS FEE SHALL BE PAID PRIOR TO THE RESCHEDULING OF THE HEARING.